

CENTER CORNER SECTION 36, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36006 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36-18-10 DATED DECEMBER 5, 1975, HE SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE NORTHEAST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36-18-10.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 36-18-10 THAT WAS SET BY RUGGLES IN 1916 BY A LARGE CORNER POST
 - 2) 1,320' SOUTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 36-18-10
- 2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 2001, FOR PROJECT NUMBER 01340-02, SURVEY F36009 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF TWO TRACTS IN THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-10, SAID THAT **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 36-18-10 AT THE INTERSECTION OF THE LINES FROM THE NORTH 1/4 CORNER TO THE SOUTH 1/4 CORNER, AND FROM THE SOUTH 1/16TH CORNER OF THE NORTHWEST 1/4 TO THE EAST 1/4 CORNER OF SECTION 36-18-10.
- 1) 15.55' ESE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
 - 2) 4.5' SOUTH TO THE NORTH FACE OF A GAS PIPELINE MARKER POST AT THE GROUND SURFACE
 - 3) 15.40' EAST TO A LINE OF FENCE TO THE SOUTH
 - 4) 4.2' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
 - 5) AT THE TOE OF THE SLOPE [EMBANKMENT] BETWEEN CROP AND PASTURE GROUND

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318.98' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 36-18-10
 - 2) 1,321.36' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10
 - 3) 2,642.72' NORTH TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10 WITH 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH & SOUTH SIDES OF THE STONE
 - 4) 2,644.05' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 36-18-10
 - 5) 2,645.91' SOUTH TO THE GLO STONE SHE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 36-18-10 WITH A 5/8" REBAR WITH A LYON COUNTY CAP BENT OVER THE TOP CENTER OF THE STONE
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2001, FOR PROJECT NUMBER 01414-02, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE CENTER CORNER OF SECTION 36-18-10 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DATED OCTOBER 17, 2001.
- 1) 15.55' ESE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
 - 2) 4.5' SOUTH TO A GAS PIPELINE MARKER
 - 3) 15.4' EAST TO A LINE OF FENCE TO THE SOUTH
 - 4) 4.2' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
 - 5) AT THE TOE OF THE SLOPE BETWEEN CROPS AND PASTURE

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,642.73' NORTH TO THE NORTH 1/4 CORNER OF SECTION 36-18-10
- 2) 2,644.05' EAST TO THE EAST 1/4 CORNER OF SECTION 36-18-10
- 3) 2,645.88' SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 36-18-10

CENTER CORNER 36-18-10