

NORTH 1/16TH CORNER NORTHEAST QUARTER SECTION 36, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY TO LOCATE THE CORNERS OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 25-18-10 DATED JANUARY 19, 1972, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A SPIKE IN THE CENTERLINE OF THE ROAD** FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 25-18-10.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323.50' EAST TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF SECTION 25-18-10 – NOT IDENTIFIED
 - 2) 55' NORTH TO THE IRON PIN SET ON THE RIGHT-OF-WAY LINE
 - 3) 1,314.25' NORTH TO THE IRON PIN SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 25-18-10

- 2) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A SURVEY NOT DATED, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SHOWS THAT **HE FOUND A PIN** AT 1,323.5 FEET WEST OF THE NORTHEAST CORNER OF SECTION 36-18-10, BEING THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 36-18-10.

- 3) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 21, 2014, FOR PROJECT NUMBER 14126-02, SURVEY F36012 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF THE RIGHT-OF-WAY OF THE AMERICUS ROAD IN THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 36-18-10 FOR THE LYON COUNTY ROAD AND BRIDGE DEPARTMENT, SAID THAT **HE SET A 2-1/2" MAG NAIL FLUSH WITH THE ASPHALT ROAD SURFACE** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 36-18-10 ON TRUE LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-18-10.
 - 1) 2.00' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE AMERICUS ROAD EAST-WEST [COUNTY ROAD 200]
 - 2) 5.50' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
 - 3) 45.00' SOUTH TO A 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP
 - 4) 57.25' SE TO THE NORTHWEST CORNER OF A HUBGUARD
 - 5) 59.30' NE TO THE SW CORNER OF A HUBGUARDHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321.69' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 36-18-10
 - 2) 1,321.69' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 36-18-10
 - 3) 42.96' SOUTH TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD 200/AMERICUS ROAD
 - 4) 1,310.05' SOUTH TO THE 1/2" IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 FO SECTION 36-18-10 FROM REFERENCE TIES BY LS 1130 AND 752

- 4) WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 5, 2014, FOR PROJECT NUMBER ADM11, SECTION CORNER RECOVERY, **FOUND THE 2-1/2" MAG NAIL FLUSH WITH THE ASPHALT ROAD SURFACE** AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 36-18-10 FROM THE EXISTING REFERENCE TIES OF STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, DATED NOVEMBER 21, 2014 ON FILE AT THE COUNTY ENGINEERS OFFICE. **I REPLACED THIS MAG NAIL WITH A 5/8" X 5" REBAR WITH A LYON COUNTY CAP SET FLUSH WITH THE ASPHALT**

ROAD SURFACE OF COUNTY ROAD 200/AMERICUS ROAD FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 36-18-10.

- 1) 2.0' TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 200/AMERICUS ROAD EAST-WEST
- 2) 5.50' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 3) 45.0' SOUTH TO A 1/2" X 24" IRON PIN WITH "S. BROSEMER" CAP FOUND
- 4) 57.25' SE TO THE NORTHWEST CORNER OF THE HUBGUARD OF A CONCRETE CULVERT
- 5) 59.30' NE TO THE SOUTHWEST CORNER OF THE HUBGUARD OF A CONCRETE CULVERT
- 6) 56.85' NORTH TO THE TOP CENTERLINE OF THE WEST 6" PIPE BRACE POST
- 7) 65.00' NORTH TO THE TOP CENTERLINE OF THE NORTH 6" PIPE BRACE POST

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 36-18-10