

**NORTH 1/16TH CORNER SOUTHWEST QUARTER SECTION 36, TOWNSHIP 18 SOUTH,  
RANGE 10 EAST**

- 1) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A SURVEY BY THE CONSENT OF THE PARTIES INTERESTED IN SECTION 36-18-10 RECORDED IN SURVEY BOOK "D" ON PAGE 170 COMPLETED ON FEBRUARY 26, 1916, SAID THAT **HE SET A STONE ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 36-18-10 AND THE STONE THAT HE FOUND AT THE SOUTH 1/8<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-18-10 ON THIS CONSENT SURVEY. HE DOES **NOT** CALL THIS STONE THE 1/8<sup>TH</sup> CORNER BETWEEN THE NORTHWEST AND SOUTHWEST QUARTERS OF SECTION 36-18-10, BUT CALLS IT THE MIDDLE POINT ON CHARLES STAATS' 80 ACRE TRACT AND THE SOUTHWEST CORNER OF I. STEISHER'S 120 ACRE TRACT AND THE NORTHWEST CORNER OF B. L. FULLER'S 120 ACRE TRACT.**

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,323.75' NORTH TO THE STONE HE SET FOR THE NORTHEAST CORNER OF CHARLES STAATS' 80 ACRE TRACT AND THE NORTHWEST CORNER OF I. STEISHER'S 120 ACRE TRACT AND THE MIDDLE POINT ON THE SOUTH LINE OF A. O. RUSE'S 80 ACRE TRACT
  - 2) 2,647.50' NORTH TO THE STONE SET FOR THE NORTH 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 36-18-10, AND THE MIDDLE POINT ON THE NORTH LINE OF A. O. RUSE'S 80 ACRE TRACT
  - 3) 1,323.75' SOUTH TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF CHARLES STAATS' 80 ACRE TRACT AND THE NORTHEAST CORNER OF M. A. STANTON'S 40 ACRE TRACT AND THE MIDDLE POINT ON THE WEST LINE OF B. L. FULLER'S 120 ACRE TRACT
  - 4) 2,647.50' SOUTH TO THE STONE FOUND AT THE SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 36-18-10, BEING THE SOUTHEAST CORNER OF M. A. STANTON'S 40 ACRE TRACT AND THE SOUTHWEST CORNER OF B. L. FULLER'S 120 ACRE TRACT
- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36006 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36-18-10 DATED DECEMBER 5, 1975, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE THAT WAS SET BY RUGGLES IN FEBRUARY 1916 BY A LARGE CORNER POST** AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36-18-10.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,646' SOUTH TO THE STONE IN PLACE HE FOUND AT THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 36-18-10 ON THE TOWNSHIP LINE THAT WAS SET BY RUGGLES IN 1916
  - 2) 1,321' EAST TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 36-18-10
- 3) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 2001, FOR PROJECT NUMBER 01340-02, SURVEY F36009 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF TWO TRACTS IN THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-10, SAID THAT SHE CONSIDERED THAT THIS 1/16<sup>TH</sup> CORNER WAS **LOST**. **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-18-10 BY A RETRACEMENT OF A SURVEY BY W. G. RUGGLES ON FILE IN THE OFFICE OF THE COUNTY ENGINEER IN SURVEY BOOK "D" ON PAGES 170-171.
- 1) 2.2' SOUTH TO A FENCE RUNNING WEST
  - 2) 5.15' ESE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
- HER TIES ARE CONTINUED ON PAGE 2

- 3) 4.4' EAST TO A FENCE RUNNING NORTH & SOUTH
- 4) 4.75' SW TO A 40 D NAIL & WASHER IN A HEDGE FENCE POST
- 5) NO OTHER REFERENCES AVAILABLE

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.81' SOUTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-18-10 ON THE TOWNSHIP LINE [ATTRIBUTABLE TO MILES, L.S. 667]
- 2) 1,323.95' NORTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10 [ATTRIBUTABLE TO MILES, L.S. 667]
- 3) 2,645.75' NORTH TO THE 1/2" REBAR WITH "LS 752" CAP SHE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10 [BROSEMER]
- 4) 1,318.98' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36-18-10
- 5) 3,963.03' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 36-18-10

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 36-18-10