

**NORTH 1/4 CORNER SECTION 03, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 73 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 10" X 4"** FOR THE NORTH 1/4 CORNER OF SECTION 3-18-11 ON THE TOWNSHIP LINE ON DECEMBER 13, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 17" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-18-11
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-18-11

- 2) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 2, 2007 FOR PROJECT NUMBER 07343-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3-18-11 FOR ROBERT KARR, SAID THAT HE SEARCHED FOR THE GLO STONE AT THE NORTH 1/4 CORNER OF SECTION 3-18-11 ON THE TOWNSHIP LINE, BUT HE DID **NOT** FIND THE GLO STONE. HE DETERMINED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 3-18-11 ON THE TOWNSHIP LINE BASED ON THE PHYSICAL EVIDENCE [LINES OF FENCE TO THE EAST, WEST AND NORTH] THAT HE FOUND AT THIS CORNER.

- 1) 7.75' EAST TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 2) 25.50' EAST TO A CONCRETE NAIL & WASHER IN THE TOP OF A FENCE POST
- 3) IN LINE WITH A FENCE TO THE NORTH
- 4) IN A LINE OF FENCE RUNNING EAST AND WEST
- 5) ON THE SOUTH SIDE OF A CORNER FENCE POST
- 6) 3.4' SOUTH TO A GUY ANCHOR FOR THE CORNER POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,639.53' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-18-11
- 2) 2,539.98' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 3-18-11—FALLS IN A POND
- 3) 3,863.51' SOUTH TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 3-18-11
- 4) 5,187.04' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 3-18-11
- 5) 2,646.33' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH A "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 3-18-11

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 17, 2010 FOR PROJECT NUMBER 10042-02, SURVEY F03002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF 4 TRACTS IN THE NORTH 1/2 OF SECTION 3-18-11 FOR ROBERT KARR, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 3-18-11 ON THE TOWNSHIP LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE BY AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, DATED OCTOBER 2007.

- 1) 7.75' EAST TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 2) 25.5' EAST TO A CONCRETE NAIL & WASHER IN THE TOP OF A FENCE POST
- 3) IN A LINE OF FENCE TO THE NORTH
- 4) IN A LINE OF FENCE RUNNING EAST-WEST
- 5) ON THE SOUTH SIDE OF A CORNER FENCE POST
- 6) 3.4' SOUTH TO A GUY ANCHOR FOR A CORNER FENCE POST

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,639.46' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-18-11
- 2) 2,646.26' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 3-18-11
- 3) 1,268.87' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF TRACT 2
- 4) 2,539.99' SOUTH TO THE THEORETICAL LOCATION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 3-18-11—FALLS IN A LAKE
- 5) 5,187.14' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 3-18-11

NORTH QUARTER CORNER 03-18-11