

**WEST 1/4 CORNER SECTION 03, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 340 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 17" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-18-11 ON DECEMBER 17, 1856. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 38.10 CHAINS NORTH TO THE 17" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-18-11 ON THE TOWNSHIP LINE
  - 2) 40.00 CHAINS SOUTH TO THE 23" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-18-11
  
- 2) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 2, 2007 FOR PROJECT NUMBER 07343-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3-18-11 FOR ROBERT KARR, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 3-18-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 3-18-11 USING THE ROAD RECORD AND THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.
  - 1) 71.40' SE TO A 40 D NAIL & WASHER IN THE NORTH GATE POST
  - 2) 12.0' NORTH TO A LINE OF FENCE TO THE EAST
  - 3) 25.30' NE TO A 60 D NAIL & WASHER IN A CORNER FENCE POST
  - 4) 20.95' WEST TO A 40 D NAIL & WASHER IN CORNER FENCE POST
  - 5) IN LINE WITH A FENCE TO THE WEST EXTENDED
  - 6) 20.0' WEST TO A LINE OF FENCE RUNNING NORTH
  - 7) IN THE CENTERLINE TRAVELED-WAY FOR COUNTY ROAD "K"HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,509.81' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-18-11 ON THE TOWNSHIP LINE
  - 2) 2,639.33' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 3-18-11 [FALLS IN A POND]
  - 3) 3,964.17' EAST TO THE THEORETICAL POSITION FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 3-18-11
  - 4) 5,289.01' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 3-18-11
  - 5) 2,647.00' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-18-11
  
- 3) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 2, 2007 FOR PROJECT NUMBER 07337-02, SURVEY F04003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TWO TRACTS IN THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 4-18-11, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 4-18-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 4-18-11 USING THE ROAD RECORD AND THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.
  - 1) 71.40' SE TO A 40 D NAIL & WASHER IN THE NORTH GATE POST
  - 2) 12.0' NORTH TO A LINE OF FENCE TO THE EAST
  - 3) 25.30' NE TO A 60 D NAIL & WASHER IN A CORNER FENCE POST
  - 4) 20.95' WEST TO A 40 D NAIL & WASHER IN CORNER FENCE POST

HIS TIES ARE CONTINUED ON PAGE 2

- 5) IN LINE WITH A FENCE TO THE WEST EXTENDED
- 6) 20.0' WEST TO A LINE OF FENCE RUNNING NORTH
- 7) IN THE CENTERLINE TRAVELED-WAY FOR COUNTY ROAD "K"

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,509.81' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 4-18-11 ON THE TOWNSHIP LINE
- 2) 1,323.50' SOUTH TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 4-18-11, BEING THE SOUTHEAST CORNER OF THE 41.91 ACRE SURVEYED TRACT
- 3) 2,647.00' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF SECTION 4-18-11
- 4) 1,380.00' WEST TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR THE NORTHWEST CORNER OF THE 41.91 ACRE SURVEYED TRACT
- 5) 2,644.24' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 4-18-11
- 6) 5,289.31' WEST TO THE THEORETICAL POSITION FOR THE WEST 1/4 CORNER OF SECTION 4-18-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 17, 2010 FOR PROJECT NUMBER 10042-02, SURVEY F03002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF 4 TRACTS IN THE NORTH 1/2 OF SECTION 3-18-11 FOR ROBERT KARR, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 3-18-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE BY AARON C. DAVIS, L.S 1368, DATED OCTOBER 2007.

- 1) 71.4' SE TO A 40 D NAIL & WASHER IN THE NORTH GATE POST
- 2) 12.0' NORTH TO A LINE OF FENCE TO THE EAST
- 3) 25.3' NE TO A 60 D NAIL & WASHER IN A CORNER FENCE POST
- 4) 20.95' WEST TO A 40 D NAIL & WASHER IN CORNER FENCE POST
- 5) IN LINE WITH A FENCE TO THE WEST EXTENDED
- 6) 20' WEST TO A LINE OF FENCE RUNNING NORTH
- 7) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "K"

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,257.60' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF TRACT 1
- 2) 2,509.84' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-18-11 ON THE TOWNSHIP LINE
- 3) 2,308.04' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF TRACT 1 – FALLS IN A LAKE
- 4) 2,639.31' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 3-18-11—FALLS IN A LAKE
- 5) 4,375.99' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF TRACT 4
- 6) 5,288.99' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 3-18-11

WEST QUARTER CORNER 03-18-11