

NORTHWEST CORNER OF SECTION 06, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 50 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 10" X 6"** FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGE 10 & 11 EAST ON NOVEMBER 28, 1856 FOR THE NORTHWEST CORNER OF SECTION 6-18-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 36.48 CHAINS EAST ON THE TOWNSHIP LINE TO THE 14" X 12" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-18-11
 - 2) 76.48 CHAINS EAST ON THE TOWNSHIP LINE TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-18-11
 - 3) 25.21 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 13" X 13" X 6" LIMESTONE THEY SET ON THE SOUTH BOUNDARY OF THE KANSAS INDIAN RESERVATION FOR THE FRACTIONAL CORNER ON THE TOWNSHIP LINE
[NOTE: THIS IS THE NORTHWEST CORNER OF GOVERNMENT LOT 2 OR THE SOUTHWEST CORNER OF GOVERNMENT LOT 8 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 4) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 25" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-18-11
 - 5) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20' X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-18-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR A COUNTY ROAD BETWEEN TOWNSHIPS 17 & 18, RANGE 10 RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 147 DATED AUGUST 24, 1876, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-17-10 ON THE RANGE LINE ON THIS ROAD SURVEY.

THE ROAD IS DESCRIBED AS FOLLOWS:

- 1) COMMENCING AT A POINT 960 FEET NORTH OF THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 28-17-10 [THIS SHOULD BE 25-17-10], I RAN S. 10°30' E. 996 FEET TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 25-17-10; THENCE S. 10°45' E. 2,640 FEET TO THE NORTHEAST CORNER OF SECTION 36-17-10; THENCE S. 10° E. 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 1-18-10, THENCE S. 10° E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 1-18-10 [AT THE TERMINUS OF THIS ROAD SURVEY.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 232 & 233 FOR A PETITION BY J. M. PARRINGTON AND OTHERS FOR CHANGE IN THE "AMERICUS AND ALLEN ROAD" IN TOWNSHIPS 17-10 AND 18-10 AND THE VACATION OF THE OLD ROAD [PACKET 183 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 24, 1876, AND WAS ESTABLISHED ON SEPTEMBER 2, 1876 AND RECORDED IN THE COMMISSIONERS JOURNAL NUMBER 2 ON PAGE 373 AS NOTED ON THE PACKET COVER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-18-10 ON THE RANGE LINE AT THE TOWNSHIP CORNER ON THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT SHOW THE FOLLOWING FOR THE ROAD LOCATED:

- 1) COMMENCING AT A POINT 996 FEET NORTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 25, TOWNSHIP 17, RANGE 10, I RUN S. 10°30' E. 996 FEET TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 25, TOWNSHIP 17, RANGE 10; THENCE S. 10°45' E. 2,640 FEET TO THE NORTHEAST CORNER OF SECTION 36, TOWN SHIP 17, RANGE 10; THENCE SOUTH 10° E. 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 1, TOWNSHIP 17 [SHOULD BE 18], RANGE 10; THENCE S. 10° E. 5,280.0 FEET TO THE SOUTHEAST CORNER OF SECTION 1, TOWNSHIP 18, RANGE 10 AND SUCH PLACE IS THE TERMINATION OF SAID ROAD

- 2) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD FOR THE PUBLIC BENEFIT
 - 3) THE VIEWERS DETERMINED THAT IS SUCH ROAD BE ESTABLISHED THAT ITS WIDTH SHALL BE THIRTY FEET EXCEPT THAT PART WHICH RUNS ALONG THE WEST LINE OF THE CEMETERY, AT WHICH PLACE IT SHALL BE FORTY FEET WIDE, AND ALSO THAT THE HEDGE FENCE ALONG THE EAST SIDE OF THE SOUTHEAST 1/4 OF SECTION 1, TOWNSHIP 18, RANGE 10 SHALL BE THE WEST LINE OF SAID ROAD.
 - 4) THE ROAD PETITIONED TO BE VACATED WAS DESCRIBED AS FOLLOWS: COMMENCING AT A POINT WHERE THE CENTER OF SAID ROAD INTERSECTS THE EAST LINE OF SECTION 25, TOWNSHIP 17, RANGE 10 AND EXTENDING IN A SOUTHWESTERLY DIRECTION OVER THE NE AND SE QUARTERS OF SAID SECTION 25 AND THE NE, NW AND SW QUARTERS OF SECTION 36 TOWNSHIP 17 RANGE 10 TO THE SOUTHWEST CORNER OF SAID SECTION 36, THE PLACE OF TERMINATION
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 57, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 136 DATED AUGUST 26, 1902 FOR A ROAD BETWEEN SECTION 2-18-10 AND 35-17-10 PETITIONED BY W. H. SHOPE, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-18-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-18-10 TO LOCATE THE NORTHEAST CORNER OF SECTION 2-18-10 ON THIS ROAD SURVEY. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 90 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 80.16 CHAINS WEST ON THE TOWNSHIP LINE TO THE **LOCATION** FOR THE NORTHEAST CORNER OF SECTION 2-18-10
 - 2) 83.98 CHAINS WEST ON THE TOWNSHIP LINE TO THE ANGLE STONE HE SET ON THIS ROAD SURVEY
 - 3) 120.49 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-18-10 TO END THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 574 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 161 THROUGH 164 PETITION BY W. H. SHOPE AND OTHERS FOR A ROAD IN TOWNSHIP 18-10 [PACKET 723 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 26, 1902, WAS ESTABLISHED AS A 40 AND 60 FOOT WIDE ROAD BY THE SURVEY NOTES ON OCTOBER 10, 1902, AND RECORDED ON NOVEMBER 23, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-18-10. HE USED THIS STONE ON THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-18-10 TO **LOCATE** THE NORTHEAST CORNER OF SECTION 2-18-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 80.16 CHAINS WEST ON THE TOWNSHIP LINE TO THE **LOCATION** FOR THE NORTHEAST CORNER OF SECTION 2-18-10
 - 2) 83.98 CHAINS WEST ON THE TOWNSHIP LINE TO THE ANGLE STONE HE SET ON THIS ROAD SURVEY
 - 3) 120.49 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-18-10 TO END THIS ROAD SURVEY
- 6) ROAD NUMBER 572 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 153 TO 156: REGISTER OF DEEDS BOOK 73, PAGE 558 RECORDED SEPTEMBER 13, 1902 FROM WILBUR A. LAWTON TO LYON COUNTY FOR ROAD PURPOSES:

A STRIP OF LAND 25 FEET WIDE FROM THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 6-18-11, AND A LIKE STRIP OF LAND 25 FEET WIDE FROM THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 31-17-11, BEING A STRIP OF LAND FIFTY FEET WIDE ON THE SECTION LINE DEEDED FOR ROAD PURPOSES.

- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE “NW CORNER SECTION 06-18-11” AT THE TOWNSHIP CORNER ON THE RANGE LINE.
 - 1) 19’ WEST TO A STONE CORNER POST
 - 2) 28’ NW TO A SPIKE IN A GUY POLE
 - 3) 45.1’ NE TO A SPIKE IN A POWER POLE

- 8) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 27, 1995, **FOUND A STONE 14” NORTH-SOUTH BY 7” EAST-WEST BY 14” TALL LOCATED 4” BELOW THE GRAVEL ROAD SURFACE WITH A 1/2” REBAR ON THE SOUTH SIDE BENT OVER THE TOP OF THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-17-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE FROM TIES IN THE “KRETSINGER COLLECTION” BOOKS. **I SET 5/8” X 24” REBARS WITH LYON COUNTY CAPS ON THE EAST AND WEST SIDES OF THE STONE, WITH THE TOPS OF THE REBARS FLUSH WITH THE TOP OF THE STONE.**
 - 1) 45.1’ NE TO A FOUND 60 D SPIKE IN A POWER POLE
 - 2) 33.9’ SE TO A PK NAIL & WASHER IN A CORNER FENCE POST
 - 3) 23.1’ WNW TO A PK NAIL & WASHER IN THE NORTH GATE POST
 - 4) 27.9’ NW TO A FOUND 60 D SPIKE IN A GUY POLE
 - 5) A FENCE BEARS WEST ON LINE
 - 6) 1’ NORTH TO THE TRAVELED WAY OF COUNTY ROAD 250 TO THE EAST
 - 7) 4’ EAST TO THE TRAVELED WAY OF COUNTY ROAD “G” NORTH-SOUTH

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 19, 1999, FOR JOB NUMBER 98600-02, SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF TWO 5 ACRE TRACTS FOR THE AMERICUS CEMETERY IN GOVERNMENT LOT 8 OF THE NORTHWEST FRACTIONAL QUARTER OF SECTION 6-18-11, SAID THAT **HE FOUND THE STONE WITH A PLUS (“+”) CUT ON ITS CENTER** AT THE NORTHWEST CORNER OF SECTION 6-18-11 AT THE TOWNSHIP CORNER ON THE RANGE LINE FROM TIES OF RECORD IN THE COUNTY ENGINEER’S OFFICE BY CHIP WOODS, L.S. 603, COUNTY SURVEYOR, DATED JUNE 1995.
 - 1) 45.2’ NNE TO A 40 D NAIL & SHINER A IN POWER POLE
 - 2) 27.8’ NNW TO A 40 D NAIL & SHINER IN A POWER POLE
 - 3) IN LINE WITH A FENCE TO THE WEST
 - 4) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 250 TO THE EAST
 - 5) 5.5’ EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD “G” NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 982.08’ SOUTH ON THE RANGE LINE TO THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET FOR THE NORTHWEST CORNER OF TRACT 2
 - 2) 1,312.08’ SOUTH ON THE RANGE LINE TO THE 1/2” REAR WITH HIS “LS 752” CAP HE SET FOR THE NORTHWEST CORNER OF TRACT 1
 - 3) 1,642.08’ SOUTH ON THE RANGE LINE TO THE 1/2” REBAR WITH “LS 82” CAP HE FOUND AT THE SOUTHWEST CORNER OF GOVERNMENT LOT 8 ON THE WEST SIDE OF THE NW1/4 OF SECTION 6-18-11
 - 4) 2,622.08’ SOUTH ON THE RANGE LINE TO THE 1-1/4” REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-18-11

HIS INFORMATION IS CONTINUED ON PAGE 4

- 5) 5,162.09' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "LS 82" CAP HE FOUND AT THE **WITNESS CORNER** LOCATED 100' NORTH OF THE SOUTHWEST CORNER OF SECTION 6-18-11
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 25, 2002, FOR PROJECT NUMBER 02046-02, SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F01018 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SAID THAT **HE FOUND THE STONE WITH A PLUS ("+") CUT** AT THE NORTHWEST CORNER OF SECTION 6-18-11 AT THE TOWNSHIP CORNER ON THE RANGE LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JANUARY 1999.
- 1) 1/2" REBAR BENT ON THE WEST SIDE OF THE STONE
 - 2) 5/8" REBAR WITH LYON COUNTY CAP ON THE EAST SIDE AND FLUSH WITH THE TOP OF THE STONE
 - 3) IN LINE WITH A FENCE LINE AND HEDGE TO THE WEST
 - 4) 18.45' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 27.75' NW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 6) 39.0' SE TO A CONCRETE NAIL & WASHER IN THE EAST FENCE BRACE POST
 - 7) 45.0' NNE TO A 40 D NAIL IN A POWER POLE
 - 8) 6.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,302.61' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 1-18-10
 - 1) 1,647.74' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF LOT 8 ON THE KANSAS INDIAN RESERVE LINE IN THE NORTHEAST 1/4 OF SECTION 6-18-11
 - 2) 2,662.15' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-18-11
 - 3) 5,262.15' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR IN A MONUMENT WELL AT THE SOUTHWEST CORNER OF SECTION 6-18-11
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 19, 2005, FOR PROJECT NUMBER 05231-02, SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, THE SURVEY OF A 10.0 ACRE TRACT IN THE NORTHWEST 1/4 OF SECTION 32-17-10 FOR MICHAEL AND ROXIE PEARSON, SAID THAT **HE FOUND THE STONE WITH A PLUS ("+") CUT IN TOP CENTER** AT THE SOUTHWEST CORNER OF SECTION 31-17-11 AT THE TOWNSHIP CORNER ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES FOR PROJECT NUMBER 02046-02 [2002].
- 1) 1/2" REBAR BENT ON WEST SIDE
 - 2) 5/8" REBAR WITH LYON COUNTY CAP ON THE EAST SIDE FLUSH WITH STONE
 - 3) IN LINE WITH A FENCE LINE AND HEDGE TO THE WEST
 - 4) 18.45' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 27.75' NW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 6) 39.0' SE TO A CONCRETE NAIL & WASHER IN THE EAST FENCE BRACE POST
 - 7) 45.0' NNE TO A 40 D NAIL IN A POWER POLE
 - 8) 6.0' EAST TO THE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH
 - 9) SURVEY COORDINATES: NORTH = -528.489 EAST = -3,321.956
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 1, 2009 FOR PROJECT NUMBER 09227-02 AND SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A SURVEY OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 AND A TRACT IN THE NORTH HALF OF THE SOUTHWEST 1/4 OF SECTION 36-17-10 FOR HANLINE, SAID THAT **HE FOUND THE STONE WITH A PLUS (+) CUT AT THE TOP CENTER** AT THE SOUTHEAST CORNER

OF SECTION 36-17-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED JULY 2005.

- 1) A BENT 1/2" REBAR IS ON THE WEST SIDE OF THE STONE
 - 2) A 5/8" REBAR WITH A LYON COUNTY CAP IS FLUSH WITH THE STONE ON THE EAST SIDE OF THE STONE
 - 3) IN LINE WITH A LINE OF FENCE AND HEDGE ROW TO THE WEST
 - 4) 18.5' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 27.75' NW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 6) 45.0' NNE TO A 40 D NAIL IN A POWER POLE
 - 7) 6.0' EAST TO THE CENTERLINE TRAVELED WAY OF ROAD "G" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.07' WEST ON THE TOWNSHIP LINE TO THE THEORETICAL LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 36-17-10
- 2) 5,301.94' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 36-17-10
- 3) 2,644.21' NORTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 36-17-10
- 4) 5,297.20' NORTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-10

- 13) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 30, 2016 FOR PROJECT NUMBER 16062-02 AND SURVEY F31005 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THE SURVEY OF A 20.00 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 31-17-11 FOR DON REUST, SAID THAT **HE FOUND THE EXISTING RECORD STONE WITH A PLUS (+) CUT ON THE TOP CENTER SAID STONE** AT THE SOUTHWEST CORNER OF SECTION 31-17-11 AT THE TOWNSHIP CORNER ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCE TIES IN 2009 FOR THIS PROJECT NUMBER 09227-02 AND ON FILE AT THE LYON COUNTY ENGINEERS OFFICE. THIS SECTION CORNER IS ALSO THE SOUTHWEST CORNER OF THE 20.00 ACRE TRACT.

- 1) 22.55' WNW TO A PK NAIL & WASHER IN THE NORTH GATE POST
- 2) 27.75' NW TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 45.00' NNE TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) 6.00' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G"
- 5) 4.50' NORTH TO THE CENTERLINE OF ROAD 250 TO THE EAST
- 6) 1/2" IRON BAR BENT ON THE WEST SIDE OF THE STONE
- 7) 5/8" IRON BAR ON THE EAST SIDE OF THE STONE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 645.00' NORTH TO THE 1/3 X 24" IRON BAR WITH HIS "PS 752 S BROSEMER" CAP HE SET FOR THE NORTHWEST TRACT CORNER
- 2) 2,643.91' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 31-17-11
- 3) 1,350.00' EAST ON THE TOWNSHIP LINE TO THE 1/2" X 24" IRON PIN WITH HS "PS 752 S. BROSEMER" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 20.00 ACRE TRACT
- 4) 2,406.60' EAST ON THE TOWNSHIP LINE TO THE 5/8" X 24" IRON BAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 31-17-11
- 5) 10,339.17' EAST ON THE TOWNSHIP LINE TO THE 1/2' IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-17011

NORTHWEST CORNER 06-18-11