

NORTH 1/4 CORNER SECTION 07, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 351 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 36.90 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-18-11 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 12" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-18-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 133 RECORDED IN SURVEY BOOK "A" ON PAGES 216 & 217 DATED AUGUST 4, 1869 TO SURVEY THE NORTHWEST 1/4 OF SECTION 7-18-11, SAID THAT **HE SET A STONE** FOR THE NORTH 1/4 CORNER OF SECTION 7-18-11 ON AT 160 RODS WEST OF THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-18-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 160 RODS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-18-11
 - 2) 140 RODS, 7 LINKS WEST TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE
 - 3) 318 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 7-8-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 42, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 DATED APRIL 4, 1902 ORDERED BY LEVI EMMEL FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF SECTION 7-18-11 AND RUN SUCH OTHER LINES AS ARE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 9' EAST OF A HEDGE** AT THE NORTH 1/4 CORNER OF SECTION 7-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACK "M 146" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNER OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 9 FEET EAST OF A HEDGE** AT THE NORTH 1/4 CORNER OF SECTION 7-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.25 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE, AT 42 LINKS SOUTH AND 35 LINKS EAST OF A HEDGE CORNER
 - 2) 4015 CHAINS EAST TO THE 20" X 12" X 5" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8-18-11, WITH A PIECE OF 1-1/2" GAS PIPE HE SET BY THE SIDE OF THE STONE

- 3) 80.05 CHAINS EAST TO THE THEORETICAL LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11, IN THE MIDDLE OF THE ROAD RUNNING WEST AND ON LINE WITH A FENCE RUNNING NORTH

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 1, 1996, FOR PROJECT 06057-02 [LYON COUNTY PROJECT 96-1M], SAID THAT HE CONSIDERED THAT THE NORTH 1/4 CORNER OF SECTION 7-18-11 WAS **LOST**. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/4 CORNER OF SECTION 7-18-11 ON A PRORATION OF A PERMANENT SURVEY RECORDED IN BOOK "A" ON PAGE 216 IN 1869 BY D. T. McAULEY.
 - 1) 33.00 NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT A RIGHT ANGLE TO THE SECTION LINE
 - 2) 33.00' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT A RIGHT ANGLE TO THE SECTION LINE
 - 3) 8.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 4) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 240 EAST-WEST
 - 5) 22.5' SOUTH TO A LINE OF FENCE TO THE WEST

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

 - 1) 2,326.16' WEST TO THE NORTHWEST CORNER OF SECTION 7-18-11
 - 2) 2,653.17' EAST TO THE NORTHEAST CORNER OF SECTION 7-18-11

- 6) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 21, 1996, **FOUND THE BADLY BENT 1/2" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 7-18-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR DATED JUNE 1996. **I REPLACED THIS BENT REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP**, WITH THE TOP OF THE REBAR AT 7" BELOW THE ROAD SURFACE, AT THE NORTH 1/4 CORNER OF SECTION 7-18-11.
 - 1) 32.9' NORTH TO A FOUND 1/2" REBAR WITH "BROSEMER" CAP
 - 2) 33.2' SOUTH TO A FOUND 1/2" REBAR WITH "BROSEMER" CAP
 - 3) 69.3' SE TO A PK NAIL & WASHER SET IN A POWER POLE
 - 4) 23.9' SSW TO A PK NAIL & WASHER SET IN A CORNER FENCE POST
 - 5) 8.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 6) 6.6' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 240 EAST-WEST

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 28, 1997, SAID THAT **HE SET A COTTON GIN SPINDLE AT THE SURFACE OF THE NEWLY SEALED COUNTY ROAD 240 AND OVER THE REBAR** AT THE NORTH 1/4 CORNER OF SECTION 7-18-11 FROM HIS 1996 TIES.
 - 1) 33.00' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP AT A RIGHT ANGLE TO THE SECTION LINE
 - 2) 33.00' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP AT A RIGHT ANGLE TO THE SECTION LINE
 - 3) 8.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 4) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 240 EAST-WEST
 - 5) 22.5' SOUTH TO A LINE OF FENCE TO THE WEST

- 8) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 11, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS ON COUNTY ASPHALT ROADS, **FOUND THE COTTON GIN SPINDLE FLUSH WITH THE SURFACE OF THE ASPHALT ROAD, AND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 8" BELOW THE ASPHALT ROAD SURFACE** AT THE NORTH 1/4 CORNER OF SECTION

7-18-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY THE TIES OF STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR DATED AUGUST 1997 AND MY TIES DATED AUGUST 1996. I LOWERED THE ORIGINAL BAR, AND I SET A 5/8" X 11" REBAR WITH A LYON COUNTY CAP ON TOP OF THE REBAR AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE ASPHALT SURFACE OF ROAD 240 AT THE NORTH 1/4 CORNER OF SECTION 7-18-11.

- 1) 24.0' SSW TO A PK NAIL & WASHER IN THE WEST FACE OF A CORNER FENCE POST
- 2) 69.3' ESE TO A PK NAIL & WASHER IN THE NORTH FACE OF A POWER POLE
- 3) 31.5' NW TO A MAG NAIL & WASHER IN THE SOUTHWEST FACE OF A CORNER FENCE POST
- 4) 28.6' NE TO A MAG NAIL & WASHER IN THE EAST FACE OF A GATE POST
- 5) 17.5' WEST TO A LINE OF FENCE TO THE NORTH
- 6) 6' WEST TO A LINE OF FENCE TO THE SOUTH
- 7) 4' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ASPHALT ROAD 240 EAST-WEST

NORTH QUARTER CORNER 07-18-11