

**NORTHWEST CORNER SECTION 07, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 49 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE CORNER TO SECTIONS 6 & 7-18-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 28, 1856.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 25" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-18-11
  - 2) 54.79 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 13" X 13" X 6" LIMESTONE THEY SET ON THE SOUTH BOUNDARY OF THE KANSAS INDIAN RESERVATION [**NOTE:** THIS IS THE NORTHWEST CORNER OF GOVERNMENT LOT 2 OR THE SOUTHWEST CORNER OF GOVERNMENT LOT 8 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
  - 3) 80.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-18-11
  - 4) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 34" X 12" X 4" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-18-11
  - 5) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 27" X 9" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-18-11
  - 6) 36.90 CHAINS EAST TO THE 24" X 16" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-18-11
  - 7) 76.90 CHAINS EAST TO THE 12" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-18-11
  
- 2) WILLIAM PERRY, SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 28 [PACKET 391 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "AMERICUS AND DUCK CREEK ROAD" THAT WAS SURVEYED MAY 3-5, 1859 AND ESTABLISHED ON NOVEMBER 15, 1859 IN THE COMMISSIONERS JOURNAL ON PAGE 79, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 6-18-11 ON THE RANGE LINE ON THIS ROAD SURVEY. A PENCIL NOTES STATES: "ROAD 66' WIDE LEGAL WIDTH TER. LAW 1859. W. S. R."  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 1-81-0 TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO AN ANGLE POINT TO THE SOUTHEASTERLY AT 181.50 CHAINS EAST OF THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 1-18-10 IN THE NE1/4 OF SECTION 8-18-11
  
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 133 RECORDED IN SURVEY BOOK "A" ON PAGES 216 & 217 DATED AUGUST 4, 1869 TO SURVEY THE NORTHWEST 1/4 OF SECTION 7-18-11, SAID THAT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE WAS **LOST**. HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-18-11 TO THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 7-18-11. HE SAID THAT HE "MADE THE PROPER CORRECTION DIVIDING THE DEFICIT BETWEEN THE TWO SECTIONS, AND AT THAT POINT" **HE SET THE STONE** FOR THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 140 RODS, 7 LINKS EAST TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 7-18-11
  - 2) 300 RODS, 7 LINKS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-18-11

CONTINUED ON PAGE 2

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 232 & 233 FOR A PETITION BY J. M. PARRINGTON AND OTHERS FOR CHANGE IN THE "AMERICUS AND ALLEN ROAD" IN TOWNSHIP 17-10 [PACKET 183 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 24, 1876, AND WAS ESTABLISHED ON SEPTEMBER 2, 1876 AS RECORDED IN THE COMMISSIONERS JOURNAL NUMBER 2 ON PAGE 373, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-18-10 ON THE RANGE LINE AT THE INTERSECTION OF THE ROAD LEADING EAST FROM AMERICUS FOR THE TERMINATION OF THIS ROAD SURVEY. THE ROAD WAS TO BE "30 FEET WIDE EXCEPT THAT PART THAT RUNS ALONG THE WEST SIDE OF THE CEMETERY [BETWEEN SECTIONS 1-18-10 AND 6-18-11] AT SUCH PLACE IT SHALL BE 40 FEET WIDE AND ALSO THAT THE HEDGE FENCE ALONG THE EAST SIDE OF THE SOUTHEAST 1/4 OF SECTION **1-17-10** SHALL BE THE WEST LINE OF SAID ROAD". **[NOTE:** THIS SHOULD BE SECTION **1-18-10** ACCORDING TO THE SURVEY PLAT – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] SEE THE INFORMATION IN PACKET 183 FOR THE PORTION OF THE ROAD THAT WAS **VACATED**. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 5,280' TO THE NORTHEAST CORNER OF SECTION 1-18-10 AT THE TOWNSHIP CORNER; THEN CONTINUES NORTH ON THE RANGE LINE FOR 5,280' TO THE NORTHEAST CORNER OF SECTION 36-17-10; THEN CONTINUES NORTH ON THE RANGE LINE FOR 2,640' TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 25-17-10; THEN CONTINUES NORTH ON THE RANGE LINE FOR 996 FEET TO WHERE THE "AMERICUS AND ALLEN" ROAD CROSSES THE EAST LINE OF SECTION 25-17-10 AND THE COMMENCEMENT OF THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 147 DATED AUGUST 24, 1876, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-18-10 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 172, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 172 DATED JUNE 7-15, 1887 ORDERED BY O. C. BREWSTER TO LOCATE THE CORNERS OF THE SOUTHEAST 1/4 OF SECTION 13-18-10, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 12-18-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,285' SOUTH ON THE RANGE LINE TO THE REMAINS OF THE STONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 13-18-10
  - 2) 7,925' SOUTH ON THE RANGE LINE TO THE 6" X 6" X 28" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 13-18-10 WHERE HE FOUND THE REMAINS OF THE OLD STONE AND AN OLD STAKE
  - 3) 10,565' SOUTH ON THE RANGE LINE TO THE 7" X 8" X 22" LIMESTONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-10
  - 4) 15,845' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-18-10
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 441 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 29 THROUGH 32 FOR ROAD NUMBER 441 PETITIONED BY LEVI EMMET AND OTHERS FOR A ROAD ON THE RANGE LINE BETWEEN TOWNSHIPS 18-10 AND 18-11 [PACKET 724 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1898, WAS ESTABLISHED AS 40 FOOT WIDE ROAD, EXCEPT THE HEDGE ROW NEAR THE WEST LINE OF THE NW1/4 OF SECTION 7-18-11 SHALL

BE THE EAST LINE OF THE ROAD. ALSO THERE SHALL ONLY BE TAKEN A STRIP OF LAND 18 FEET WIDE OFF OF THE WEST SIDE OF THE SW1/4 OF SECTION 7-18-11, ON JULY 9, 1898 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JANUARY 4, 1900 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT HE FOUND THE STONE AT THE NORTHEAST CORNER OF SECTION 12-18-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
  
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 42 LINKS SOUTH AND 35 LINKS EAST OF A HEDGE CORNER** AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.25 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 7-18-11 AT 9 FEET EAST OF A HEDGE
  - 2) 79.40 CHAINS EAST TO THE 20" X 12" X 5" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8-18-11 WITH A PIECE OF 1-1/2" DIAMETER GAS PIPE HE SET BY THE SIDE OF THE STONE
  - 3) 119.30 CHAINS EAST TO THE THEORETICAL LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11 IN THE MIDDLE OF THE ROAD RUNNING WEST AND ON LINE WITH A FENCE RUNNING NORTH
- 9) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 97 AT THE TOP OF THE PAGE SHOWS A **3/4" IRON PIN** AT THE "NW CORNER SECTION 7-18-11" ON THE RANGE LINE.
    - 1) 31.0' NW TO THE NEAR CORNER OF THE WEST CONCRETE HEADWALL
    - 2) 26.6' NNE TO THE NEAR CORNER OF THE EAST CONCRETE HEADWALL
  
  - 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **REA PIN** AT THE "NW CORNER SECTION 7-18-11" ON THE RANGE LINE.
    - 1) 31.0' NW TO THE NEAR CORNER [SOUTHWEST] OF THE HEADWALL
    - 2) 26.6' NORTH TO THE NEAR CORNER OF THE HEADWALL
  
  - 11) MELVIN B. HENSLEY, L.S. 206, IN LARGE SURVEY SR#01004 IN THE SURVEY DRAWER FOR TOWNSHIP 18-10 FOR A PLAT OF TRACTS IN THE SE1/4 OF THE SE1/4 OF SECTION 1-18-10 DATED MAY 10, 1978 AND RECORDED IN THE REGISTER OF DEEDS OFFICE IN VOLUME 2 OF PLATS ON PAGE 77 ON OCTOBER 12, 1978, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE SOUTHEAST CORNER OF SECTION 1-18-10 ON THE RANGE LINE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 4

- 1) 1,363.44' WEST TO THE IRON PIN AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 1-18-10
  - 2) 1,353.00' NORTH ON THE RANGE LINE TO THE IRON PIN AT THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 1-18-10
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 1, 1996, FOR PROJECT NUMBER 96057-02 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR ROAD IMPROVEMENT PROJECT 96-1M, SAID THAT **HE FOUND A 1-1/4" REBAR AT 12" BELOW THE ROAD SURFACE** AT THE SOUTHWEST CORNER OF SECTION 6-18-11 ON THE RANGE LINE. HE SAID THAT **NO STONE** WAS FOUND UNDER THE REBAR.
- 1) 34.1' NW TO THE NORTHWEST CORNER NORTHEAST CORNER HEADWALL
  - 2) 30.1' NE TO THE NORTHEAST CORNER NORTHWEST CORNER HEADWALL
  - 3) 1/2" REBAR W/ HIS CAP 100.00' SOUTH ON LINE WITH THE WEST 1/4 OF 7-18-11
  - 4) 1/2" REBAR WITH HIS CAP 10.00' NORTH ON LINE WITH THE WEST 1/4 OF 6-18-11
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,326.16' EAST TO THE SOUTH 1/4 CORNER OF SECTION 6-18-11
  - 2) 5,285.33' EAST TO THE SOUTHEAST CORNER OF SECTION 6-18-11
  - 3) 2,640.36' NORTH ON THE RANGE LINE TO THE WEST 1/4 CORNER OF SEC. 6-18-11
  - 4) 3,614.88' NORTH ON THE RANGE LINE TO THE NORTHWEST CORNER OF LOT 2
  - 5) 2,640.36' SOUTH ON THE RANGE LINE TO THE WEST 1/4 CORNER OF SEC. 7-18-11
  - 6) 5,276.02' SOUTH ON THE RANGE LINE TO THE SOUTHWEST CORNER OF SECTION 7-18-11
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 28, 1997, FOR PROJECT NUMBER 97073-03, SAID THAT **HE SET A COTTON GIN SPINDLE AT THE SURFACE OF NEWLY SEALED COUNTY ROAD 240 AND OVER THE REBAR HE FOUND AT THE** NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE.
- 1) 34.1' NW TO THE NORTHWEST CORNER OF THE NORTHEAST HEADWALL
  - 2) 30.1' NE TO THE NORTHEAST CORNER OF THE NORTHWEST HEADWALL
  - 3) 1/2" REBAR WITH HIS "LS 752" CAP HE SET 100.00' SOUTH ON LINE WITH THE WEST 1/4 CORNER OF SECTION 7-18-11
  - 4) 1/2" REBAR WITH HIS "LS 752" CAP HE SET 100.00' NORTH ON LINE WITH THE WEST 1/4 CORNER OF SECTION 6-18-11
- 14) POLLY A. JONES, L.S. 1130, IN SURVEY F12017 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A 3.24 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 12-18-10 DATED MAY 19, 2000 FOR PROJECT NUMBER 99517-02 SAID THAT SHE REESTABLISHED THE NORTHEAST CORNER OF SECTION 12-18-10 FROM WITNESS CORNERS PREVIOUSLY SET TO REFERENCE THE CORNER PRIOR TO THE ROAD CONSTRUCTION. **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHEAST CORNER OF SECTION 12-18-10 ON THE RANGE LINE. SEE ALSO SURVEY **F12018** IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR PROJECT NUMBER 01345-02 DATED DECEMBER 12, 2002 FOR AN ADDITIONAL 2.04 ACRE TRACT ADDED TO THE ORIGINAL 2000 SURVEYED TRACT. HER TIES ARE MISSING FROM THE SURVEY TIE FILES.
- SURVEY DRAWING F12017 SHOWS THE FOLLOWING INFORMATION:
- 1) 1,262.82' WEST TO THE COTTON GIN SPINDLE SHE SET FOR THE NORTHEAST CORNER OF THE 2.904 ACRE TRACT
  - 2) 1,709.82' WEST TO THE COTTON GIN SPINDLE SHE SET FOR THE NORTHWEST CORNER OF THE 2.904 ACRE TRACT
  - 3) 2,627.53' WEST TO THE 1-1/4" REBAR SHE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 12-18-11
  - 4) 99.95' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE **WITNESS CORNER**
- HER INFORMATION IS CONTINUED ON PAGE 5

- 5) 99.95' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE **WITNESS CORNER**
  - 6) 2,640.36' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-18-11
- HER SURVEY DRAWING F12018 SHOWS THE FOLLOWING INFORMATION:
- 1) 1,187.82' WEST TO THE COTTON GIN SPINDLE SHE SET FOR THE NORTHEAST CORNER OF THE ADDITIONAL SURVEYED TRACT
  - 2) 1,262.82' WEST TO THE COTTON GIN SPINDLE SHE FOUND AT THE NORTHEAST CORNER OF THE PREVIOUSLY SURVEYED TRACT FROM HER PREVIOUS SURVEY
  - 3) 1,709.82' WEST TO THE COTTON GIN SHE FOUND AT THE NORTHWEST CORNER OF THE PREVIOUSLY SURVEYED TRACT FROM HER PREVIOUS SURVEY
  - 4) 2,627.53' WEST TO THE 1-1/4" REBAR SHE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 12-18-11
  - 5) 99.95' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE **WITNESS CORNER**
  - 6) 99.95' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE **WITNESS CORNER**
  - 7) 2,640.46' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-18-11
- 15) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 10, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND THE 1-1/4" REBAR AT 14" BELOW THE ASPHALT ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DATED MAY 2000. **I SET A 5/8" X 12" REBAR WITH A LYON COUNTY CAP ON TOP OF THE 1-1/4" REBAR, AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF COUNTY ASPHALT ROAD 240** AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE.
- 1) 28.8' SE TO A SET MAG NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
  - 2) 47.3' SE TO A FOUND NAIL & WASHER IN THE WEST FACE OF A POWER POLE
  - 3) 38.6' SW TO A FOUND NAIL & WASHER IN THE EAST FACE OF A POWER POLE
  - 4) 28.1' NW TO A PLUS (+) CUT IN THE EAST HEADWALL OF A RCB CULVERT
  - 5) 3' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" TO THE NORTH
  - 6) 5.5' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" TO THE SOUTH
  - 7) IN THE TRAVELED WAY OF ASPHALT COUNTY ROAD 240 EAST-WEST
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 25, 2002, FOR PROJECT NUMBER 02046-02, SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F01018 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SAID THAT HE FOUND THE **5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT BOX** AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE
- 1) 47.25' SE TO A PK NAIL IN A POWER POLE
  - 2) 38.6' SW TO A PK NAIL IN A POWER POLE
  - 3) 28.1' NW TO A "+" CUT ON THE EAST-WEST HEADWALL FOR CONCRETE BOX
  - 4) 30.15' NE TO THE NORTHEAST CORNER OF THE NORTH-SOUTH HEADWALL FOR A CONCRETE BOX
  - 5) IN THE CENTERLINE TRAVELED WAY OF ASPHALT COUNTY ROAD 240 EAST-WEST

HIS TIES ARE CONTINUED ON PAGE 6

- 6) 3.0' WEST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,726.63' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTH 1/4 CORNER OF SEC. 12-18-10
- 2) 5,418.89' WEST TO THE 1-1/4" IRON PIN HE FOUND OVER THE STONE AT THE NORTHWEST CORNER OF SECTION 12-18-10
- 3) 2,640.32' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 7-18-11
- 4) 5,276.38' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-18-11

- 17) RICHARD J. IMAN, L.S. 1450, OF BG CONSULTANTS, INC. IN A LAND SURVEY REFERENCE REPORT DATED MAY 28, 2010 FOR PROJECT NUMBER 09-1302E, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE NORTHEAST CORNER OF SECTION 12-18-10 ON THE RANGE LINE FROM USING REFERENCES BY CHIP WOODS DATED 7-10-2001.

- 1) 28.4' SE TO A FOUND MAG NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 2) 47.2' SE TO A FOUND NAIL & WASHER IN THE WEST FACE OF A POWER POLE
- 3) 38.6' SW TO A FOND NAIL & WASHER IN THE EAST FACE OF A POWER POLE
- 4) ON THE TRAVELED WAY OF EAST-WEST ASPHALT COUNTY ROAD 240
- 5) 3' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" TO THE NORTH
- 6) 3.5' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G5" TO THE SOUTH

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 20, 2011 FOR PROJECT NUMBER 11135-02, SURVEY F12021 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THREE TRACTS IN THE NORTHEAST 1/4 OF SECTION 12-18-10 FOR CLAUDE ROSWURM, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE NORTHEAST CORNER OF SECTION 12-18-10 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) 4.0' WEST TO THE TRAVELED WAY OF COUNTY ROAD "G" TO THE NORTH
- 2) 5.5' WEST TO THE TRAVELED WAY OF COUNTY ROAD "G" TO THE SOUTH
- 3) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 240 EAST-WEST
- 4) 28.4' SE TO A MAG NAIL IN THE TOP OF A CORNER FENCE POST
- 5) 38.6' SW TO A SPIKE & WASHER IN THE EAST FACE OF A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,726.38' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 12-18-10
- 2) 2,640.50' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 12-18-10

NORTHWEST CORNER 07-18-11