

CENTER CORNER OF SECTION 08, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 AND DATED MARCH 1868, SAID THAT HE RAN THE LINES FROM THE OPPOSITE 1/4 CORNERS. HE SET A TEMPORARY POST AT 160 RODS WEST OF THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 8-18-11, AND A TEMPORARY POST AT 160 RODS NORTH OF THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11. THE TEMPORARY POSTS WERE NOT AT THE SAME POINT, SO HE PROJECTED ANGLES AND BROUGHT THEM TO THE SAME PLACE, AND AT THAT POINT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 8-18-11.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 16" X 12" X 4" STONE WITH A RAILROAD LINK BY THE SIDE OF THE STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11 ON LINE BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-18-11 AND THE McAULEY STONE THAT HE FOUND AT THE NORTH 1/8TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 8-18-11 AND AT THE PRORATED DISTANCE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.98 CHAINS EAST TO THE McAULEY STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 8-18-11
 - 2) 39.96 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 8-18-11
 - 3) 39.96 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-18-11
 - 4) 39.56 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11
 - 5) 40.21 CHAINS NORTH TO THE THEORETICAL LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11 IN THE MIDDLE OF THE ROAD RUNNING WEST AND IN LINE WITH A FENCE RUNNING NORTH

- 3) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT **HE SET AN IRON PIN** FOR THE CENTER CORNER OF SECTION 8-18-11 ON THIS **INFORMAL SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,637.36' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-18-11
 - 2) 2,653.9' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11
 - 3) 1,318.68' EAST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-18-11
 - 3) 2,611.0' SOUTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 17-18-11

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS AN **IRON PIN** AT THE "SW CORNER NE1/4 SECTION 8-18-11".
- 1) 29' NE TO AN IRON PIN
- 5) LLOYD J. DOBLER, L.S. 541, IN A SURVEY DATED DECEMBER 1977 FOR WAYNE JONES, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF THE WEST 1980 FEET OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11 DATED DECEMBER 1977, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE CENTER CORNER OF SECTION 8-18-11. HE DOES NOT INDICATE THE METHODOLOGY HE USED TO DETERMINE THE LOCATION FOR THE CORNER AND HE DOES NOT DESCRIBE THE IRON PIN OR HAVE ANY TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. **VERIFY AND CHECK BEFORE USING!!**
- WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR**
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,326.95' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-18-11
 - 2) 2,653.90' NORTH TO THE IRON PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11
 - 3) 1,318.68' EAST TO THE FOUND STONE "PER COUNTY RECORDS"
 - 4) 1,980.00' EAST TO THE PIN HE SET FOR THE SOUTHEAST CORNER OF THE WEST 1980 FEET OF THE S1/2 OF THE NE1/4 OF SECTION 8-18-11

CENTER CORNER 08-18-11