

**NORTH 1/4 CORNER SECTION 08, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 351 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-8-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.75 CHAINS WEST TO THE 12" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-18-11
- 2) 39.75 CHAINS EAST TO THE 18" X 16" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-18-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 319 RODS, 12 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11

- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 60 DATED JUNE 13, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 11 FOR JOHN B. MILLER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE 1/4 SECTION LINE FOR 7.28 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 78° E. FOR 9.55 CHAINS TO AN ANGLE STONE HE SET; THENCE S. 69°10' E. FOR 7.00 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 64°20' E. FOR 25.59 CHAINS EAST TO AN ANGLE STONE HE SET ON THE SECTION LINE; THENCE NORTH ON THE SECTION LINE FOR 2.61 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 52°10' E. ABOUT 4 CHAINS ACROSS ALLEN CREEK [THE CREEK BEING TOO FULL TO ADMIT A CROSSING THE LAST DISTANCE WAS ASSUMED] TO AN ANGLE STONE HE SET ON THE SECTION LINE ABOUT 3 CHAINS EAST OF THE NORTHEAST CORNER OF SECTION 8-18-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 228 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 498 TO 500 PETITIONED BY JOHN B. MILLER AND OTHERS FOR CHANGING AND LOCATING A COUNTY ROAD IN TOWNSHIP 18-11 [PACKET 453 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13 1883, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 6, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 SECTION CORNER OF SECTION 8-18-11 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 2) THIS ROAD EXTENDS SOUTH ON THE 1/4 SECTION LINE FOR 7.28 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 78° E. FOR 9.55 CHAINS TO AN ANGLE STONE HE SET; THENCE S. 69°10' E. FOR 7.00 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 64°20' E. FOR 25.59 CHAINS EAST TO AN ANGLE STONE HE SET ON THE SECTION LINE; THENCE NORTH ON THE SECTION LINE FOR 2.61 CHAINS TO

AN ANGLE STONE HE SET; THENCE N. 52°10' E. ABOUT 4 CHAINS ACROSS ALLEN CREEK [THE CREEK BEING TOO FULL TO ADMIT A CROSSING THE LAST DISTANCE WAS ASSUMED] TO AN ANGLE STONE HE SET ON THE SECTION LINE ABOUT 3 CHAINS EAST OF THE NORTHEAST CORNER OF SECTION 8-18-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 107, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 107 DATED JUNE 5, 1885 FOR G. W. WHITE, PRINCIPLE PETITIONER FOR A ROAD IN SECTION 8-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE QUARTER LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 302 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 158 TO 160 PETITIONED BY G. W. WHITE AND OTHERS FOR A COUNTY ROAD IN SECTION 8-18-11 [PACKET 533 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 5, 1885, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 9, 1885 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 23, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE 1/4 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 OVER THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11, AND AT 79.77 CHAINS HE INTERSECTED THE MIDDLE OF A 50 FOOT ROAD RUNNING WEST AND ON LINE WITH A FENCE RUNNING NORTH, BUT HE DID **NOT** RESET THE NORTH 1/4 CORNER OF SECTION 8-18-11 ON THIS SURVEY. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.90 CHAINS WEST TO THE 20" X 12" X 5" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8-18-11, WITH A PIECE OF 1-1/2" GAS PIPE HE SET BY THE SIDE OF THE STONE
- 2) 80.05 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 7-17-11
- 3) 119.30 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE

HIS INFORMATION IS CONTINUED ON PAGE 3

- 4) 40.21 CHAINS SOUTH TO THE 16" X 12" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11, WITH A RAILROAD LINK HE SET BY THE SIDE OF THE STONE
  - 5) 79.77 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11
- 8) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT HE USED THE STONES THAT HE FOUND AS RECORDED IN SURVEYS BY ALVA J. SMITH IN APRIL AND AUGUST OF 1902 IN SECTION 8-18-11, AND **HE SET AN IRON PIN** FOR THE NORTH 1/4 OF SECTION 8-18-11 ON THIS **INFORMAL SURVEY**. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,653.9' SOUTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-18-11
  - 2) 5,264.9' SOUTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 17-17-11
  - 3) 7,913.9' SOUTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 17-17-11 IN ACCORDANCE WITH PREVIOUS SURVEY BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS
  - 4) 10,560.9' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 17-17-11 IN ACCORDANCE WITH PREVIOUS SURVEYS BY PARKMAN, SMITH, MILLIKEN AND ALL OTHER PREVIOUS COUNTY SURVEYORS
- 9) LLOYD J. DOBLER, L.S. 541, IN A SURVEY DATED DECEMBER 1977 FOR WAYNE JONES, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF THE WEST 1980 FEET OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND AN IRON PIN "PER COUNTY RECORDS"** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11. HE DOES NOT DESCRIBE THE IRON PIN OR HAVE ANY TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,326.95' SOUTH TO THE PIN HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-18-11
  - 2) 2,653.90' SOUTH TO THE PIN HE SET FOR THE CENTER CORNER OF SEC. 8-18-11
- 10) LLOYD J. DOBLER, L.S. 541, IN A SURVEY DATED APRIL 1978 FOR IMOGENE KERNS, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 7.44 ACRE TRACT IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11, SHOWS ON HIS SURVEY DRAWING A **"MONUMENT"** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 8-18-11. HE DOES NOT DESCRIBE THE MONUMENT OR HAVE ANY TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,326.95' SOUTH TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 8-18-11 – NOT DESCRIBED
- 11) JAMES D. SCHMITZ, L.S. 727, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 8, 1992, SURVEY F08003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A PROPOSED EQUIPMENT STATION EASEMENT FOR BEST COMMUNICATIONS IN THE NORTHWEST 1/4 OF SECTION 8-18-11, SAID THAT **HE FOUND A 3/4" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 IN A NORTH-SOUTH FENCE LINE AT THE NORTH 1/4 CORNER OF SECTION 8-18-11.
- 1) 14.35' WEST TO A PK NAIL & BOTTLECAP IN THE NORTH SIDE OF AN 18" HACK-BERRY TREE

HIS TIES ARE CONTINUED ON PAGE 4

- 2) 19.69' WNW TO A PK NAIL & BOTTLECAP IN THE NORTH SIDE OF AN 18" HACK-BERRY TREE
- 3) 21.04' EAST TO A PK NAIL & BOTTLECAP IN THE NORTH SIDE OF AN 8" LOCUST TREE
- 4) 19.6' NNW TO THE BOTTOM OF A FENCE CORNER POST FOR FENCES WEST-NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,625.31' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-18-11
  - 2) 1,320.98' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 8-18-11 [DOBLER = 1,326.95' ON RECORD SURVEY DATED DECEMBER 1977]
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED MAY 1, 1995, FOR JOB NUMBER 95017-02, SAID THAT **HE FOUND THE 3/4" REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 5-18-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) THIS CORNER IS IN A LINE OF NORTH-SOUTH FENCE
  - 2) 21.1' EAST TO A PK NAIL & BOTTLE CAP IN THE NORTH SIDE OF A 10" LOCUST
  - 3) 49.8' NE TO A PK NAIL IN A 66" HEDGE TREE
  - 4) 14.4' WEST TO A PK NAIL & BOTTLE CAP IN A 20" HACKBERRY TREE
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,625.76' WEST TO THE SOUTHWEST CORNER OF SECTION 5-18-11
  - 2) 2,639.74' EAST TO THE LOCATION FOR THE SOUTHEAST CORNER OF SECTION 5-18-11
  - 3) 5,286.13' EAST TO THE SOUTH 1/4 CORNER OF SECTION 4-18-11
  - 4) 7,918.37' EAST TO THE SOUTHEAST CORNER OF SECTION 4-18-11
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 1, 2007, FOR PROJECT NUMBER 07375-02, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MAY 1995.
- 1) THIS CORNER IS IN A LINE OF FENCE NORTH-SOUTH
  - 2) 21.1' EAST TO A PK NAIL & BOTTLE CAP IN THE NORTH SIDE OF A 10" LOCUST
  - 3) 14.4' WEST TO A PK NAIL & BOTTLE CAP IN A 20" HACKBERRY TREE
  - 4) A SURVEY SIGN POST IS ON THE EAST SIDE OF THE BAR

NORTH QUARTER CORNER 08-18-11