

WEST 1/4 CORNER OF SECTION 08, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 350 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 15" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-18-11.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 8-18-11 ON THIS SURVEY.
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 133 RECORDED IN SURVEY BOOK "A" ON PAGES 216 & 217 DATED AUGUST 4, 1869 TO SURVEY THE NORTHWEST 1/4 OF SECTION 7-18-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 7-18-11 ON THIS SURVEY.
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 117 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 39 DATED AUGUST 10, 1873 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE OF SECTION 18, THE NORTHEAST CORNER OF SECTION 18, THE CENTER CORNER, AND TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE EAST AND WEST, ALL IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,640' SOUTH TO THE OLD STONE HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 8-18-11
 - 2) 5,280' SOUTH TO THE OLD STONE HE FOUND AND **HE RESET** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-18-11
 - 3) 7,920' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-18-11
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 42, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 DATED APRIL 4, 1902 ORDERED BY LEVI EMMEL FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF SECTION 7-18-11 AND RUN SUCH OTHER LINES AS ARE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A 12" X 12" X 5" SANDSTONE WITH A 14" PIECE OF 1-1/2" GAS PIPE BY THE STONE AT 2 FEET EAST OF AN OLD FENCE LINE AND 25 LINKS EAST OF A HEDGE** ACCORDING TO THE AFFIDAVIT OF H. F. LAMB AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 7-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 146" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.11 CHAINS SOUTH TO THE 22" X 12" X 3" STONE, WITH THE CASTING FROM A WELL PULLEY IN THE HOLE WITH THE STONE, HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 7-18-11
 - 2) 80.25 CHAINS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 120.33 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-18-11
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8-18-11, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE [WITH A 1-1/2" GAS PIPE BESIDE IT AT 2 FEET EAST OF AN OLD FENCE LINE AND 25 LINKS EAST OF A HEDGE]** AT THE WEST 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 20.05-1/2 CHAINS NORTH TO THE STONE 12" X 8" X 8" HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 8-18-11
 - 2) 40.11 CHAINS NORTH TO THE 20" X 12" X 5" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8-18-11, WITH A PIECE OF 1-1/2" GAS PIPE HE SET BY THE SIDE OF THE STONE
 - 3) 40.11 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11
 - 4) 39.96 CHAINS EAST TO THE 16" X 12" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11, WITH A RAILROAD LINK HE SET BY THE SIDE OF THE STONE
 - 5) 59.94 CHAINS EAST TO THE McAULEY STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 8-18-11
 - 6) 79.92 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 8-18-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 116, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 197 DATED FEBRUARY 14, 1905 FOR J. M. HUMPHREY, PRINCIPAL PETITIONER FOR A ROAD BETWEEN SECTIONS 7 & 8, TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE [WITH A 1-1/2" GAS PIPE BESIDE IT AT 2 FEET EAST OF AN OLD FENCE LINE AND 25 LINKS EAST OF A HEDGE]** AT THE WEST 1/4 CORNER OF SECTION 8-18-11 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, LYING 20 FEET EACH SIDE OF THE SECTION LINE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH OF THE SECTION LINES FOR 20.05-1/2 CHAINS TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 8-18-11, THEN CONTINUES NORTH ON THE SECTION LINES FOR 20-05-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 595 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 249 THROUGH 252 PETITION BY J. H. HUMPHRY AND OTHERS FOR A ROAD BETWEEN SECTIONS 7 & 8-18-11 [PACKET 747 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 14, 1905, WAS GRANTED

AS A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE, ON APRIL 7, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON FEBRUARY 20, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE [WITH A 1-1/4" GAS PIPE BESIDE IT AT 2 FEET EAST OF AN OLD FENCE LINE AND 25 LINKS EAST OF A HEDGE]** AT THE WEST 1/4 CORNER OF SECTION 8-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH OF THE SECTION LINES FOR 20.05-1/2 CHAINS TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 8-18-11, THEN CONTINUES NORTH ON THE SECTION LINES FOR 20-05-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 9) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20-18-11, SAID THAT **HE FOUND THE STONE THAT WAS SET BY ALVA J. SMITH IN SURVEYS RECORDED IN APRIL & AUGUST 1902** AT THE WEST 1/4 OF SECTION 8-18-11 ON THIS INFORMAL SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.6' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 8-18-11, THAT WAS SET BY ALVA J. SMITH
 - 2) 2,647.2' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF SECTION 8-18-11, ACCORDING TO THE SURVEYS BY ALVA J. SMITH
 - 3) 2,647.3' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-18-11
 - 4) 5,296.5' SOUTH TO THE IRON PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 17-18-11
 - 5) 7,943.0' SOUTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-18-11
 - 6) 10,616.6' SOUTH TO THE IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 20-18-11, THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
 - 7) 2,637.36' EAST TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-18-11
 - 8) 3,956.04' EAST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-18-11, THAT WAS SET BY ALVA J. SMITH
- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **SANDSTONE AND GAS PIPE** AT THE WEST 1/4 CORNER OF SECTION 8-18-11.
- 1) 21' EAST TO A CORNER FENCE POSTS
 - 2) 30' NE TO A 1/2" SQUARE IRON PIN
- 11) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 75 AT THE BOTTOM OF THE PAGE SHOWS A **SANDSTONE & GAS PIPE** AT THE "W1/4 CORNER SECTION 8-18-11".
- 1) 30' NE TO A 1/2" SQUARE IRON PIN
 - 2) 21' EAST TO THE NEAR FACE OF A CORNER FENCE POST
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 29, 1992, FOR JOB NUMBER 92026-02, SURVEY F18003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE WEST HALF OF THE SOUTHWEST QUARTER OF THE NORTHEAST QUARTER AND A

TRACT OF 7.0 ACRES IN SECTION 18-18-11 FILED FEBRUARY 7, 1992 IN VOLUME 463 ON PAGE 859 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE WITH A GAS PIPE ON THE EAST SIDE OF THE STONE** AT THE EAST 1/4 CORNER OF SECTION 7-18-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) 21.2' EAST TO A CONCRETE NAIL & SHINER IN A CORNER POST
- 2) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 3) 6.0' SOUTH TO A FENCE TO THE WEST EXTENDED
- 4) 18.5' SOUTH TO THE CENTERLINE OF THE ENTRANCE TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.12' SOUTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-18-11
- 2) 5,294.76' SOUTH TO THE OLD "CON" #5 REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11
- 3) 7,941.10' SOUTH TO THE DETERIORATING LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-18-11, WITH A 1" X 9" X 15" CAP STONE OVER THE LIMESTONE. HE DROVE A 1/2" REBAR WITH HIS "LS 752" CAP THROUGH THE STONE

- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 30, 2011 FOR PROJECT NUMBER 11270-02, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 18-11, A SURVEY OF A 3.1 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 7-18-11 FOR HARRY HANSON, SAID THAT **HE FOUND THE STONE WITH A GAS PIPE ON THE EAST SIDE AND A 1/2" REBAR ON THE WEST SIDE OF THE STONE** AT THE EAST 1/4 CORNER OF SECTION 7-18-11 FROM HIS EXISTING HIS REFERENCE TIES ON FILE AT THE LYON COUNTY ENGINEER'S OFFICE DATED JANUARY 1992.

- 1) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" NORTH-SOUTH
- 2) 21.50' WSW TO A SPIKE & BOTTLECAP IN THE EAST FACE OF A CORNER POST
- 3) 2.50' SOUTH TO A LINE OF FENCE TO THE EAST
- 4) 21.20' EAST TO A CONCRETE NAIL & SHINER IN THE SOUTH FACE OF A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.15' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 7-18-11

WEST QUARTER CORNER 08-18-11