

**WEST 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 08, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE SET A STONE** FOR THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 8-18-11 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 AND THE STONE THAT HE SET FOR THE CENTER CORNER OF SECTION 8-18-11 ON THIS SURVEY.
  
- 2) LLOYD J. DOBLER, L.S. 541, IN A SURVEY DATED DECEMBER 1977 FOR WAYNE JONES, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF THE WEST 1980 FEET OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11 DATED DECEMBER 1977, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11 ON LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 8-18-11.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,326.95' NORTH TO THE IRON PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 "PER COUNTY RECORDS"
  - 2) 1,326.95' SOUTH TO THE PIN HE SET FOR THE CENTER CORNER OF SEC. 8-18-11
  - 3) 1,908.00' EAST TO THE PIN HE SET FOR THE NORTHEAST CORNER OF THE WEST 1980 FEET OF THE S1/2 OF THE NE1/4 OF SECTION 8-18-11
  
- 3) LLOYD J. DOBLER, L.S. 541, IN A SURVEY DATED APRIL 1978 FOR IMOGENE KERNS, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 7.44 ACRE TRACT IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHWEST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 8-18-11, BUT HE DOES NOT DESCRIBE THE MONUMENT IN HIS LEGEND.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,326.95' NORTH TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-18-11
  - 2) 1,425.85' EAST TO THE PIN HE SET FOR THE SOUTHWEST CORNER OF THE 7.44 ACRE TRACT
  - 3) 1,925.03' EAST TO THE PIN HE SET FOR THE SOUTHWEST CORNER OF THE 7.44 ACRE TRACT
  
- 4) JAMES D. SCHMITZ, L.S. 727, IN A SURVEY DATED OCTOBER 13, 1992 FOR JOB NUMBER 92-79-B, SURVEY F08003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A PROPOSED EQUIPMENT STATION EASEMENT FOR BEST COMMUNICATIONS IN THE NORTHEAST 1/4 OF SECTION 8-18-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1/2" BAR** AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 8-18-11 AS PER THE LLOYD DOBLER SURVEY OF DECEMBER 1977.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,320.98' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 [DOBLER SURVEY = 1,326.95']

WEST SIXTEENTH CORNER NORTHEAST QUARTER 08-18-11