

**WEST 1/4 CORNER SECTION 09, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 344 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 17" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 9-18-11.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 9-18-11 ON THIS SURVEY.
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 20.08 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-18-11
  - 2) 40.16 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-18-11
  - 3) 19.98 CHAINS WEST TO THE McAULEY STONE HE FOUND AT THE NORTH 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-18-11
  - 4) 39.96 CHAINS WEST TO THE 16" X 12" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11, AND HE PLACED A RAILROAD LINK BY THE SIDE OF THE STONE
  - 5) 79.92 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-18-11
- 4) REA BOOK 30 ON PAGE 13 DATED APRIL 24, 1939, SAID THAT THEY BEGAN "AT A **STONE** [ONLY STONE WE FOUND TO MARK W1/4 CORNER SECTION 9 AND IT IS USED AS A FOOTING FOR A FENCE BRACE]". HE COMMENTED "I AM **UNCERTAIN** ABOUT THIS STONE AT THE WEST 1/4 CORNER. BEGINNING AT THE STONE AT THE FOOT OF SAID FENCE BRACE I RAN EAST ALONG OLD HEDGE 193 [FEET] AND FOUND STONE I BELIEVE TO BE THE ONE MARKING W 1/4 CORNER OF SAID SECTION 9". **VERIFY BEFORE USING AS THEY WERE UNCERTAIN OF ITS POSITION!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 5)) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 1, 1995, FOR PROJECT NUMBER 95017-02, FOR LYON COUNTY PROJECT 92-V0, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 9-18-11. HE DID **NOT** RESET THE WEST 1/4 CORNER OF SECTION 9-18-11 ON THIS SURVEY.

WEST QUARTER CORNER 09-18-11