

WEST 1/4 CORNER SECTION 10, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 340 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-18-11.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-18-11 ON THIS SURVEY.
- 3) REA BOOK 30 ON PAGE 14 SAYS THAT **THEY ESTABLISHED** THE EAST 1/4 CORNER OF SECTION 9-18-11 ON APRIL 20, 1939. IT DOES NOT SAY WHAT MONUMENT THEY SET FOR THE EAST 1/4 CORNER OF SECTION 9-18-11, BUT HE NORMALLY SET SQUARE IRON PINS.
 - 1) STAKE AT WITNESS READS 29' EAST TO CORNER
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 16, 1983, SAID THAT **HE FOUND A #6 SQUARE REBAR** AT THE WEST 1/4 CORNER OF SECTION 10-18-11 THAT WAS SET BY AI CHAMNESS ON A REA SURVEY IN 1939.
 - 1) 27.2' WEST TO THE NEAR FACE OF A HEDGE CORNER POST
 - 2) 28.6' EAST TO THE NEAR FACE OF A HEDGE CORNER POST
 - 3) 2.0' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 4) 2.0' SOUTH TO A LINE OF FENCE EAST & WEST [EXTENDED]

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

 - 1) 2,644.8' NORTH TO THE #6 SQUARE REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-18-11
 - 2) 2,644.8' SOUTH TO THE FENCE EAST AND THE TRAVELED WAY OF THE ROAD TO THE WEST AT THE SOUTHWEST CORNER OF SECTION 10-18-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 28, 2003, FOR PROJECT NUMBER 03197-02, SURVEY F09001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SUBDIVISION OF THE SOUTHEAST QUARTER OF SECTION 9-18-11, SAID THAT **HE FOUND THE 3/4" SQUARE REBAR** AT THE EAST 1/4 CORNER OF SECTION 9-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JUNE 1983.
 - 1) 27.2' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 28.55' EAST TO A CONCRETE NAIL & WASHER IN A RAILROAD TIE POST
 - 3) 41.20' SE TO A CONCRETE NAIL & WASHER IN A HEDGE GATE POST
 - 4) 4.5' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
 - 5) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "K" NORTH-SOUTH
 - 6) 1.5' SOUTH TO A LINE OF FENCE TO THE WEST [EXTENDED]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,641.91' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF SEC. 9-18-11
 - 2) 1,322.45' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 9-18-11
 - 3) 2,644.91' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 9-18-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 1,305.90' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 9-18-11
 - 5) 2,611.80' WEST TO THE 3/4" REBAR EH FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 10-18-11
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 11, 2006, FOR PROJECT NUMBER 05395-02, SURVEY F10006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE SOUTH LINE OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 10-18-11 FOR DOUG COFFMAN, SAID THAT **HE FOUND THE 3/4" SQUARE REBAR** AT THE WEST 1/4 CORNER OF SECTION 10-18-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE IN 2003 FOR PROJECT 03197.
- 1) 27.2' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 41.2' SE TO A CONCRETE NAIL & WASHER IN A HEDGE GATE POST
 - 3) 28.6' EAST TO A CONCRETE NAIL & WASHER IN A RAILROAD TIE FENCE POST
 - 4) 2.0' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "K" NORTH-SOUTH
 - 5) 1.5' SOUTH TO A LINE OF FENCE TO THE WEST EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,648.82' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 10-18-11
 - 2) 5,321.50' EAST TO THE COTTON GIN SPINDLE HE FOUND AT THE NORTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 10-18-11
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 21, 2013 FOR PROJECT NUMBER 13053-02, THE SURVEY OF A 5.00 ACRE TRACT IN THE NORTHWEST 1/4 OF SECTION 10-18-11 FOR MARTIN ALVARADO, SURVEY F10007 IN THE SURVEY FILE FOR TOWNSHIP 18-11, SAID THAT **HE FOUND THE 3/4" IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 10-18-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE LYON COUNTY ENGINEERS OFFICE DATED JANUARY 2006.
- 1) 1.50' SOUTH TO A LINE OF FENCE TO THE WEST EXTENDED
 - 2) 4.50' SOUTH TO A LINE OF FENCE TO THE EAST EXTENDED
 - 3) 3.00' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "K" NORTH-SOUTH
 - 4) 27.00' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 28.55' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 508.78' NORTH TO THE POINT OF BEGINNING OF THE 5.00 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "S. BROSEMER" CAP HE SET AT 30.00' EAST
 - 2) 961.78' NORTH TO THE NORTHWEST CORNER OF THE 5.00 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "S. BROSEMER" CAP HE SET AT 30.00' EAST
 - 3) 2,644.74' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 10-18-11

WEST QUARTER CORNER 10-18-11