

WEST 1/4 CORNER SECTION 15, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 339 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 16-18-11.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 89 RECORDED IN SURVEY BOOK "A" ON PAGE 183 DATED FEBRUARY 12, 1869 FOR A SURVEY OF LANE OWNED BY H. F. PLUMB AND BROWN, BEING IN SECTION 15-18-11, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE NORTHEAST 1/4 BY AN EAST AND WEST LINE, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 15-18-11 ON THIS SURVEY.
- 3) **REA PIN—MUST VERIFY AND CHECK FOR OTHER MONUMENTS BEFORE USING; THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 14 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 15-18-11 ON APRIL 17, 1939.
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2004, FOR PROJECT NUMBER 04024-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE EAST LINE OF THE WEST HALF OF THE OF THE NORTHWEST QUARTER OF SECTION 16-18-11, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 16-18-11 WAS **LOST. HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 16-18-11 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHEAST & SOUTHEAST CORNERS OF SECTION 16-18-11.
 - 1) 24.50' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 33.95' NE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 3) 27.05' WEST TO THE END OF A BOLT IN THE SOUTH FACE OF A PIPE CORNER POST
 - 4) 43.50' NW TO A CONCRETE NAIL & WASHER IN THE NORTH GATE POST
 - 5) IN LINE WITH AN OLD FENCE TO THE EAST EXTENDED
 - 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "K" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,654.73' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-18-11
 - 2) 2,654.73' SOUTH TO THE 5/8" SQUARE REBAR FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 16-18-11
 - 3) 2,578.47' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 16-18-11
 - 4) 3,889.93' WEST TO A 1/2" THEORETICAL POSITION FOR THE SOUTHEAST CONNER OF THE W1/2 OF THE NW1/4 OF SECTION 16-18-11—FALLS IN A CREEK AND WITNESSED BY 1/2" REBARS WITH HIS "LS 752" CAPS HE SET AT 50' AND 100' NORTH TO THE TRUE POSITION
 - 5) 5,189.02' WEST TO THE 1/2" BENT REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 16-8-11, AND **HE REPLACED** WITH A 5/8" REBAR WITH A LYON COUNTY CAP
- 5) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 1, 2004, FOR KDOT PROJECT 99-56-K9627-01, SAID THAT **HE FOUND A 1/2" REBAR WITH A PLASTIC CAP MARKED "LYON COUNTY" AT 0.2 FEET DEEP** AT THE WEST 1/4 CORNER OF SECTION 15-18-11 FROM RECORDED TIES IN LYON COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED MARCH 19, 2004. PROJECT POINT NUMBER 15208.

- 1) IN THE TRAVELED WAY OF THE NORTH-SOUTH PUBLIC ROAD
 - 2) IN LINE WITH A FENCE EAST AND WEST
 - 3) 43.5' WNW TO A NAIL & WASHER IN THE SIDE OF A GATE FENCE POST
 - 4) 27.6' WEST TO THE CENTERLINE TOP OF A STEEL GATE FENCE POST
 - 5) 24.5' EAST TO A NAIL & WASHER IN THE SIDE OF A GATE FENCE POST
 - 6) 34.0' NE TO A NAIL & WASHER IN THE SIDE OF A BRACE FENCE POST
- SURVEY F10005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 SIGNED BY LARRY D. MOORE, L.S. 1174, DATED APRIL 16, 2004 SHOWS THE FOLLOWING INFORMATION:
- 1) 2,654.96' NORTH TO THE 5/8" REBAR WITH A PLASTIC CAP STAMPED "LYON COUNTY" HE FOUND AT 0.2' DEEP AT THE NORTHWEST CORNER OF SECTION 15-18-11
 - 2) 2,654.61' SOUTH TO THE 1/2" SQUARE REBAR HE FOUND AT 0.5' DEEP AT THE SOUTHWEST CORNER OF SECTION 15-18-11
 - 3) 2,644.67' EAST TO THE 6" X 9" X 10" LIMESTONE HE FOUND AT 1.3' DEEP AT THE CENTER OF SECTION 15-18-11
 - 4) 5,341.02' EAST TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 15-18-11
 - 5) 7,986.46' EAST TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE CENTER OF SECTION 14-18-11
 - 6) 10,694.85' EAST TO THE 1/2" IRON BAR HE FOUND AT 0.7' DEEP AT THE EAST 1/4 CORNER OF SECTION 14-18-11
 - 7) PROJECT COORDINATES X 0.999928556 = KANSAS SOUTH STATE PLANE
NORTH = 1982767.931 EAST = 1973777.108
- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 23, 2004, FOR PROJECT NUMBER 04417-02, SURVEY F15002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 26 ACRE TRACT IN THE SOUTH HALF OF THE NORTHWEST QUARTER OF SECTION 15-18-11 FOR ALAN KUSMAUL, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 OF SECTION 15-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 2004.
- 1) 24.50' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 33.95' NE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 3) 27.05' WEST TO THE END OF A BOLT IN THE SOUTH FACE OF A PIPE CORNER FENCE POST
 - 4) 43.50' NW TO A CONCRETE NAIL & WASHER IN THE NORTH GATE POST
 - 5) IN LINE WITH AN OLD FENCE TO THE EAST EXTENDED
 - 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "K" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 450.00' NORTH TO THE 40 D NAIL HE SET FOR THE SOUTHWEST CORNER OF THE 26 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' EAST
 - 2) 1,327.38' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 15-18-11, AND THE P.O.B. OF THE 26 ACRE TRACT
 - 3) 2,654.77' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY HE FOUND AT THE NORTHWEST CORNER OF THE N1/2 OF THE NW1/4 OF SECTION 15-18-11
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED FEBRUARY 24, 2005, FOR PROJECT NUMBER 05040-02, SURVEY F15003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 30.36 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 15-18-11 FOR PAUL HANCOCK AND ALICE GATEWOOD, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 15-18-11 FROM HIS EXISTING TIES AT THE COUNTY ENGINEER'S OFFICE [DATED NOVEMBER 2004].

- 1) 24.50' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 33.95' NE TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 3) 27.05' WEST TO THE END OF A BOLT IN THE SOUTH FACE OF A PIPE CORNER FENCE POST
- 4) 43.50' NW TO A CONCRETE NAIL & WASHER IN THE NORTH GATE POST
- 5) IN LINEN WITH AN OLD FENCE TO THE EAST EXTENDED
- 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "K" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.33' EAST TO THE THEORETICAL LOCATION FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 15-18-11
- 2) 2,644.66' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 15-18-11
- 3) 1,327.35' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 15-18-11
- 4) 2,654.69' SOUTH TO THE 5/8" SQUARE REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 15-18-11

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 29, 2005, FOR PROJECT NUMBER 05130-02, SURVEY F15004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF TWO TRACTS IN THE SOUTH HALF OF THE NORTHWEST QUARTER OF SECTION 15-18-11 FOR EK REAL ESTATE, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 15-18-11 FROM HIS TIES FOR PROJECT 05040-02 [FEBRUARY 2005].

- 1) 24.50' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 33.95' NE TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 3) 27.05' WEST TO THE END OF A BOLT IN THE SOUTH FACE OF A PIPE CORNER FENCE POST
- 4) 43.50' NW TO A CONCRETE NAIL & WASHER IN THE NORTH GATE POST
- 5) IN LINE WITH AN OLD FENCE TO THE EAST EXTENDED
- 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "K" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 400.00' NORTH TO THE NORTHWEST CORNER OF THE SOUTH TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' EAST
- 2) 450.00' NORTH TO THE 40 D NAIL HE FOUND AT THE P.O.B. OF THE EAST TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' EAST
- 3) 1,327.38' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 15-18-11
- 4) 1,333.12' EAST TO THE SOUTHEAST CORNER OF THE SOUTH TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 3.0' NORTH OF THE TRUE POSITION DUE TO A RAVINE
- 5) 2,644.66' EAST TO THE STONE WITH A KDOT CAP ON THE EAST SIDE OF THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 15-18-11

WEST QUARTER CORNER 15-18-11