

WEST 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 15, TOWNSHIP 18 SOUTH, RANGE 11 EAST

1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 89 RECORDED IN SURVEY BOOK "A" ON PAGE 183 DATED FEBRUARY 12, 1869 FOR A SURVEY OF LANE OWNED BY H. F. PLUMB AND BROWN, BEING IN SECTION 15-18-11, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE NORTHEAST 1/4 BY AN EAST AND WEST LINE, SAID THAT **HE SET A STONE** FOR THE WEST 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 15-18-11 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 15-18-11 AND THE STONE THAT HE SET FOR THE CENTER CORNER OF SECTION 15-18-11 ON THIS SURVEY.

2) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 1, 2004, FOR KDOT PROJECT 99-56-K9627-01, SAID THAT **HE FOUND A 4" X 12" X 16" LIMESTONE** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15-18-11. **HE SET A 1/2" REBAR WITH AN ALUMINUM KDOT CAP 0.3 FEET EAST OF THE CENTERLINE OF THE STONE.** HE IDENTIFIED THE STONE AS THE 1/16TH CORNERSTONE THAT WAS SET BY D. T. McAULEY, COUNTY SURVEYOR, ON A SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 183 AND DATED FEBRUARY 12, 1869. PROJECT POINT NUMBER 15048.

- 1) IN A NORTH-SOUTH HEDGE ROW AT AN OLD CORNER FENCE POST
- 2) IN LINE WITH OLD FENCE REMAINS TO THE EAST
- 3) 4' NORTH TO A FENCE GATE POST AND A FENCE TO THE WEST
- 4) IN LINE WITH A HEDGE TO THE WEST
- 5) 12.9' WEST TO A SPIKE & KDOT WASHER IN THE TOP OF A GATE POST
- 6) 3.1' SOUTH TO A SPIKE & KDOT WASHER IN THE EAST FACE OF A HEDGE TREE
- 7) 11.8' NORTH TO A SPIKE & KDOT WASHER IN THE EAST FACE OF A HACKBERRY TREE

SURVEY F10005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 SIGNED BY LARRY D. MOORE, L.S. 1174, DATED APRIL 16, 2004 SHOWS THE FOLLOWING INFORMATION:

- 1) 1,341.06' NORTH TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 15-18-11
- 2) 2,693.39' EAST TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 15-18-11
- 3) 5,341.92' EAST TO THE 4" X 6" X 18" LIMESTONE HE FOUND AT 0.4' DEEP AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 14-18-11
- 4) 1,339.26' SOUTH TO THE 6" X 9" X 10" LIMESTONE HE FOUND AT 1.3' DEEP AT THE CENTER CORNER OF SECTION 15-18-11
- 5) 3,973.16' SOUTH TO THE 1/2" REBAR HE FOUND AT 0.5' DEEP AT THE SOUTH 1/4 CORNER OF SECTION 15-18-11
- 6) PROJECT COORDINATES X 0.999928556 = KANSAS SOUTH STATE PLANE
NORTH = 1984113.261 EAST = 1976394.248

3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 23, 2004, FOR PROJECT NUMBER 04417-02, SURVEY F15002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 26 ACRE TRACT IN THE SOUTH HALF OF THE NORTHWEST QUARTER OF SECTION 15-18-11 FOR ALAN KUSMAUL, SAID THAT **HE FOUND THE 4" X 12" X 16" LIMESTONE** AT THE EAST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 15-18-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) 0.3' EAST TO A 1/2" REBAR WITH A KDOT ALUMINUM CAP
- 2) 4.0' NORTH TO A FENCE LINE TO THE WEST
- 3) IN LINE WITH A HEDGE ROW NORTH-SOUTH
- 4) 12.9' WNW TO A SPIKE & KDOT WASHER IN TOP THE TOP OF A GATE POST

HIS TIES ARE CONTINUED ON PAGE 2

- 5) 3.0' SOUTH TO A SPIKE & KDOT WASHER IN THE EAST FACE OF A HEDGE TREE
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,375.24' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 26 ACRE TRACT
 - 2) 2,645.94' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 15-18-11
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 29, 2005, FOR PROJECT NUMBER 05130-02, SURVEY F15004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF TWO TRACTS IN THE SOUTH HALF OF THE NORTHWEST QUARTER OF SECTION 15-18-11 FOR EK REAL ESTATE, SAID THAT **HE FOUND THE 4" X 12" X 16" LIMESTONE** AT THE EAST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 15-18-11 FROM EXISTING REFERENCE TIES AT THE COUNTY ENGINEER'S OFFICE BY HIM FOR PROJECT NUMBER 04417-02 [2004].
- 1) 0.3' EAST TO A 1/2" REBAR WITH A KDOT ALUMINUM CAP
 - 2) 4.0' NORTH TO A FENCE LINE TO THE WEST
 - 3) IN LINE WITH A HEDGE ROW NORTH-SOUTH
 - 4) 12.9' WNW TO A SPIKE & KDOT WASHER IN TOP THE TOP OF A GATE POST
 - 5) 3.0' SOUTH TO A SPIKE & KDOT WASHER IN THE EAST FACE OF A HEDGE TREE
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,375.24' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE EAST TRACT
 - 2) 2,645.94' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 15-18-11
 - 3) 1,339.65' SOUTH TO THE STONE WITH A KDOT CAP ON THE EAST SIDE HE FOUND AT THE SOUTHEAST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 14-18-11

WEST SIXTEENTH CORNER NORTHEAST QUARTER 15-18-11