

WEST 1/16TH CORNER OF THE SOUTHEAST QUARTER OF SECTION 15, TOWNSHIP 18 SOUTH, RANGE 11 EAST

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 24, 2005, FOR PROJECT NUMBER 05040-02, SURVEY F15003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 30.36 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 15-18-11 FOR PAUL HANCOCK AND ALICE GATEWOOD, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 15-18-11 ON TRUE LINE AND HALF-WAY BETWEEN THE CENTER CORNER OF SECTION 15-18-11 AND THE SOUTH QUARTER CORNER OF SECTION 15-18-11.

- 1) 20.8' NNW TO THE NEAR FACE OF A CORNER FENCE POST
- 2) 26.8' NW TO THE NEAR FACE OF A CORNER FENCE POST
- 3) 21' NORTH TO A LINE FENCE TO THE WEST
- 4) 2.6' WEST TO A LINE HEDGE TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.77' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 15-18-11
- 2) 1,316.77' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-18-11
- 3) 1,325.03' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER OF THE SOUTHWEST 1/4 OF SECTION 15-18-11
- 4) 2,650.44' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 15-18-11

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 26, 2010 FOR PROJECT NUMBER 10101-02, SURVEY F15005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TRACTS IN THE SOUTH HALF OF THE SOUTHEAST QUARTER OF SECTION 15-18-11 FOR MR. WOODS, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 15-18-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED FEBRUARY 2005.

- 1) 20.8' NNW TO THE NEAR FACE OF A CORNER FENCE POST
- 2) 26.8' NW TO THE NEAR FACE OF A BRACE POST
- 3) 21.0' NORTH TO A LINE OF FENCE TO THE WEST
- 4) 2.6' WEST TO A LINE OF HEDGE TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.86' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 15-18-11
- 2) 2,677.55' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 15-18-11

3) JOSHUA L. JUNGHANS, L.S. 1488, OF KAW VALLEY ENGINEERING, INC. IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 3, 2014 FOR PROJECT NUMBER F14S0051, THE SURVEY OF TWO TRACTS IN THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 15-18-11 FOR HEATH BROWN, SURVEY F15006 IN THE SURVEY FILE FOR TOWNSHIP 18-11, SAID THAT **HE FOUND THE 1/2" REBAR WITH "LS 752" CAP** AT THE EAST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 15-18-11 FROM EXISTING REFERENCE TIES FROM THE COUNTY SURVEYORS OFFICE. HE SENT THE FOLLOWING **HORIZONTAL TIES:**

- 1) 20.8' NW TO THE NEAR FACE OF A CORNER FENCE POST
- 2) 26.8' NW TO THE NEAR FACE OF A BRACE POST
- 3) 21.0' NORTH TO A LINE OF FENCE TO THE WEST
- 4) 2.6' WEST TO A LINE OF HEDGE TO THE SOUTH

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.76' SOUTH TO THE 1/2" BAR, ORIGIN UNKNOWN, HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 15-18-11
- 2) 1,320.44' NORTH TO THE 6" X 9" X 10" LIMESTONE AT 1.3' DEEP THAT HE FOUND AT THE NORTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 15-18-11 THAT WAS SET BY D. T. McAULEY ON FEBRUARY 12, 1869
- 3) 1,693.38' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET ON THE NORTHEASTERLY RIGHT-FO-WAY OF THE KANSAS TURNPIKE AT THE SOUTHWEST CORNER OF TRACT 1
- 4) 2,644.46' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE POINT OF BEGINNING OF TRACT A
- 5) 2,677.46' EAST [GEOTECH, INC. SURVEY DATED 4/30/2010 = 2,677.53'] TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 15-18-11

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 15-18-11