

**NORTH 1/4 CORNER SECTION 16, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 343 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-18-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.87 CHAINS WEST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-11
- 2) 39.87 CHAINS EAST TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-18-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT HE FOUND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 9-18-11, BUT HE DETERMINED THAT THIS STONE WAS **INCORRECT**. **HE SET A STONE** FOR THE TRUE SOUTH 1/4 CORNER OF SECTION 9-18-11 EQUIDISTANT AND ON TRUE LINE BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 9-18-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-18-11 ON THIS SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY L. A. HAMBLIN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 184 TO 186 [PACKET 30 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] PETITIONED BY H. W. PEARSALL AND OTHERS, THAT HE SURVEYED APRIL 21, 1871 AND WAS ORDERED ESTABLISHED AND RECORDED BY THE BOARD OF COMMISSIONERS AS A 50 FOOT WIDE ROAD ON OCTOBER 2, 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 16-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 10.00 CHAINS NORTH TO THE ROCK HE FOUND
- 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 80.00 CHAINS TO THE NORTH 1/4 CORNER OF SECTION 9-18-11 AT A TURN TO THE WEST
- 3) THIS ROAD EXTENDS SOUTH ON THE CENTERLINE OF THE SECTIONS FOR 80.00 CHAINS TO THE SOUTH 1/4 CORNER OF SECTION 16-18-11 AT A TURN TO THE EAST

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 AND DATED APRIL 1902, SAID THAT **HE FOUND THE STONE AT 7 FEET EAST OF A STONE FENCE** AT THE NORTH 1/4 CORNER OF SECTION 16-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACK "M 146" IN MISCELLANEOUS DRAWER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED APRIL 2, 1974 FOR A SURVEY TO LOCATE THE EAST LINE OF THE WEST 1/2 OF THE WEST 1/2 OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 16, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 16-18-11. THERE ARE NO TIES ON THE SURVEY.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,260' WEST TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE W1/2 OF THE W1/2 OF THE NW1/4 OF SECTION 16-18-11
  - 2) 2,583' WEST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-18-11 [**NOTE:** THIS SHOULD BE THE NORTHWEST CORNER OF SECTION 16-18-11 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "S 1/4 CORNER SECTION 9-18-11".
- 1) 39.0' NW TO A SPIKE & WASHER
  - 2) 30.5' SW TO A SPIKE & WASHER
  - 3) 33.0' SE TO A SPIKE & WASHER
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 1, 1995, FOR JOB NUMBER 95017-02, SAID THAT **HE FOUND THE CORNERSTONE WITH A 1/2" REBAR BENT OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 9-18-11 FROM RECORDS IN THE COUNTY ENGINEER'S OFFICE.
- 1) 34.3' SE TO A NAIL & DISC IN A CORNER FENCE POST
  - 2) 39.2' NE TO A NAIL & DISC IN A POWER POLE
  - 3) 4.0' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 4) 1.0' SOUTH TO THE TRAVELED WAY OF THE ROAD EAST-WEST
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 5,288.01' NORTH TO THE NORTH 1/4 CORNER OF SECTION 9-18-11
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 28, 2003, FOR PROJECT NUMBER 03197-02, SURVEY F09001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SUBDIVISION OF THE SOUTHEAST QUARTER OF SECTION 9-18-11, SAID THAT **HE FOUND THE 1/2" REBAR BENT OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 9-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MAY 1995.
- 1) 39.2' NE TO A NAIL & WASHER IN A POWER POLE
  - 2) 35.6' NW TO THE TOP OF A TELEPHONE PEDESTAL
  - 3) 33.9' SE TO A NAIL & WASHER IN A CORNER FENCE POST
  - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE EAST
  - 6) IN THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,316.80' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 9-18-11
  - 2) 2,633.60' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 9-18-11
  - 3) 1,299.12' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE SOUTH 1/16<sup>TH</sup> OF THE SE1/4 OF SECTION 9-18-11
  - 4) 2,598.24' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 9-18-11
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2004, FOR PROJECT NUMBER 04024-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE EAST LINE OF THE WEST HALF OF THE OF THE NORTHWEST QUARTER OF SECTION 16-18-11, SAID THAT **HE FOUND THE 1/2" REBAR BENT OVER THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 16-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2003.

- 1) 39.2' NE TO A NAIL & WASHER IN A POWER POLE
  - 2) 35.6' NW TO THE TOP OF A TELPED
  - 3) 33.9' SE TO A NAIL & WASHER IN A CORNER FENCE POST
  - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY NORTH-SOUTH
  - 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD TO THE EAST
  - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD TO THE WEST  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
    - 1) 1,291.66' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 16-18-11
    - 2) 2,683.32' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 16-18-11
    - 3) 2,698.27' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-18-11
    - 4) 2,654.69' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 16-18-11
    - 5) 5,306.19' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-18-11
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 7, 2005, FOR PROJECT NUMBER 05404-02, SURVEY F09002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 15.78 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 9-18-11 FOR MAXWELL, SAID THAT **HE FOUND THE 1/2" REBAR BENT OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 9-18-11 FROM EXISTING REFERENCE TIES DATED MARCH 2004.
- 1) 39.2' NE TO A NAIL & WASHER IN A POWER POLE
  - 2) 35.6' NW TO THE TOP OF A TELEPHONE PEDESTAL
  - 3) 33.9' SE TO A NAIL & WASHER IN A CORNER FENCE POST
  - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY NORTH-SOUTH
  - 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD TO THE EAST
  - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD TO THE WEST  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
    - 1) 2,633.59' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 9-18-11

NORTH QUARTER CORNER 16-18-11