

**NORTHWEST CORNER SECTION 16, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 343 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 23" X 12" X 3"** FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.87 CHAINS EAST TO THE 19" X 12" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-18-11
  - 2) 79.74 CHAINS TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-18-11
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 9-18-11 ON THIS SURVEY.
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 42, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 DATED APRIL 4, 1902 ORDERED BY LEVI EMMEL FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF SECTION 7-18-11 AND RUN SUCH OTHER LINES AS ARE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 146" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.76 CHAINS WEST TO THE STONE HE FOUND SITTING THE WRONG WAY IN THE GROUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11
  - 2) 79.79 CHAINS WEST TO THE 22" X 12" X 3" STONE WITH A CASTING FROM A WELL PULLEY HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 7-18-11
  - 3) 119.90 CHAINS WEST TO THE 20" X 12" X 4" STONE HE SET FOR THE PERMANENT SOUTHWEST 1/4 CORNER OF SECTION 7-18-11
  - 4) 155.35 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE
  
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 58, A ROAD SURVEY FOR A ROAD IN TOWNSHIP 18, RANGE 11 PETITIONED BY JASPER GRIMSLEY, RECORDED IN SURVEY BOOK "F" ON PAGE 137 DATED AUGUST 12, 1902, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 8-18-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 79.54 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 9-18-11 TO END THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE,
  - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 12.25 CHAINS TO THE EAST GATE POST IN A FENCE, LAYING THE ROAD 60 FEET WIDE, 20 FEET ON THE SOUTH SIDE AND 40 FEET ON THE NORTH SIDE OF THE SECTION LINE, THEN CONTINUES WEST ON THE SECTION LINE FOR 27.59 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 8-18-

11 TO BEGIN THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 575 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 165 THROUGH 168 PETITION BY JASPER GRIMSLEY AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 714 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 12, 1902, WAS GRANTED AS A 40 AND 60 FOOT WIDE ROAD AS SURVEYED ON NOVEMBER 6, 1902 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON NOVEMBER 11, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 8-18-11 ON THIS ROAD SURVEY

HIS NOTES/SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 79.54 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-18-11 TO END THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE,
- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 12.25 CHAINS TO THE EAST GATE POST IN A FENCE, LAYING THE ROAD 60 FEET WIDE, 20 FEET ON THE SOUTH SIDE AND 40 FEET ON THE NORTH SIDE OF THE SECTION LINE, THEN CONTINUES WEST ON THE SECTION LINE FOR 27.59 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 8-18-11 ON THIS PERMANENT SURVEY.** HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.08 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-18-11
- 2) 40.16 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 8-18-11
- 3) 19.87 CHAINS WEST TO THE 18" X 7" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-18-11
- 4) 39.74 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11
- 5) 79.75 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11
- 6) HE NOTED THAT WHEN HE SET THE TRANSIT OVER THE STONE AT THE SOUTHWEST CORNER OF SECTION 8-18-11 EAST OVER THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11, HE FELL 75 LINKS NORTH OF THE STONE AT THE SOUTHEAST CORNER OF SECTION 8-18-11

CONTINUED ON PAGE 3

- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "D" ON PAGE 389 AND DATED AUGUST 1907 FOR ROAD NUMBER 630, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY.
- 8) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT HE USED THE STONES THAT HE FOUND AS RECORDED IN SURVEYS BY ALVA J. SMITH IN APRIL AND AUGUST OF 1902 IN SECTION 8-18-11. **HE FOUND THE STONE RECORDED IN SURVEYS BY ALVA J. SMITH IN APRIL & AUGUST 1902** AT THE SOUTHEAST CORNER OF SECTION 8-18-11 ON THIS INFORMAL SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,311.4' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-18-11 THAT WAS FOUND BY SMITH
  - 2) 2,622.4' WEST TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11
  - 3) 5,260.3' WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-18-11
  - 4) 2,647.5' SOUTH TO THE IRON PIN HE SET FOR THE EAST 1/4 CORNER OF SECTION 17-18-11
  - 5) 5,295.1' SOUTH TO THE 18" X 9" X 4" LIMESTONE HE SET FOR THE NORTHEAST CORNER OF SECTION 20-18-11
  - 6) 7,940.3' SOUTH TO THE IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-18-11, THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
- 9) IN A FIELD BOOK IN VAULT IN COUNTY ENGINEER'S OFFICE MARKED "RT. 1078 HEINZ ROAD" ON PAGE 42 FOR A SURVEY BY LESLIE M. GOULD DATED APRIL 1, 1974, SAID THAT HE BEGAN THE SECOND LINE OF THIS SURVEY AT THE **STONE** AT THE NORTHWEST CORNER OF SECTION 16-18-11.
- 10) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED APRIL 2, 1974 FOR A SURVEY TO LOCATE THE EAST LINE OF THE WEST 1/2 OF THE WEST 1/2 OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 16, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 16-18-11. HE DOES NOT DESCRIBE THE STONE OR HAVE ANY TIES ON THE SURVEY. [NOTE: ON THE DRAWING THIS CORNER IS LABELED AS THE "NE CORNER OF SECTION 16-18-11" BUT IT IS THE NORTHWEST CORNER OF SECTION 16-18-11 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 323' EAST TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE W1/2 OF THE W1/2 OF THE NW1/4 OF SECTION 16-18-11
  - 2) 2,583' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-18-11
  - 3) 2,647.5' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET ON THE NORTH EDGE OF THE LEVEE AT THE SOUTHWEST CORNER OF THE NW1/4 OF SEC. 16-18-11
- 11) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SW CORNER SECTION 9-18-11".
- 1) 83.5' WEST TO A ROCKER PIN AT THE EAST END OF THE TRUSS BRIDGE
  - 2) 55.8' NW & 23.5' SW TO REBARS

CONTINUED ON PAGE 4

- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2004, FOR PROJECT NUMBER 04024-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE EAST LINE OF THE WEST HALF OF THE OF THE NORTHWEST QUARTER OF SECTION 16-18-11, SAID THAT **HE FOUND THE STONE AT THE NORTHWEST CORNER OF SECTION 16-18-11. HE SET A 1/2" REBAR WITH HIS "LS 752" CAP OVER THE CENTER OF THE STONE.**
- 1) 4.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY TO THE EAST
  - 2) 41.35' WEST TO A NAIL & WASHER IN THE TOP OF A RAIL POST
  - 3) 22.8' SW TO A NAIL & WASHER IN A DOUBLE TREE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,291.66' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 16-18-11
  - 2) 2,583.32' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 16-18-11
  - 3) 5,181.59' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-18-11
  - 4) 2,643.93' SOUTH TO THE BENT 1/2" SQUARE REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 16-18-11 AND **HE REPLACED WITH A 5/8" REBAR WITH A LYON COUNTY CAP**

NORTHWEST CORNER 16-18-11