

**CENTER CORNER SECTION 17, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 456 RECORDED IN ROAD RECORD BOOK "D" ON PAGE 89 THROUGH 92 PETITIONED BY C. H. SMITH AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 695 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 24, 1900, WAS ESTABLISHED AS A 40 AND 80 FOOT WIDE ROAD AGREEABLE TO THE SURVEYORS REPORT ON AUGUST 8, 1900 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON SEPTEMBER 3, 1900 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 17-18-11 TO END THIS ROAD SURVEY.

THE CENTERLINE OF THE ROAD IS DESCRIBED AS FOLLOWS:

- 1) FROM THE STONE HE SET AT 20 FEET SOUTH OF THE CENTER CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY HE RAN WEST VARIANCE 9° LAYING THE ROAD 40 FEET WIDE ALL ON THE SOUTH SIDE OF THE 1/2 SECTION LINE 1,149 FEET, THENCE N. 41°30' W. [MAGNETIC MERIDIAN] FOR 115 FEET, THENCE N. 69°15' W. FOR 50 FEET, THENCE S. 47°30' W. FOR 260 FEET, THENCE S. 42°30' W. FOR 121 FEET TO A POINT ON THE 1/2 SECTION LINE 1,595 FEET WEST OF THE CENTER CORNER OF SECTION 16-18-11, THENCE WEST LAYING THE CENTER OF THE ROAD ON THE 1/2 SECTION LINE FOR 3,633 FEET TO THE CENTER CORNER OF SECTION 17-18-11. THE ENTIRE ROAD IS 40 FEET WIDE EXCEPTING 260 FEET RUNNING S. 47°30' W. WHICH IS 80 FEET WIDE. LENGTH OF ROAD IS 5,328 FEET. STONES WERE SET AT ALL ANGLES.
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 11, A ROAD SURVEY RECORDED IN ROAD SURVEY BOOK "E" ON PAGE 191 DATED JULY 24, 1900, FOR A ROAD IN TOWNSHIP 18-11 FOR C. H. SMITH, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE CENTER OF SECTION 17-18-11 TO END THIS ROAD SURVEY FOR A 40 AND 80 FOOT WIDE ROAD.  
THE CENTERLINE OF THE ROAD IS DESCRIBED AS FOLLOWS:
- 1) FROM THE STONE HE SET AT 20 FEET SOUTH OF THE CENTER CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY HE RAN WEST VARIANCE 9° LAYING THE ROAD 40 FEET WIDE ALL ON THE SOUTH SIDE OF THE 1/2 SECTION LINE 1,149 FEET, THENCE N. 41°30' W. [MAGNETIC MERIDIAN] FOR 115 FEET, THENCE N. 69°15' W. FOR 50 FEET, THENCE S. 47°30' W. FOR 260 FEET, THENCE S. 42°30' W. FOR 121 FEET TO A POINT ON THE 1/2 SECTION LINE 1,595 FEET WEST OF THE CENTER CORNER OF SECTION 16-18-11, THENCE WEST LAYING THE CENTER OF THE ROAD ON THE 1/2 SECTION LINE FOR 3,633 FEET TO THE CENTER CORNER OF SECTION 17-18-11. THE ENTIRE ROAD IS 40 FEET WIDE EXCEPTING 260 FEET RUNNING S. 47°30' W. WHICH IS 80 FEET WIDE. LENGTH OF ROAD IS 5,328 FEET. STONES WERE SET AT ALL ANGLES.
- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 184, A **PERMANENT/ROAD** SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 4 REQUESTED BY C. H. SMITH, PRINCIPAL PETITIONER, FOR COUNTY ROAD #626, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 17-18-11 AND THE BEGINNING OF THIS ROAD SURVEY ON THIS **PERMANENT/ROAD SURVEY**. THE SURVEY WAS COMPLETED ON APRIL 19, 1907 AND ENTERED ON APRIL 20, 1907. HE NOTED IN THE TOP RIGHT CORNER THAT THIS ROAD WAS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 373.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) HE RAN NORTH ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-18-11
- 2) THIS ROAD EXTENDS WEST ON THE 1/4 SECTION LINE, PASSING OVER THE SOUTH SIDE OF THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION

18-18-11, FOR 1 MILE TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 18-11-11 TO END THIS ROAD SURVEY

- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 626 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 373 THROUGH 376 PETITIONED BY C. H. SMITH AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 770 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 28, 2907, WAS GRANTED AS A 40 FOOT WIDE ROAD ON APRIL 4, 1907 AS NOTED BY G. H. ARNOLD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY JNO E. MARTIN, COUNTY CLERK, AND RECORDED ON APRIL 20, 1907 BY J. HARRISON PARKMAN, COUNTY SURVEYOR, SAID THAT **HE SET A STONE** AT THE CENTER CORNER OF SECTION 17-18-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 3) HE RAN NORTH ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-18-11
  - 4) THIS ROAD EXTENDS WEST ON THE 1/4 SECTION LINE, PASSING OVER THE SOUTH SIDE OF THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11, FOR 1 MILE TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 18-11-11 TO END THIS ROAD SURVEY
- 5) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT **HE SET AN IRON PIN** FOR THE CENTER CORNER OF SECTION 17-18-11 "IN ACCORDANCE WITH SURVEYS PREVIOUSLY MADE BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS" ON THIS INFORMAL SURVEY.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,649.0' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 17-18-11
  - 2) 5,260.0' NORTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-18-11
  - 3) 7,913.9' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11
  - 4) 2,621.3' EAST TO THE IRON PIN HE SET FOR THE EAST 1/4 CORNER OF SECTION 17-18-11
  - 5) 2,647.0' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 17-18-11
  - 6) 2,638.0' WEST TO THE IRON PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 17-18-11
- 6) THE KRETSINGER REFERENCE TIE BOOKS FOR TOWNSHIP 18-11 SHOWS AN **IRON PIN** AT THE "SW CORNER NE1/4 SECTION 17-18-11".
- 1) 24.9' NW TO AN IRON PIN
  - 2) 45' NE TO AN IRON PIN
- 7) IN A FIELD BOOK IN VAULT IN COUNTY ENGINEER'S OFFICE MARKED "RT. 1078 HEINZ ROAD" ON PAGE 42 FOR A SURVEY BY LESLIE M. GOULD DATED APRIL 1, 1974, SAID THAT HE BEGAN THIS SURVEY AT THE CENTER CORNER OF SECTION 17-18-11. HE DOES NOT DESCRIBE THE "**MONUMENT**" THAT THEY FOUND OR SET AT THE CENTER CORNER OF SECTION 17-18-11.

CENTER CORNER 17-18-11