

**NORTH 1/4 CORNER SECTION 17, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 350 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 17-18-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.85 CHAINS WEST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-18-11
  - 2) 39.85 CHAINS EAST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-11
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 29 RECORDED IN SURVEY BOOK "A" ON PAGES 123 & 124 DATED MARCH 24, 1868 FOR A SURVEY OF R. DENNIS'S, MILLER'S, AND A PART OF C. DRAKE'S LAND, BEING THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 9, AND THE SURVEY THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 ON THIS SURVEY.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 177 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 294 TO 296 PETITIONED BY B. F. KING, THOMAS A. WHITE, AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 & 18-11 [PACKET 420 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 15, 1882, WAS ESTABLISHED AS A 50 FOOT ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** FOR THE NORTH 1/4 CORNER OF SECTION 17-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,620 FEET TO THE "2 MILE STONE" HE SET FOR THE NORTHWEST CORNER OF SECTION 17-18-11; THEN CONTINUES WEST ON THE SECTION LINES FOR ONE MILE TO THE "3 MILE STONE" HE SET FOR THE NORTHWEST CORNER OF SECTION 18-18-11 ON THE RANGE LINE; THEN CONTINUES WEST ON THE SECTION LINE FOR 420' TO THE ANGLE STONE HE SET AT THE INTERSECTION OF THE SECTION LINE WITH THE RIGHT-OF-WAY OF THE M. K. & T. RAILROAD; THENCE N. 55°15' W. ALONG SAID RIGHT-OF-WAY FOR 2,820 FEET TO INTERSECT THE WEST LINE OF THE SE1/4 OF SECTION 12-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 2,658' TO THE "MILE STONE HE SET"; THENCE CONTINUES SOUTH ON THE 1/2 SECTION LINE FOR 2,614' TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 20-18-11; THENCE SOUTH ON THE 1/2 SECTION LINE FOR 2,666' TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 20-18-11 TO COMMENCE THIS ROAD SURVEY
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGE 322 FOR ROAD NUMBER 184 JUNE 15, 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 17-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,658' SOUTH TO THE ROAD STONE HE SET ON THIS SURVEY
- 2) 5,272' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 17-18-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,620' WEST TO THE ROAD STONE HE SET ON THIS SURVEY
  - 4) 5,280' WEST TO THE ROAD STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 18-18-11
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 16 DATED JUNE 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 17-18-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 2,658' SOUTH TO THE ROAD STONE HE SET ON THIS SURVEY
  - 2) 5,272' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 17-18-11
  - 3) 2,620' WEST TO THE ROAD STONE HE SET ON THIS SURVEY
  - 4) 5,280' WEST TO THE ROAD STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 18-18-11
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 107, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 107 DATED JUNE 5, 1885 FOR G. W. WHITE, PRINCIPLE PETITIONER FOR A ROAD IN SECTION 8-18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE QUARTER SECTION LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 TO END THIS ROAD SURVEY
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 302 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 158 TO 160 PETITIONED BY G. W. WHITE AND OTHERS FOR A COUNTY ROAD IN SECTION 8-18-11 [PACKET 533 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 5, 1885, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 9, 1885 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 23, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE 1/4 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-18-11 TO END THIS ROAD SURVEY
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 42, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 DATED APRIL 4, 1902 ORDERED BY LEVI EMMEL FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF SECTION 7-18-11 AND RUN SUCH OTHER LINES AS ARE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN THE ROAD AND STANDING THE WRONG WAY IN THE GROUND** AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACK "M 146" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.76' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-18-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 40.03 CHAINS WEST TO THE 22" X 12" X 3" STONE WITH A CASTING FROM A WELL PULLEY IN THE HOLE WITH THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 7-18-11
  - 3) 80.14 CHAINS WEST TO THE 20" X 12" X 4" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 7-18-11
  - 4) 115.59 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-18-11 ON THE RANGE LINE
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 58, A ROAD SURVEY FOR A ROAD IN TOWNSHIP 18, RANGE 11 PETITIONED BY JASPER GRIMSLEY, RECORDED IN SURVEY BOOK "F" ON PAGE 137 DATED AUGUST 12, 1902, SAID THAT **HE FOUND THE STONE [STANDING THE WRONG WAY IN THE GROUND]** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 27.59 CHAINS TO THE EAST GATE POST IN A FENCE, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINE FOR 12.25 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-18-11 LAYING THE ROAD 60 FEET WIDE, 20 FEET ON THE SOUTH SIDE AND 40 FEET ON THE NORTH SIDE OF THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINES FOR 79.54 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-18-11 TO END THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE
- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 575 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 165 THROUGH 168 PETITION BY JASPER GRIMSLEY AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 714 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 12, 1902, WAS GRANTED AS A 40 AND 60 FOOT WIDE ROAD AS SURVEYED ON NOVEMBER 6, 1902 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON NOVEMBER 11, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE [STANDING THE WRONG WAY IN THE GROUND]** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 SECTION 8-18-11 TO BEGIN THIS ROAD SURVEY  
HIS NOTES/SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 27.59 CHAINS TO THE EAST GATE POST IN A FENCE, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINE FOR 12.25 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-18-11 LAYING THE ROAD 60 FEET WIDE, 20 FEET ON THE SOUTH SIDE AND 40 FEET ON THE NORTH SIDE OF THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINES FOR 79.54 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-18-11 TO END THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE
- 11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 104, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 185 DATED AUGUST 5 TO 25, 1902, AT THE REQUEST OF J. S. CROCK TO RETRACE A McAULEY SURVEY IN SECTION 8-18-11 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER AND SOUTH 1/4 CORNERS OF SECTION 8-18-11, AND ALSO THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 8, AND RUN SUCH LINES AS MAY BE

NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE [STANDING THE WRONG WAY IN THE GROUND]** AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 85 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 145" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.01 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11
- 2) 39.56 CHAINS NORTH TO THE 16" X 12" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-18-11, AND HE SET A RAILROAD LINK BY THE SIDE OF THE STONE
- 3) 79.77 CHAINS NORTH TO THE THEORETICAL LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11 IN THE MIDDLE OF THE ROAD RUNNING WEST AND IN LINE WITH F FENCE RUNNING NORTH
- 4) 19.87 CHAINS EAST TO THE 18" X 7" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-18-11
- 5) 39.74 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-18-11
- 6) HE NOTED THAT A TRANSIT LINE FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11 OVER THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 8-18-11 FELL 75 LINKS NORTH OF THE STONE AT THE SOUTHEAST CORNER OF SECTION 8-18-11

- 12) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 184, A **PERMANENT/ROAD** SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 4 REQUESTED BY C. H. SMITH, PRINCIPAL PETITIONER, FOR COUNTY ROAD #626, SAID THAT **HE FOUND THE NORTH 1/4 SECTION STONE** OF SECTION 17-18-11 ON THIS **PERMANENT/ROAD SURVEY**. THE SURVEY WAS COMPLETED ON APRIL, 1907 AND ENTERED ON APRIL 19, 1907. HE NOTED IN THE TOP RIGHT CORNER THAT THIS ROAD WAS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 373.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) HE RAN SOUTH ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 17-18-11 TO BEGIN THIS ROAD SURVEY, THEN WEST ON THE 1/4 SECTION LINE, PASSING OVER THE SOUTH SIDE OF THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11, FOR 1 MILE TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 18-11-11 TO END THIS ROAD SURVEY

- 13) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 626 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 373 THROUGH 376 PETITIONED BY C. H. SMITH AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 770 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 28, 2907, WAS GRANTED AS A 40 FOOT WIDE ROAD ON APRIL 4, 1907 AS NOTED BY G. H. ARNOLD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY JNO E. MARTIN, COUNTY CLERK, AND RECORDED ON APRIL 20, 1907 BY J. HARRISON PARKMAN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 17-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) HE RAN SOUTH ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 17-18-11 TO BEGIN THIS ROAD SURVEY, THEN WEST ON THE 1/4 SECTION LINE, PASSING OVER THE SOUTH SIDE OF THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11,

FOR 1 MILE TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 18-11-11 TO END THIS ROAD SURVEY

- 14) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT **HE SET AN IRON PIN** FOR THE NORTH 1/4 OF SECTION 8-18-11 ON LINE AND BASED ON THE STONE THAT HE FOUND AS RECORDED IN SURVEYS BY ALVA J. SMITH IN APRIL AND AUGUST 1902 AT THE SOUTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8-18-11, AND THE IRON PIN THAT HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-18-11 ON THIS **INFORMAL SURVEY**. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,637.9' WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-18-11
  - 2) 1,311.0' EAST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-18-11 THAT WAS FOUND BY SMITH
  - 3) 2,622.4' EAST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-18-11 THAT WAS FOUND BY SMITH
  - 4) 2,649' SOUTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 17-18-11 IN ACCORDANCE WITH SURVEYS PREVIOUSLY MADE BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS
  - 5) 5,296.0' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 17-18-11 IN ACCORDANCE WITH SURVEYS PREVIOUSLY MADE BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS
  - 6) 2,611.0' NORTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-18-11
  - 7) 5,264.9' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11
- 15) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS AN **IRON PIN** AT THE "SW CORNER SE1/4 SECTION 8-18-11" AND AT THE "NW CORNER NE1/4 SECTION 17-18-11".
- 1) 26' SE TO A CORNER FENCE POST
  - 2) 28' NW TO A CORNER FENCE POST
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 29, 1992, FOR JOB NUMBER 92926-02 SAID THAT **HE FOUND A 1/2" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 17-18-11 FROM RECORDS IN THE COUNTY ENGINEER'S OFFICE. [**NOTE:** THIS IRON PIN WAS SET BY LESLIE M. GOULD, L.S. 142, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 144 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 1) 38.5' SW TO A CONCRETE NAIL & SHINER IN A POWER POLE
  - 2) 27.3' SE TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
  - 3) IN THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE EAST
  - 4) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE WEST
  - 5) 3.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH

NORTH QUARTER CORNER 17-18-11