

NORTH 1/4 CORNER SECTION 19, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 349 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 37.50 CHAINS WEST TO THE 25" X 11" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 19" X 14" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-18-11

- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 82 DATED APRIL 15, 1865, FOR A SURVEY TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-18-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE NORTH 1/4 CORNER OF SECTION 19-18-11. HE DOES NOT IDENTIFY THE MONUMENT THAT HE FOUND AT THIS CORNER.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.92-1/2 CHAINS SOUTH TO THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 19-18-11 – NOT IDENTIFIED
 - 2) 39.85 CHAINS SOUTH TO THE CENTER CORNER OF SECTION 19-18-11 – NOT IDENTIFIED

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 117 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 39 DATED AUGUST 10, 1873 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE OF SECTION 18-18-11, THE NORTHEAST CORNER OF SECTION 18, THE CENTER CORNER, AND TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 19-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,317' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 18-18-11
 - 2) 2,634' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 18-18-11

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 57 DATED MAY 31, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 11 AT THE REQUEST OF L. ZIMMER, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 19-18-11 ON THIS ROAD SURVEY. NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO AN ANGLE STONE HE SET AT 147.5' NORTH OF THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 19-18-11, THEN EAST FOR 147.5 FEET TO AN ANGLE STONE HE SET, THEN SOUTH FOR 147.5' TO THE STONE HE SET TO BEGIN THIS ROAD SURVEY AT 147.5' EAST OF THE SOUTHWEST CORNER OF THE NW1/4 OF SEC. 19-18-11
 - 2) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18-18-11 TO END THIS ROAD SURVEY

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 108, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 92 DATED JUNE 4, 1886 FOR A ROAD IN TOWNSHIP 18, RANGE 11 FOR ORRIN SMITH, PRINCIPAL PETITIONER, APPARENTLY

FOUND THE STONE AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 19-19-11 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE LINE RUN. **HE NOTED:** "STONES HAVING PROPER MARKS WERE SET IN THEIR RESPECTIVE PLACES".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO AN ANGLE STONE HE SET AT 147.5' NORTH OF THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 19-18-11, THEN EAST FOR 147.5 FEET TO AN ANGLE STONE HE SET, THEN SOUTH FOR 147.5' TO THE STONE HE SET TO BEGIN THIS ROAD SURVEY AT 147.5' EAST OF THE SOUTHWEST CORNER OF THE NW1/4 OF SEC. 19-18-11
 - 2) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18-18-11 TO END THIS ROAD SURVEY
- 5) MATHEW BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 341 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 314 TO 316 PETITION BY ORRIN SMITH AND 68 OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 558 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1886, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE LINE RUN, ON OCTOBER 30, 1886 BY T. E. McMILLAN, CHAIRMAN OF THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MARCH 10, 1887 BY ROLAND LAKIN, LYON COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 19-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO AN ANGLE STONE HE SET AT 147.5' NORTH OF THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 19-18-11, THEN EAST FOR 147.5 FEET TO AN ANGLE STONE HE SET, THEN SOUTH FOR 147.5' TO THE STONE HE SET TO BEGIN THIS ROAD SURVEY AT 147.5' EAST OF THE SOUTHWEST CORNER OF THE NW1/4 OF SEC. 19-18-11
 - 2) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18-18-11 TO END THIS ROAD SURVEY
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **SANDSTONE AND IRON PIN** AT THE "S1/4 18-18-11" ON JULY 19, 1954.
- 1) 30.5' WNW TO AN IRON PIN
 - 2) 27.5' NW TO AN IRON PIN
 - 3) 63.0' NNW TO AN ASH TREE

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 29, 1992, FOR JOB NUMBER 92026-02, SURVEY F18003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE WEST HALF OF THE SOUTHWEST QUARTER OF THE NORTHEAST QUARTER AND A TRACT OF 7.0 ACRES IN SECTION 18-18-11 FILED FEBRUARY 7, 1992 IN VOLUME 463 ON PAGE 859 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND A SQUARE 5/8" REBAR OVER THE SANDSTONE** AT THE SOUTH 1/4 CORNER OF SECTION 18-18-11 AS REFERENCED BY LESLIE M. GOULD, L.S. 142, IN 1954.

- 1) 8.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 2) NO OTHER REFERENCES AVAILABLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,673.64' EAST TO THE DETERIORATING LIMESTONE WITH A 1" X 9" X 15" CAP STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-18-11. HE DROVE A 1/2" REBAR WITH HIS "LS 752" CAP THROUGH THE LIMESTONE

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 2,639.96' NORTH TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 18-18-11
 - 3) 3,961.88' NORTH TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 18-18-11
 - 4) 5,283.81' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-18-11
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 11, 2000, FOR PROJECT NUMBER 00238-02, SURVEY F18004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A RETRACEMENT OF PART OF A LYON COUNTY ROAD RECORDED IN ROAD RECORD BOOK "D" AT PAGE 285 (1905), SAID THAT **HE FOUND A 1" PIPE WITH A 1-1/4" PIN SET ON THE EAST SIDE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 18-18-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. **[NOTE: HIS PREVIOUS SECTION CORNER REPORT DATED JANUARY 29, 1992 STATES THAT HE FOUND A SQUARE 5/8" REBAR OVER THE SANDSTONE AT THIS CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640.10' NORTH TO THE 1/2" REBAR WITH HIS "LS 7852" CAP FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 18-18-11
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F18005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED JANUARY 19, 2001 FOR PROJECT NUMBER 01006-02 FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 18-18-11, BEING ALL OF THAT PART OF THE OLD M. K. & T. RAILROAD LYING IN SAID SOUTHWEST QUARTER, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1" PIPE WITH A 1-1/4" IRON PIN ON THE EAST SIDE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 18-18-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. **[NOTE: HIS PREVIOUS SECTION CORNER REPORT DATED JANUARY 29, 1992 STATES THAT HE FOUND A SQUARE 5/8" REBAR OVER THE SANDSTONE AT THIS CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640.10' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 18-18-11

NORTH QUARTER CORNER 19-18-11