

NORTHWEST CORNER SECTION 19, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 49 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 11" X 3-1/2"** FOR THE CORNER TO SECTIONS 18 & 19-18-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 28, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 37.50 CHAINS EAST TO THE 19" X 11" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-18-11
 - 2) 77.50 CHAINS EAST TO THE 19" X 14" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-18-11
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 27" X 15" X 2" SANDSTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 19-18-11
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE POST THEY SET FOR THE CORNER TO SECTIONS 19 & 30-18-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY ON REVIEW FROM THE ORIGINAL SURVEY OF SEPTEMBER 10, 1858, AND ESTABLISHED NOVEMBER 1, 1858, RECORDED IN SURVEY BOOK "A" ON PAGES 26, 27 & 28 DATED FEBRUARY 15, 1859 FOR THE COUNTY ROAD FROM EMPORIA TO AMERICUS, SAID THAT **HE FOUND THE STONE POST** AT THE SOUTHWEST CORNER OF SECTION 18-18-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

- 3) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 30 [PACKET 916 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ON THE PETITION OF A. W. BAKER FOR A CHANGE IN THE "EMPORIA AND AMERICUS ROAD" ESTABLISHED JANUARY 7, 1861 IN THE COMMISSIONERS JOURNAL ON PAGE 133, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-18-10 ON THE RANGE LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SECTION 13-18-10, AT A TURN TO THE WEST
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SECTION 24-18-10, AT A TURN TO THE EAST TO THE CENTER CORNER OF SECTION 19-18-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 103 RECORDED IN SURVEY BOOK "A" ON PAGE 195 DATED MARCH 29, 1869 FOR A SURVEY OF SECTION 24-18-10, TO REESTABLISH THE 1/4 CORNER ON THE SOUTHERN BOUNDARY AND ALSO THE CENTER CORNER OF SECTION 24-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-18-11 ON THE RANGE LINE ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 161 RODS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 24-18-10
 - 2) 322 RODS, 7 LINKS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-10
 - 3) 320 RODS SOUTH ON THE RANGE LINE TO THE POST HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-18-10

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 117 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 39 DATED AUGUST 10, 1873 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE OF SECTION 18, THE NORTHEAST

CORNER OF SECTION 18, THE CENTER CORNER OF SECTION 18, AND TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE EAST AND WEST, ALL IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 18-18-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,315' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 18-18-11
- 2) 2,630' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 18-18-11

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 172, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 172 DATED JUNE 7-15, 1887 ORDERED BY O. C. BREWSTER TO LOCATE THE CORNERS OF THE SOUTHEAST 1/4 OF SECTION 13-18-10 ON THE RANGE LINE, SAID THAT **HE SET A 7" X 9" X 22" LIMESTONE** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' NORTH ON THE RANGE LINE TO THE 6" X 6" X 28" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 13-18-10, WHERE HE FOUND THE REMAINS OF THE OLD STONE AND AN OLD STAKE
- 2) 5,280' NORTH ON THE RANGE LINE TO THE REMAINS OF THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 13-18-10
- 3) 10,565' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 12-18-10
- 4) 2,669' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 13-18-10
- 5) 5,338' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 13-18-10

- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE 8" X 6" TOP** AT THE "SW CORNER SECTION 18-18-11" ON THE RANGE LINE ON JULY 19, 1954 AND NOTED THAT THE STONE IS "IN A FIELD".

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 27, 2000, FOR PROJECT NUMBER 00041-02, SAID THAT HE DEEMED THE NORTHEAST CORNER OF SECTION 13-18-10 WAS **LOST** AS IT FALLS IN A CREEK. HE RESET THIS CORNER BY SINGLE PROPORTIONATE MEASUREMENT ALONG THE RANGE LINE. **HE SET A 5/8" X 24" CAPPED REBAR WITH A LYON COUNTY CAP AS A WITNESS CORNER AT 25.0' NORTH OF THE TRUE POSITION** OF THE NORTHEAST CORNER OF SECTION 13-18-10 ON THE RANGE LINE. HE SET A SURVEY MARKER ON THE SOUTH SIDE OF THIS WITNESS CORNER. HE SAID THAT NO REFERENCES WERE AVAILABLE.

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING FROM THE TRUE CORNER:

- 1) 2,643.01' NORTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SEC. 13-18-10
- 2) 2,643.01' SOUTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SEC. 24-18-10
- 3) 5,286.00' SOUTH ON THE RANGE LINE TO THE SOUTHEAST CORNER OF SECTION 24-18-10
- 4) 2,673.23' WEST TO THE SOUTH 1/4 CORNER OF SECTION 13-18-10
- 5) 5,352.46' WEST TO THE SOUTHWEST CORNER OF SECTION 13-18-10

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2001, FOR PROJECT NUMBER 01414-02, SAID THAT **HE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP WITNESS CORNER** FOR THE NORTHWEST CORNER OF SECTION 19-18-11 ON THE RANGE LINE FROM HIS PREVIOUS SURVEY IN APRIL 2000.

- 1) ON LINE WITH THE EAST 1/4 CORNER AND **25.0' NORTH OF TRUE POSITION**
- 2) SURVEY MARKER ON THE NORTH SIDE OF THE REBAR
- 3) NO OTHER REFERENCES AVAILABLE

NORTHWEST CORNER 19-18-11