

NORTH 1/4 CORNER SECTION 20, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 349 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 23" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.90 CHAINS WEST TO THE 19" X 14" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-18-11
 - 2) 39.90 CHAINS EAST TO THE 24" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-18-11

- 2) D. W. BOWMAN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 66 RECORDED IN SURVEY BOOK "A" ON PAGE 166 DATED JULY 22, 1868 FOR S SURVEY OF LAND OWNED BY JOHN WHITE AND OTHERS, BEING SECTION 20-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 20-18-11 ON THIS SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 16 DATED JUNE 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 20-18-11 ON THIS ROAD SURVEY.

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 177 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 294 TO 296 PETITIONED BY B. F. KING, THOMAS A. WHITE, AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 & 18-11 [PACKET 420 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 15, 1882, WAS ESTABLISHED AS A 50 FOOT ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** FOR THE NORTH 1/4 CORNER OF SECTION 20-18-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 2,614 FEET TO THE "1 MILE STONE" HE SET; THEN CONTINUES NORTH ON THE 1/2 SECTION LINE FOR 2,658 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-18-11; THEN EXTENDS WEST ON THE SECTION LINES FOR 2,620 FEET TO THE "2 MILE STONE" HE SET FOR THE NORTHWEST CORNER OF SECTION 17-18-11; THEN CONTINUES WEST ON THE SECTION LINES FOR ONE MILE TO THE "3 MILE STONE" HE SET FOR THE NORTHWEST CORNER OF SECTION 18-18-11 ON THE RANGE LINE; THEN CONTINUES WEST ON THE SECTION LINE FOR 420' TO THE ANGLE STONE HE SET AT THE INTERSECTION OF THE SECTION LINE WITH THE RIGHT-OF WAY OF THE M. K. & T. RAILROAD; THENCE N. 55°15' W. ALONG SAID RIGHT -OF-WAY 2,820 FEET TO INTERSECT THE WEST LINE OF THE SE1/4 OF SECTION 12-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 2,666' TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 20-18-11 TO COMMENCE THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGE 322 FOR ROAD NUMBER 184 DATED JUNE 15, 1882, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-18-11 ON THIS ROAD SURVEY.
HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,666' SOUTH TO THE STONE AT THE CENTER CORNER OF SECTION 20-18-11

- 6) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 54 DATED MAY 28, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 11 FOR E. D. CHILDERS, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 SECTION CORNER OF SECTION 17-18-11 FOR THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO A POINT 40 LINKS WEST OF THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 21-18-11 AND DEVIATES TO THE NORTH TO AVOID LITTLE'S HOUSE, AND THEN INTERSECTS THE SECTION LINE WITHIN 20 FEET OF THE SOUTH 1/4 CORNER OF SECTION 16-18-11 AND CONTINUES EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY
 - 2) FROM THE ABOVE NAMED 1/16TH CORNER TO ALLEN CREEK THE ROAD IS ALL SOUTH OF LINE, FROM ALLEN CREEK TO THE TERMINUS THE ROAD IS 15 FEET ON THE SOUTH SIDE OF LINE AND 28 FEET ON THE NORTH SIDE OF LINE
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 219 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 462 TO 464 PETITION BY E. D. CHILDERS AND OTHERS TO LOCATE A COUNTY ROAD IN TOWNSHIP 18-11 [PACKET 460 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 28, 1883 AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 3, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 17-18-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3/4 OF A MILE TO A POINT 41 LINKS WEST OF THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 21-18-11; THEN ANGLES NORTHEASTERLY THROUGH SEVERAL ANGLES TO AVOID LITTLE'S HOUSE AND INTERSECTS THE SECTION LINE "WITHIN 20 FEET" EAST OF THE SOUTH 1/4 CORNER OF SECTION 16-18-11; THEN CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY
 - 2) FROM THE ABOVE NAMED 1/8TH CORNER TO ALLEN CREEK THE ROAD IS ALL SOUTH OF LINE, FROM ALLEN CREEK TO THE TERMINUS THE ROAD IS 15 FEET ON THE SOUTH SIDE OF LINE AND 28 FEET ON THE NORTH SIDE OF LINE ACCORDING TO THE WORDING IN SURVEY BOOK "F" ON PAGE 54 AS THE DESCRIPTION ON PAGE 462 DOES NOT MAKE SENSE
- 8) REA BOOK 31 ON PAGE 1 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 20-18-11 AT 2,649.2 FEET NORTH OF THE CENTER CORNER OF SECTION 20-18-11.
- 1) 21' EAST TO A WITNESS PIN
- 9) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20-18-11, SAID THAT **HE SET AN IRON PIN** FOR THE NORTH 1/4 OF SECTION 20-18-11 ON THIS INFORMAL SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,638.1' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-18-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 2,620.3' EAST TO THE STONE HE HAD PREVIOUSLY SET FOR THE NORTHEAST CORNER OF SECTION 20-18-11
 - 3) 5,241.2' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21-18-11
 - 4) 7,799.7' EAST TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11 THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
 - 5) 2,647.0' NORTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 17-18-11 IN ACCORDANCE WITH SURVEYS PREVIOUSLY MADE BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS
 - 6) 5,296.0' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 17-18-11 IN ACCORDANCE WITH SURVEYS PREVIOUSLY MADE BY PARKMAN, SMITH, MILLIKEN AND ALL FORMER COUNTY SURVEYORS
 - 7) 7,907.0' NORTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-18-11
 - 8) 10,560.9' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-18-11
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 32
ON MARCH 18, 1946 A PETITION SIGNED BY T. H. McCOLM AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND E. C. GOLDSMITH, COUNTY ENGINEER, ON APRIL 11, 1946 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON APRIL 18, 1946 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT A POINT 30 RODS WEST AND 116 FEET NORTH OF THE SOUTH 1/4 CORNER OF SECTION 16-18-11; THENCE WEST THROUGH AND ALONG THE SOUTH SIDE OF SAID SECTION 16 AND ALONG THE SOUTH SIDE OF SECTION 17-18-11 TO THE SOUTH 1/4 CORNER OF SAID SECTION 17 AND ENDING THERE.
 - 2) THIS ROAD SHOULD BE VACATED. THE ROAD HAS HAD LITTLE USE FOR SEVERAL YEARS AND WE DO NOT BELIEVE THAT THERE IS SUFFICIENT DEMAND FOR THE ROAD TO MAKE IT PRACTICAL FOR THE TOWNSHIP AND COUNTY TO MAINTAIN IT TO A POINT 279 FEET EAST OF THE NORTH 1/4 CORNER OF SECTION 20-18-11.
- 11) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SW CORNER SE1/4 SECTION 17-18-11", BUT THERE ARE NO TIES ON THE PAGE.
- 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS AN **IRON PIN** AT THE "NW CORNER NE1/4 SECTION 20-18-11".
- 1) 14' WEST TO AN IRON PIN
 - 2) 17' WEST TO AN IRON PIN
 - 3) 1' NORTH OF A CORNER POST
- 13) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF TWO TRACTS IN THE SOUTHEAST 1/4 OF SECTION 17-18-11 DATED MAY 31, 1977, SHOWS ON AN AERIAL PHOTOGRAPH A "**MONUMENT**" AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 17-18-11. HE DOES NOT DESCRIBE THE MONUMENT AT THIS CORNER.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 578' NORTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF THE SOUTH TRACT
 - 2) 917.30' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE SOUTH TRACT
 - 3) 1,329.80' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE NORTH TRACT

- 14) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F17002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TH SURVEY OF A 16.9 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 17-18-11, SHOWS ON AN AERIAL PHOTOGRAPH A “**MONUMENT**” AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 17-18-11, BEING THE SOUTHWEST CORNER OF THE 16.9 ACRE TRACT. THERE IS NO DATE ON THE SURVEY AND THERE IS NO DESCRIPTION OF THE MONUMENT THAT HE FOUND OR SET AT THIS CORNER.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
1) 578’ NORTH TO THE IRON PIN AT THE NORTHWEST CORNER OF THE 16.9 ACRE TRACT
- 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 1, 2005, FOR PROJECT NUMBER 05362-02, SURVEY F20001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 6.69 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 20-18-11 FOR PAUL HANCOCK/MICHAELS, SAID THAT **HE FOUND A 3/4” REBAR AT 14” DEEP** AT THE NORTH 1/4 CORNER OF SECTION 20-18-11. **HE SET A 5/8” X 12” REBAR WITH A LYON COUNTY CAP** OVER THE FOUND 3/4" REBAR FOR THE NORTH 1/4 CORNER OF SECTION 20-18-11.
1) 69.0’ SSW TO THE NEAR FACE OF A PIPE CORNER FENCE POST
2) 30’ SOUTH TO THE CENTER OF A FIELD ENTRANCE TO THE EAST
3) 13.0’ EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD “H5” NORTH-SOUTH
4) 8.0’ NORTH TO THE CENTER OF A FIELD ENTRANCE TO THE EAST
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
1) 2,684.18’ SOUTH TO THE 5/8” REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 20-18-11
2) 3,124.18’ SOUTH TO THE 1/2" REBAR WITH HIS “LS 752” CAP HE SET FOR THE SOUTHWEST CORNER OF THE 6.69 ACRE TRACT
3) 5,355.38’ SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 20-18-11

NORTH QUARTER CORNER 20-18-11