

NORTHWEST CORNER SECTION 20, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 348 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 19" X 14" X 3"** FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.90 CHAINS EAST TO THE 23" X 15" X 2" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-18-11
 - 2) 79.80 CHAINS EAST TO THE 24" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-18-11

- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 82 DATED APRIL 15, 1865, FOR A SURVEY TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-18-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE NORTHEAST CORNER OF SECTION 19-18-11. HE DOES NOT IDENTIFY THE MONUMENT THAT HE FOUND AT THIS CORNER.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.96-1/2 CHAINS SOUTH TO THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 19-18-11
 - 2) 39.93 CHAINS SOUTH TO THE EAST 1/4 CORNER OF SECTION 19-18-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 117 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 39 DATED AUGUST 10, 1873 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE OF SECTION 18, THE NORTHEAST CORNER OF SECTION 18, THE CENTER CORNER, AND TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE EAST AND WEST, ALL IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTIONS 18-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,640' NORTH TO THE OLD STONE HE FOUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 18-18-11
 - 2) 5,280' NORTH TO THE OLD STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 18-18-11
 - 3) 7,920' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-18-11

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 42, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 223 DATED APRIL 4, 1902 ORDERED BY LEVI EMMEL FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF SECTION 7-18-11 AND RUN SUCH OTHER LINES AS ARE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 18-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 42, AND THERE IS ADDITIONAL INFORMATION IN PACK "M 146" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
 - 1) STONE IS AT THE SOUTH END OF A FENCE
 - 2) HEDGE RUNNING SOUTH IS 27 LINKS WEST OF THE STONEHIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.08 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11
 - 2) 80.22 CHAINS NORTH TO THE 22" X 12" X 3" STONE WITH A CASTING FROM A WELL PULLEY IN THE HOLE WITH THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 7-18-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 120.33 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-18-11
- 5) REA BOOK 30 ON PAGE 13 SHOWS THAT **THEY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 20-18-11 AT 32' SOUTHEAST OF A WITNESS PIN ABOUT 8" SOUTH OF A STONE POST, AND 28 FEET SOUTHWEST OF A WITNESS PIN 1 FOOT OR SO SOUTHWEST OF A FENCE CORNER POST.
- 6) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20, SAID THAT SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 20-18-11 THAT WAS FOUND BY ALVA J. SMITH IN A SURVEY RECORDED IN APRIL 1902 ON THIS **INFORMAL SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.5' NORTH TO THE IRON PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 17-18-11
 - 2) 5,295.7' NORTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-18-11 BASED ON SMITHS SURVEY
 - 3) 7,943.0' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-18-11 THAT WAS FOUND BY SMITH
 - 4) 9,266.6' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 8-18-11 THAT WAS FOUND BY SMITH
 - 5) 10,593.2' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF SECTION 8-18-11 BASED ON SMITHS SURVEY
 - 6) 2,673.6' SOUTH TO THE IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 20 THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
 - 7) 2,638.1' EAST TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 20-18-11
 - 8) 5,258.4' EAST TO THE STONE HE HAD PREVIOUSLY SET FOR THE NORTHEAST CORNER OF SECTION 20-18-11
 - 9) 7,879.3' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21-18-11
 - 10) 10,473.8' EAST TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11. THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SW CORNER NW1/4 SECTION 17-18-11" AND "NW CORNER SECTION 20-18-11", BUT THERE ARE NO TIES ON THE PAGE.
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SE CORNER SECTION 18-18-11".
 - 1) 1' EAST OF A CORNER FENCE POST
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F18003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE WEST HALF OF THE SOUTHWEST QUARTER OF THE NORTHEAST QUARTER AND A TRACT OF 7.0 ACRES IN SECTION 18-18-11 FILED FEBRUARY 7, 1992 IN VOLUME 463 ON PAGE 859 IN THE REGISTER OF DEEDS OFFICE FOR JOB NUMBER 92026-01, STATES IN HIS *SURVEY NOTES* THAT **HE FOUND A DETERIORATING LIMESTONE ABOUT 1 FOOT WEST OF THE EXISTING CORNER POST** AT THE SOUTHEAST CORNER OF SECTION 18-18-11. THE LIMESTONE WAS FOUND WITH A 1" X 9" X 15" CAP STONE OVER IT. HE SAID THAT GOULD'S CALL FOR THE STONE WAS 1 FOOT EAST OF THE POST. **HE DROVE A #4 REBAR WITH HIS "LS 752" CAP THROUGH THE STONE AT THE SOUTHEAST CORNER OF SECTION 18-18-11.** HE SAID THAT THE GLO NOTES

CALLED FOR A SANDSTONE AT THIS CORNER. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,673.64' WEST TO THE SANDSTONE AND REBAR HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 18-18-11, AS REFERENCED BY L. M. GOULD, L.S. 142
- 2) 2,646.34' NORTH TO THE OLD "CON" RIBBED #5 REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-18-11
- 3) 5,294.98' NORTH TO THE STONE WITH A WELL PULLEY CASING HE FOUND ABOUT 2' DEEP AT THE NORTHEAST CORNER OF SECTION 18-18-11. HE SET A 1/2" REBAR WITH HIS "LS 752" CAP OVER THE STONE
- 4) 7,941.10' NORTH TO THE STONE WITH A GAS PIPE ON THE EAST SIDE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-18-11

NORTHWEST CORNER 20-18-11