

NORTH 1/4 CORNER SECTION 21, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 343 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.08 CHAINS WEST TO THE 24" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-18-11
 - 2) 40.07 CHAINS EAST TO THE 23" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-18-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 10 RECORDED IN SURVEY BOOK "A" ON PAGE 7 DATED APRIL 27, 1858, A **PERMANENT SURVEY** OF THE TOWNSITE OF FREMONT, BEING THE EAST 1/2 OF SECTION 21-18-11, SAID THAT **HE FOUND THE NORTH 1/4 STONE POST** OF SECTION 21-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,663' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11

- 3) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 24 & 25 [PACKET 437 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "FOREST HILL TO AMERICUS" ROAD IN BRECKENRIDGE COUNTY DATED APRIL 1859 FOR THE "FOREST HILL TO AMERICUS ROAD" SURVEYED MARCH 30 THROUGH APRIL 1, 1859 AND ESTABLISHED APRIL 27, 1859 IN THE COMMISSIONERS JOURNAL ON PAGE 66, APPARENTLY **FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 21-18-11 AT THE NORTHWEST CORNER OF THE TOWN OF FREMONT ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE CENTER CORNER OF SECTION 28-18-11 AT A TURN TO THE EAST THROUGH THE TOWN OF FREMONT
 - 2) THIS ROAD EXTENDS NORTHWESTERLY TO THE TOWN OF AMERICUS TO END THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY L. A. HAMBLIN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 184 TO 186 [PACKET 30 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] PETITIONED BY H. W. PEARSALL AND OTHERS, THAT HE SURVEYED APRIL 21, 1871 AND WAS ORDERED ESTABLISHED AND RECORDED BY THE BOARD OF COMMISSIONERS AS A 50 FOOT WIDE ROAD ON OCTOBER 2, 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND** THE SOUTH 1/4 CORNER OF SECTION 21-18-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 20.14 CHAINS TO THE NORTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 21-18-11 AT A TURN TO THE SOUTH
 - 2) THIS ROAD EXTENDS NORTH ON THE CENTERLINE OF THE SECTIONS FOR 160.00 CHAINS TO THE NORTH 1/4 CORNER OF SECTION 9-18-11 AT A TURN TO THE EAST

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 54 DATED MAY 28, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 11 FOR E. D. CHILDERS, PRINCIPAL PETITIONER, SAID THAT **HE FOUND**

THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 16-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD DEVIATES FROM THE SECTION LINE AT A POINT "WITHIN 20 FEET" EAST OF THIS 1/4 CORNER AND EXTENDS EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-18-11 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD INTERSECTS THE SECTION LINES AT 40 LINKS WEST OF THE STONE HE FOUND AT THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 16-18-11, AND CONTINUES WEST ON THE SECTION LINES FOR 3/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 20-18-11 FOR THE TERMINUS OF THIS ROAD SURVEY
- 3) FROM THE ABOVE NAMED 1/16TH CORNER TO ALLEN CREEK THE ROAD IS ALL SOUTH OF LINE, FROM ALLEN CREEK TO THE TERMINUS THE ROAD IS 15 FEET ON THE SOUTH SIDE OF LINE AND 28 FEET ON THE NORTH SIDE OF LINE

- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 219 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 462 TO 464 PETITION BY E. D. CHILDERS AND OTHERS TO LOCATE A COUNTY ROAD IN TOWNSHIP 18-11 [PACKET 460 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 28, 1883 AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 3, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 16-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD INTERSECTS THE SECTION LINES AT 41 LINKS WEST OF THIS 1/16TH CORNER AND EXTENDS EAST ON THE SECTION LINES FOR 3/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 17-18-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD INTERSECTS THE SECTION LINE "WITHIN 20 FEET" EAST OF THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 16-18-11; THEN CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-18-11 TO BEGIN THIS ROAD SURVEY
- 3) FROM THE ABOVE NAMED 1/8TH CORNER TO ALLEN CREEK THE ROAD IS ALL SOUTH OF LINE, FROM ALLEN CREEK TO THE TERMINUS THE ROAD IS 15 FEET ON THE SOUTH SIDE OF LINE AND 28 FEET ON THE NORTH SIDE OF LINE ACCORDING TO THE WORDING IN SURVEY BOOK "F" ON PAGE 54 AS THE DESCRIPTION ON PAGE 462 DOES NOT MAKE SENSE

- 7) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 120 RECORDED IN SURVEY BOOK "A" ON PAGES 207 & 208 DATED MAY 25 & 26, 1868 FOR A SURVEY OF LAND SITUATED IN SECTION 21-18-11, TO REESTABLISH THE 1/4 CORNERS ON THE EASTERN AND WESTERN BOUNDARIES, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 21-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 21-18-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 77 RODS, 1 LINK EAST TO THE STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 21-18-11
- 2) 154 RODS, 2 LINKS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11
- 3) 80 RODS, 2-1/2 LINKS SOUTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 21-18-11
- 4) 160 RODS, 5 LINKS SOUTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 21-18-11

CONTINUED ON PAGE 3

- 8) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 630 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 389 THROUGH 392 PETITION BY C. M. McCOLM AND OTHERS FOR THE VACATION AND REESTABLISHMENT OF A ROAD IN TOWNSHIP 18-11 [PACKET 895 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY, 1907, AND WAS ALLOWED AS A 40 FOOT WIDE ROAD, 20 FEET EACH SIDE OF THE SURVEYED LINE, ON AUGUST 9, 1907 AS NOTED BY G. F. ARNOLD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 10, 1907 BY J. HARRISON PARKMAN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 16-18-11, AS HE ENDED THIS ROAD SURVEY AT A POINT 116 FEET NORTH OF THIS CORNER. THE OLD ROAD BETWEEN THE BEGINNING AND TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY WAS **VACATED** AS PETITIONED. SEE THE ROAD SURVEY FOR THE DESCRIPTION OF THE CENTERLINE OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 9) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 198, A ROAD SURVEY FOR COUNTY ROAD #630 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 21 AT THE REQUEST OF C. M. McCOLM, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 16-18-11, AS HE ENDED THIS ROAD SURVEY AT A POINT 116 FEET NORTH OF THIS CORNER ON THIS **PERMANENT SURVEY**. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS ALSO RECORDED IN ROAD RECORD BOOK "D" ON PAGE 389. THERE IS NO DATE ON THIS ROAD SURVEY AND THERE IS NO WIDTH RECORDED. SEE THE SURVEY FOR THE DESCRIPTION OF THE CENTERLINE OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 10) REA BOOK 30 ON PAGE 2 SHOWS A **STONE** AT THE SOUTH 1/4 CORNER OF SECTION 16-21-11, BUT THERE ARE NO TIES ON THE PAGE.
- 11) REA BOOK 30 ON PAGE 4 GIVES THE FOLLOWING TIES TO THE SOUTH 1/4 CORNER OF SECTION 16-21-11, BUT NO DESCRIPTION OF THE "**MONUMENT**" THAT WAS FOUND OR SET:
- 1) 27' NORTH TO A WITNESS PIN
- 12) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 144 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 20-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 OF SECTION 21-18-11 ON THIS INFORMAL SURVEY. THERE ARE NO TIES ON THIS INFORMAL SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,558.5' EAST TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11 THAT WAS SET BY AI CHAMNESS ON A REA SURVEY
 - 2) 2,620.9' WEST TO THE 18" X 9" X 4" LIMESTONE HE SET FOR THE NORTHEAST CORNER OF SECTION 20-18-11
 - 3) 5,241.2' WEST TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 20-18-11
 - 4) 7,879.3' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-18-11
- 13) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 32
ON MARCH 18, 1946 A PETITION SIGNED BY T. H. McCOLM AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY

COMMISSIONERS AND E. C. GOLDSMITH, COUNTY ENGINEER, ON APRIL 11, 1946 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON APRIL 18, 1946 VACATED THE FOLLOWING ROAD:

- 1) BEGINNING AT A POINT 30 RODS WEST AND 116 FEET NORTH OF THE SOUTH 1/4 CORNER OF SECTION 16-18-11; THENCE WEST THROUGH AND ALONG THE SOUTH SIDE OF SAID SECTION 16-18-11 AND ALONG THE SOUTH SIDE OF SECTION 17-18-11 TO THE SOUTH 1/4 CORNER OF SAID SECTION 17-18-11 AND ENDING THERE.
 - 2) THIS ROAD SHOULD BE VACATED. THE ROAD HAS HAD LITTLE USE FOR SEVERAL YEARS AND WE DO NOT BELIEVE THAT THERE IS SUFFICIENT DEMAND FOR THE ROAD TO MAKE IT PRACTICAL FOR THE TOWNSHIP AND COUNTY TO MAINTAIN IT TO A POINT 279 FEET EAST OF THE NORTH 1/4 CORNER OF SECTION 20-18-11.
- 14) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SW CORNER SE1/4 SECTION 16-18-11":
- 1) 26.0' WEST OF NORTH TO A SPIKE & WASHER
 - 2) 22.0' SOUTH TO A SPIKE IN A TELEPHONE POLE
- 15) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21003 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO EQUALLY DIVIDE A 40 ACRE TRACT OF GROUND LOCATED IN THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED OCTOBER 29, 1973, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 21-18-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 442.81' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 2) 885.62' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 3) 1,328.43' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11
- 16) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21001 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO LOCATE THE CORNERS TO A 2 ACRE TRACT OF GROUND LOCATED IN THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED JUNE 25, 1974, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 21-18-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,279.5' EAST TO THE "IRON PIN IN PLACE" HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11
- 17) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21002 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO LOCATE THE CORNERS TO A 4 ACRE TRACT OF GROUND LOCATED IN THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED JUNE 25, 1974, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 21-18-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,279.5' EAST TO THE "PIN IN PLACE" HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11
- 18) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21005 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO SET ASIDE 50 ACRES IN A TRACT COMPOSED OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND ALL THAT PART OF THE SOUTH 1/2 OF THE NORTHWEST 1/4

LYING EAST OF ALLEN CREEK, ALL IN SECTION 21-18-11 DATED SEPTEMBER 9, 1975, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 21-18-11. THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,278.5' EAST TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11

- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F21010 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR PROJECT NUMBER 04032-02 DATED MARCH 4, 2004 FOR THE SURVEY OF A TRACT IN THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 21-18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 21-18-11 USING DISTANCES FROM A PRIOR SURVEY BY LESLIE M. GOULD DATED JUNE 1974 [SURVEY #F21001 IN THE OFFICE OF THE COUNTY ENGINEER].

- 1) 1/2" REBAR ON SOUTH SIDE CENTER OF THE STONE FOUND
- 2) 3.25' SSW TO A CUTOFF T-POST
- 3) 9.5' WEST TO A 40 D NAIL & WASHER IN A STEEL FENCE POST
- 4) 9.4' SW TO A CONCRETE NAIL & BOTTLECAP IN A FENCE POST
- 5) 17.1' SSW TO A 40 D NAIL & WASHER IN THE TOP OF A FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 719.29' EAST TO THE 40 D NAIL HE SET FOR THE NORTHWEST TRACT CORNER, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' SOUTH
- 2) 1,280.29' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11, FROM A PRIOR SURVEY BY L. M. GOULD DATED JUNE 1974 [GOULD = 1,279.5']
- 3) 885.35' SOUTH TO THE 1/2" REBAR HE FOUND FROM A PRIOR SURVEY BY L. M. GOULD DATED JUNE 1974, AT 5.5' EAST OF THE TRUE POSITION [GOULD = 885.62']
- 4) 1,327.90' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11, FROM A PRIOR SURVEY BY L. M. GOULD DATED JUNE 1974 [GOULD = 1,328.43']

- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2004, FOR PROJECT NUMBER 04024-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE EAST LINE OF THE WEST HALF OF THE OF THE NORTHWEST QUARTER OF SECTION 16-18-11, SAID THAT **HE FOUND THE STONE WITH A 1/2" REBAR ON THE SOUTH SIDE CENTER OF THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 16-18-11 USING DISTANCES FROM A PRIOR SURVEY BY LESLIE M. GOULD DATED JUNE 1974 AND HIS TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED MARCH 4, 2004.

- 1) **1/2" REBAR ON THE SOUTH SIDE OF THE CENTER OF THE STONE FOUND**
- 2) 3.25' SSW TO A CUT-OFF "T"-POST
- 3) 9.5' WEST TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 4) 9.4' SW TO A CONCRETE NAIL IN A FENCE POST
- 5) 17.1' SSW TO A 40 D SPIKE & WASHER IN THE TOP OF A FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,651.50' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 16-21-11
- 2) 5,306. 19' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 16-21-11
- 3) 2,558.68' EAST TO THE 5/8" SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 16-21-11

NORTH QUARTER CORNER 21-18-11

