

**NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 21, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 120 RECORDED IN SURVEY BOOK "A" ON PAGES 207 & 208 DATED MAY 25 & 26, 1868 FOR A SURVEY OF LAND SITUATED IN SECTION 21-18-11, TO REESTABLISH THE 1/4 CORNERS ON THE EASTERN AND WESTERN BOUNDARIES, AND TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 21-18-11, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 CORNER OF SECTION 21-18-11 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 77 RODS, 1 LINK WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21-18-11
  - 2) 77 RODS, 1 LINK EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-18-11
  - 3) 80 RODS, 8 LINKS SOUTH TO THE STONE HE SET FOR THE CENTER OF THE NE1/4 OF SECTION 21-18-11
  - 4) 160 RODS, 16 LINKS SOUTH TO THE STONE HE SET FOR THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE NE1/4 OF SECTION 21-18-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY L. A. HAMBLIN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 184 TO 186 [PACKET 30 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] PETITIONED BY H. W. PEARSALL AND OTHERS, THAT HE SURVEYED APRIL 21, 1871 AND WAS ORDERED ESTABLISHED AND RECORDED BY THE BOARD OF COMMISSIONERS AS A 50 FOOT WIDE ROAD ON OCTOBER 2, 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND** THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11 ON THIS ROAD SURVEY.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 20.14 CHAINS TO THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-18-11 AT A TURN TO THE NORTH
  - 2) THIS ROAD EXTENDS SOUTH ON THE 1/4/4 SECTION LINE FOR 80.00 CHAINS TO THE ROCK AT THE NORTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 28-18-11 AT A TURN TO THE NORTH
- 3) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F21004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A PLAT OF SURVEY OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED FEBRUARY 23, 1972, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN SET** AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 21-18-11. HE DOES NOT SHOW HIS METHODOLOGY FOR DETERMINING THE LOCATION FOR THIS 1/16<sup>TH</sup> CORNER AND THERE ARE NO TIES ON THE SURVEY OR IN THE TIE FILES.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 639.75' EAST TO THE IRON PIN HE SET
  - 2) 1,279.5' EAST TO THE NORTHEAST CORNER OF SECTION 21-18-11 – NOT IDENTIFIED
  - 3) 1,660.56' SOUTH TO THE IRON PIN HE SET
  - 4) 2,656.9' SOUTH TO THE "IRON PIN IN PLACE" HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 21-18-11

- 4) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21003 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO EQUALLY DIVIDE A 40 ACRE TRACT OF GROUND LOCATED IN THE NORTHWEST 1/4

OF THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED OCTOBER 29, 1973, SHOWS ON HIS SURVEY DRAWING AN **“IRON PIN IN PLACE”** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,279.5' WEST TO THE STONE AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 21-18-11
  - 2) 442.81' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
  - 3) 885.62' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
  - 4) 1,328.43' SOUTH TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11
- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21001 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO LOCATE THE CORNERS TO A 2 ACRE TRACT OF GROUND LOCATED IN THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED JUNE 25, 1974, SHOWS ON HIS SURVEY DRAWING AN **“IRON PIN IN PLACE”** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,279.5' WEST TO THE STONE AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 21-18-11
  - 2) 885.62' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 2 ACRE TRACT
  - 3) 1,060.42' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 2 ACRE TRACT
  - 4) 1,328.42' SOUTH TO THE SOUTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11 – NOT IDENTIFIED
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21002 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO LOCATE THE CORNERS TO A 4 ACRE TRACT OF GROUND LOCATED IN THE NORTHEAST 1/4 OF SECTION 21-18-11 DATED JUNE 25, 1974, SHOWS ON HIS SURVEY DRAWING AN **“IRON PIN IN PLACE”** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 535.62' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 4 ACRE TRACT
  - 2) 885.62' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 4 ACRE TRACT
  - 3) 1,328.43' SOUTH TO THE SOUTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11 – NOT IDENTIFIED
- 7) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY NUMBER F21005 IN THE SURVEY DRAWER FOR TOWNSHIP 18-11 FOR A SURVEY TO SET ASIDE 50 ACRES IN A TRACT COMPOSED OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND ALL THAT PART OF THE SOUTH 1/2 OF THE NORTHWEST 1/4 LYING EAST OF ALLEN CREEK, ALL IN SECTION 21 DATED SEPTEMBER 9, 1975, SHOWS ON HIS SURVEY DRAWING AN **“IRON PIN”** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 21-18-11 ON THIS SURVEY.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,328.5' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11
  - 2) 2083.5' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 50 ACRE TRACT
  - 3) 2,657.5' SOUTH TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 21-18-11

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F21010 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR PROJECT NUMBER 04032-02 DATED MARCH 4, 2004 FOR THE SURVEY OF A TRACT IN THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 21-18-11, SAID THAT **HE FOUND A 1/2" REBAR** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 21-18-11 FROM A PRIOR SURVEY BY LESLIE M. GOULD, L.S. 142, DATED JUNE 1974.
- 1) 34.20' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 2) 40.80' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 3) 26.35' NNE TO A 40 D SPIKE & WASHER IN A POWER POLE
  - 4) 27.65' NNE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
  - 5) 8.5' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 561.00' WET TO THE 40 D NAIL HE SET FOR THE NORTHWEST TRACT CORNER AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET 25' SOUTH
  - 2) 1,280.29' WEST TO THE STONE AND 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11 [GOULD = 1,279.5']
  - 3) 521.00' SOUTH TO THE 40 DA NAIL HE SET FOR THE SOUTHEAST TRACT CORNER AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET 25' WEST
  - 4) 1,327.28' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 21-18-11

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 21-18-11