

**NORTH 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 22, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 24, 2005, FOR PROJECT NUMBER 05040-02, SURVEY F15003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 30.36 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 15-18-11 FOR PAUL HANCOCK AND ALICE GATEWOOD, SAID THAT **HE FOUND A 1/2" REBAR OF UNKNOWN ORIGIN** BUT IN A REASONABLE POSITION AT THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 15.
  - 1) 28.2' NORTH TO A CORNER GATE POST
  - 2) 21.15' SOUTH TO A CORNER FENCE POST
  - 3) 35.35' NE TO A FENCE GATE POST BRACE
  - 4) 4.0' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD 220 EAST-WEST
  - 5) 0.5' WEST TO A LINE OF FENCE NORTH-SOUTH

**HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**

  - 1) 660.00' WEST TO A 40 D NAIL SET FOR THE SOUTHWEST CORNER OF THE EXCEPTED TRACT AS WITNESSED BY A 1/2" REBAR WITH HIS "LS 752" CAP SET 25.00' NORTH
  - 2) 1,328.53' WEST TO A 5/8" SQUARE REBAR FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 15
  - 3) 1,327.76' EAST TO A 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15
  - 4) 660.00' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTH-EAST CORNER OF THE EXCEPTED TRACT
  - 5) 1,322.35' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE CENTER OF THE SW1/4 OF SECTION 15
  - 6) 2,644.41' NORTH TO THE THEORETICAL POSITION FOR THE 1/16<sup>TH</sup> CORNER ON THE NORTH SIDE OF THE SW1/4 OF SECTION 15

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 22-18-11