

CENTER CORNER SECTION 23, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 59 DATED FEBRUARY 18, 1874, TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 23-18-11 INTO EAST & WEST HALVES, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 23-18-11.

- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 45 & 46 [PACKET 155 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "COUNTY ROAD FROM SECTION 23-18-11 VIA FREMONT TO PLYMOUTH ROAD" PETITIONED BY JOHN LOY AND OTHERS THAT WAS SURVEYED APRIL 14 & 23, 1864 AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON JULY 4-6, 1864 ON PAGE 71, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 23-18-11 TO BEGIN THIS ROAD SURVEY FOR THE 66 FOOT WIDE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE ON THE MIDDLE SECTION LINES FOR 4-1/2 MILES TO JOHN LOY'S, THEN CONTINUES WEST FOR 24.50 CHAINS TO INTERSECT THE ROAD LEADING TO AMERICUS AT A TURN TO THE SOUTH

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 36 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 146 TO 149 PETITIONED BY HERBERT DAVIS AND OTHERS TO VACATE AND LOCATE A COUNTY ROAD IN TOWNSHIP 18-11 [PACKET 126 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 7, 1879, WAS ESTABLISHED AS A 45 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 17, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT THE ROAD TO BE **VACATED** COMMENCES AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 22-18-11 AND RUNS EAST "AS FAR EAST AS THE ROAD IS LOCATED". [**NOTE:** THE SURVEY DRAWING ON PAGE 147 INDICATES THAT THIS VACATED ROAD ENDS AT THE CENTER CORNER OF SECTION 23-18-11 AS NOTED IN SURVEY BOOK "A" ON PAGES 45 & 46 BY E. B. KIRKENDALL IN 1864- WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 11-25, 1903 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 22-18-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 23-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 5) REA BOOK 30 ON PAGE 33 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE CENTER CORNER OF SECTION 23-18-11 AT 2,623 FEET SOUTH OF THE SOUTH 1/4 CORNER OF 14-18-11 AND IN LINE WITH A HEDGE TO THE WEST. **VERIFY BEFORE USING AS THIS WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!!**
WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
 - 1) 26' TO A WITNESS PIN SET BY A CORNER POST AND IN LINE WITH A HEDGE LINE OF STUMPS

CONTINUED ON PAGE 2

- 6) JOHN R. YOUNG, L.S. 112, IN SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED NOVEMBER & DECEMBER 1977 FOR A *CERTIFICATE OF SURVEY* FOR THE NORTH HALF OF THE SOUTHWEST QUARTER OF SECTION 23-18-11 AND A TRACT IN THE NORTHWEST 1/4 OF SAID SECTION 23, SHOWS ON HIS SURVEY DRAWING THAT **HE SET** THE CENTER CORNER OF SECTION 23-18-11 AT A FENCE CORNER ON THIS SURVEY. THERE IS NO DESCRIPTION OF THE MONUMENT THAT HE SET FOR THE CENTER CORNER, BUT HIS LEGEND INDICATES THAT IT MAY BE A 1/2" BAR. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,592.29' WEST TO THE 1/2" BAR HE SET FOR THE SOUTHEAST CORNER OF A 2.99 ACRE TRACT
 - 2) 2,678.29' WEST TO THE PK NAIL & WASHER HE SET FOR THE WEST 1/4 CORNER OF SECTION 23-18-11
 - 3) 1,332.13' SOUTH TO THE 1/2" REBAR HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 23-18-11
 - 4) 2,664.26' SOUTH TO THE 3/4" BAR HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 23-18-11

CENTER CORNER 23-18-11