

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 23, TOWNSHIP 18 SOUTH, RANGE 11 EAST

1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 11-25, 1903 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 22-18-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE 1/2/4 STONE** AT THE WEST 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 23-18-11 ON THIS **PERMANENT SURVEY**. AN AFFIDAVIT BY WILLIAM McCREARY, SAID THAT THE STONE WAS SET FOR A. J. McFADDEN AND WILLARD COURTRIGHT WHEN DIVIDING THE NORTHEAST 1/4 OF SECTION 22-18-11 ABOUT THE YEAR 1883, ON A TRUE LINE BETWEEN THE STONE AT THE NORTHWEST CORNER OF SECTION 23-18-11, SUPPOSED TO BE THE ORIGINAL CORNER, AND SO RECOGNIZED BY PERSONS LIVING HERE AT THE TIME OF THE ORIGINAL SURVEY, AND THE STONE THAT HE FOUND THAT WAS SET BY ROBERT MILLIKEN NEAR THE SOUTHWEST CORNER THEREOF. SEE THE AFFIDAVIT THAT WAS MADE A PART OF THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 20.13 CHAINS NORTH TO THE STAKE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-18-11, AS WITNESSED BY THE WAGON SPOKE HE DROVE AT 24 LINKS SOUTH OF THE TRUE CORNER THAT IS 33 FEET EAST AND 16 FEET NORTH OF A HEDGE. HE NOTED THAT THIS CORNER WAS NOT CALLED FOR IN THE ORDER FOR THE SURVEY SO HE DID **NOT** SET A STONE FOR THE NORTHWEST CORNER OF SECTION 23-18-11
 - 2) 60.29 CHAINS NORTH TO THE 12" X 10" X 3" STONE MARKED WITH A "4" CLOSE TO THE TOP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 14-18-11, AT 4-1/2 FEET DEEP CLOSE TO THE WALL ON THE SOUTH SIDE OF A STONE CULVERT. HE NOTED THAT THIS STONE IS ABOUT 4 FEET EAST OF A LINE OVER THE OTHER STONES
 - 3) 80.32 CHAINS NORTH TO THE 1/2/4 STONE HE FOUND AT THE WEST 1/4 CORNER SIDE OF THE NORTHWEST 1/4 OF SECTION 14-18-11, NEARLY ON LINE WITH THE HEDGES. HE NOTED THAT A **WITNESS STONE** STANDS IN THE HEDGE AT 25-1/2 FEET WEST
 - 4) 100.35 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-18-11 ON LINE WITH THE HEDGES
 - 5) 19.95-1/2 CHAINS SOUTH TO THE 24" X 6" X 3" STONE MARKED "X" ON THE WEST SIDE THE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 23
 - 6) 60.04 CHAINS SOUTH TO THE 18" X 9" X 3" STONE MARKED "X" ON THE WEST SIDE **HE SET AT 1 LINK SOUTH OF THE TRUE CORNER** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 23-18-11
 - 7) 99.99 CHAINS SOUTH TO THE STONE MARKED "1/4" HE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-18-11 AT 2 FEET EAST OF A FENCE CORNER, AND 20 FEET NORTH AND 1 FOOT WEST OF AN 8" WALNUT TREE
 - 8) 140.20 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-18-11, AT 34 LINKS WEST OF THE HEDGE ON THE EAST SIDE OF THE ROAD AND 35 LINKS NORTH AND 32 LINKS SOUTH OF THE HEDGES EXTENDING EAST
- 2) GREGORY ALAN MILES, L.S. 667, IN SURVEY F22005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR PROJECT NUMBER 84-190 DATED OCTOBER 19, 1984, AND RECORDED IN VOLUME 413 ON PAGE 294 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 7, 1985 FOR A BOUNDARY SURVEY OF A 6.66 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 22-18-11, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE NORTHEAST CORNER OF THE SOUTHEAST 1/4

OF THE NORTHEAST 1/4 OF SECTION 22-18-11 ON THIS SURVEY AT 1,321.96 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 22-18-11. HE DID NOT SAY IF HE SEARCHED FOR THE STONE OF RECORD AT THIS CORNER THAT WAS MENTIONED IN ALVA J. SMITHS 1903 PERMANENT SURVEY. **VERIFY BEFORE USING!!**

WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321.96' NORTH TO THE NORTHEAST CORNER OF SECTION 22-18-11 – NOT IDENTIFIED
- 2) 400.00' SOUTH TO THE “PIN SET” FOR THE SOUTHEAST CORNER OF THE 6.66 ACRE TRACT
- 2) 726.04' WEST TO THE “PIN SET” FOR THE NORTHWEST CORNER OF THE 6.66 ACRE TRACT

WEST SIXTEENTH CORNER NORTHWEST QUARTER 23-18-11