

**WEST 1/4 CORNER SECTION 24, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 329 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 15" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 24-18-11.
  
- 2) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 32 [PACKET 918 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD IN FREMONT TOWNSHIP, BRECKENRIDGE COUNTY, PETITIONED BY THOMAS BRYANT AND OTHERS SURVEYED AUGUST 21, 1861 AND ESTABLISHED DECEMBER 3, 1861 ON THE COMMISSIONERS JOURNAL ON PAGE 163, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 POST OF SECTION 24-18-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.09 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-11 AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) 40.05 CHAINS SOUTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-11
  - 3) 60.05 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF W. STUCKERS TRACT
  - 4) 60.80 CHAINS SOUTH TO ANGLE STAKE NUMBER 4 TO THE SOUTHWESTERLY
  
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 115 RECORDED IN SURVEY BOOK "A" ON PAGE 205 DATED MAY 13 & 14, 1869 FOR A SURVEY IN SECTION 24-18-11, TO REESTABLISH THE 1/4 CORNERS ON THE SOUTHERN, WESTERN, AND NORTHERN BOUNDARIES, TO ESTABLISH THE CENTER CORNER, AND TO DIVIDE THE SOUTHWEST 1/4 OF SECTION 24 BY AN EAST AND WEST LINE, SAID THAT **HE SET A STONE** FOR THE WEST 1/4 CORNER OF SECTION 24-18-11, EQUIDISTANT BETWEEN THE STONES THAT HE FOUND AT THE SOUTHWEST AND NORTHWEST CORNERS OF SECTION 24-18-11 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 80 RODS, 2 LINKS SOUTH TO THE STONE HE SET FOR THE 1/2/4 CORNER ON THE WEST SIDE OF THE SW1/4 OF SECTION 24-18-11
  - 2) 160 RODS, 4 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 24-18-11
  - 3) 160 RODS, 4 NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-11
  
- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 30, 1992, FOR JOB NUMBER 92009-02, SURVEY F23004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 39.9 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 23-18-11, SAID THAT SHE EXCAVATED AND **SHE FOUND THE GLO STONE** AT THE EAST 1/4 CORNER OF SECTION 23-18-11. **SHE PLACED 1/2" REBARS ON THE EAST AND WEST SIDES OF THE STONE AND SHE PLACED A 1/2" REBAR WITH HER "LS 1130" CAP BENT OVER THE CENTER OF THE STONE** AT THE EAST 1/4 CORNER OF SECTION 23-18-11.
  - 1) 26.0' WNW TO A CONCRETE NAIL IN A BRACE POST
  - 2) 25.5' SOUTH TO A LINE OF FENCE TO THE NORTH AND HEDGE TO THE SOUTH
  - 3) 30.0' WEST TO A LINE OF FENCE NORTH-SOUTH
  - 4) 1' SOUTH TO A LINE OF HEDGE TO THE EAST EXTENDEDHER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,320.25' NORTH TO THE #4 REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 39.9 ACRE TRACT

HER INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,658.85' NORTH TO THE #4 REBAR SHE FOUND AT THE NORTHEAST CORNER OF SECTION 23-18-11
  - 3) 1,319.30' WEST TO THE CORNER POST IN CONCRETE WITH HER "LS 1130" CAP ON TOP AT THE SOUTHWEST CORNER OF THE 39.9 ACRE TRACT
- 5) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1994, FOR JOB NUMBER 94203-02, SURVEY F23005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF AN 8.45 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 23-18-11, SAID THAT **SHE FOUND THE GLO STONE WITH REBARS ON THE EAST AND WEST SIDES** AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 23-18-11, WITH A **REBAR BEARING HER "LS 1130" CAP BENT OVER THE CENTER OF THE STONE** FROM HER TIES OF RECORD AT THE COUNTY ENGINEER'S OFFICE DATED JANUARY 1992.
- 1) 26.0' ENE TO A CONCRETE NAIL IN A BRACE POST
  - 2) 25.5' EAST TO A LINE OF FENCE TO THE NORTH AND A HEDGE TO THE SOUTH
  - 3) 30.0' WEST TO A LINE OF FENCE NORTH-SOUTH
  - 4) 1.0' SOUTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
  - 5) 1.0' SOUTH TO A LINE OF HEDGE TO THE EAST [EXTENDED]
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,782.50' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 8.54 ACRE TRACT
  - 2) 2,657.50' SOUTH TO THE 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF SECTION 23-18-11

WEST QUARTER CORNER 24-18-11