

**NORTH 1/4 CORNER SECTION 25, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 329 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-18-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.03 CHAINS WEST TO THE 23" X 15" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-18-11
  - 2) 40.02 CHAINS EAST TO THE 18" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 24 & 25-18-11 ON THE EAST TOWNSHIP BOUNDARY
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 115 RECORDED IN SURVEY BOOK "A" ON PAGE 205 DATED MAY 13 & 14, 1869 FOR A SURVEY IN SECTION 24-18-11, TO REESTABLISH THE 1/4 CORNERS ON THE SOUTHERN, WESTERN, AND NORTHERN BOUNDARIES, TO ESTABLISH THE CENTER CORNER, AND TO DIVIDE THE SOUTHWEST 1/4 OF SECTION 24 BY AN EAST AND WEST LINE, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 24-18-11 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 80 RODS, 12 LINKS NORTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 24-18-11
  - 2) 160 RODS, 24 LINKS NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 24-18-11
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 AND DATED AUGUST 1903, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 25-18-11 ON THIS **PERMANENT SURVEY** TO RETRACE SURVEY NUMBER 89 BY D. T. McAULEY IN SURVEY BOOK "A" IN 1869. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE
  
- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 34 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 25-18-11 AT 2,681' EAST OF THE SOUTHWEST CORNER OF SECTION 24-18-11 AND IN LINE WITH A WIRE FENCE TO THE SOUTH.
  - 1) 23.75' SOUTH TO A WITNESS PIN BY A SMALL FENCE POST [A LITTLE WEST]
  
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **REA PIN** AT THE "SE CORNER SE1/4 SECTION 24-18-11". **VERIFY AND CHECK FOR THE STONE OF RECORD AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 23.75' SOUTH TO A WITNESS [REA]
  
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 TO DETERMINE THE CORNERS OF TWO 7.5 ACRE TRACTS OF GROUND LOCATED IN THE NORTHWEST 1/4 OF SECTION 25-18-11 DATED NOVEMBER 31, 1972 AND CORRECTED MAY 14, 1973, SHOWS ON HIS SURVEY DRAWING AN "**IRON PIN SET**" AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 25-18-11. THERE ARE NO TIES ON THE SURVEY. **VERIFY BEFORE USING AS THIS MAY BE THE REA PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 228.5' WEST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF TRACT NUMBER 2
- 2) 2,674.0' WEST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 25-18-11
- 3) 1,321.5' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT NUMBER 2
- 4) 2,643' SOUTH TO THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 25-18-11

NORTH QUARTER CORNER 25-18-11