

**NORTHWEST CORNER SECTION 25, TOWNSHIP 18 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 329 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 23" X 15" X 4"** FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-18-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.03 CHAINS EAST TO THE 24" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-18-11
  - 2) 80.05 CHAINS EAST TO THE 18" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 24 & 25-18-11 ON THE EAST TOWNSHIP BOUNDARY
  
- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 24 & 25 [PACKET 437 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "FOREST HILL TO AMERICUS" ROAD IN BRECKENRIDGE COUNTY SURVEYED MARCH 30 THROUGH APRIL 1, 1859 AND ESTABLISHED APRIL 27, 1859 IN THE COMMISSIONERS JOURNAL ON PAGE 66, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 26-18-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 28-18-11, AT THE SOUTHEAST CORNER OF THE TOWN OF FREMONT, AT A TURN TO THE NORTH
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE NORTH 1/4 CORNER OF SECTION 30-18-12 AT A TURN TO THE SOUTH
  
- 3) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 32 [PACKET 918 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD IN FREMONT TOWNSHIP, BRECKENRIDGE COUNTY, PETITIONED BY THOMAS BRYANT AND OTHERS SURVEYED AUGUST 21, 1861 AND ESTABLISHED DECEMBER 3, 1861 ON THE COMMISSIONERS JOURNAL ON PAGE 163, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 25-18-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.05 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 POST OF SECTION 24-18-11
  - 2) 80.14 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-11 AT THE TERMINUS OF THIS ROAD SURVEY
  - 3) 20.00 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF W. STUCKERS TRACT
  - 4) 20.75 CHAINS SOUTH TO ANGLE STAKE NUMBER 4 TO THE SOUTHWESTERLY
  
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 108 RECORDED IN SURVEY BOOK "A" ON PAGE 199 DATED APRIL 24, 1869 FOR A CHANGE IN A COUNTY ROAD PETITIONED BY M. H. CLARKE AND OTHERS IN TOWNSHIP 18-11, SAID THAT HE ENDED THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD AT THE NORTHEAST CORNER OF SECTION 26-18-11 **AT A STONE SET IN THE GROUND.**
  
- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 115 RECORDED IN SURVEY BOOK "A" ON PAGE 205 DATED MAY 13 & 14, 1869 FOR A SURVEY IN SECTION 24-18-11, TO REESTABLISH THE 1/4 CORNERS ON THE SOUTHERN, WESTERN, AND NORTHERN BOUNDARIES, TO ESTABLISH THE CENTER CORNER, AND TO DIVIDE THE SOUTHWEST 1/4 OF SECTION 24 BY AN EAST AND WEST LINE, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 24-18-11 ON THIS SURVEY.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 323 RODS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-18-11
  - 2) 80 RODS, 2 LINKS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 24-18-11
  - 3) 160 RODS, 4 LINKS NORTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 24-18-11
  - 4) 320 RODS, 8 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-11
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 10 DATED FEBRUARY 10-12, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 25-26-35-36 IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 25-18-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 97' SOUTH TO THE STONE HE FOUND
  - 2) 1,323' SOUTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 25-18-11
  - 3) 2,653' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-18-11
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 15, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 15 DATED FEBRUARY 28, 1870 TO ESTABLISH THE 1/4 SECTION CORNER BETWEEN SECTIONS 25 & 26, BETWEEN SECTION 23 & 26, AND THE CENTER OF SECTION 26, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,641' WEST TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 26-18-11
  - 2) 5,282' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-18-11
- 8) IN SURVEY NUMBER 45 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 193 DATED MAY 9, 1872 TO ESTABLISH THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11 AND TO PART OFF 60 ACRES FROM THE SOUTH SIDE OF THE NORTHWEST 1/4 OF SECTION 26, THE NOTES STATE THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**. [**NOTE:** THE SURVEY IS NOT SIGNED, BUT IT WAS APPARENTLY PERFORMED BY ROBERT MILLIKEN, COUNTY SURVEYOR – WARREN CHIP WOODS, P.S. 603, COUNTY SURVEYOR]
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 AND DATED AUGUST 1903, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 25-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE
- 10) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 187, A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 7 FOR REQUESTED BY MRS. GUY SERVISS TO MAKE A SURVEY OF THE

SECTION LINE BETWEEN SECTIONS 25 & 26-18-11, SAID THAT **HE SET A STAKE IN THE CENTER OF THE CROSS ROADS** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS BEGUN ON MARCH 20, 1907 AND WAS ENTERED ON MAY 5, 1907.

- 11) REA BOOK 30 ON PAGE 34 SAYS THAT **THEY SET AN IRON PIN** FOR THE CORNER COMMON TO SECTIONS 23, 24, 25 & 26-18-11 IN THE CENTER OF THE INTERSECTION OF THE CROSS ROADS.
  - 1) 38' SW TO A WITNESS PIN 14.25' SOUTH OF THE SOUTH END OF A CULVERT
  - 2) 35' SE TO A WITNESS PIN ON THE SOUTH SIDE OF A FENCE POST
- 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **REA PIN** AT THE "SE CORNER SECTION 23-18-11".
  - 1) 38' SW TO A WITNESS [REA]
  - 2) 35' SE TO A WITNESS [REA]
  - 3) 38.2' SW TO A SPIKE IN A POWER POLE
  - 4) 36.35' SSE TO A SPIKE IN A POWER POLE
- 13) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F26001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 SHOWING THE LINES OF A SURVEY OF A 5.48 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 26-18-11 DATED MAY 22, 1972 SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF SECTION 26-18-11. THERE ARE NO TIES ON THE SURVEY.
- 14) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F26002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 SHOWING THE LINES OF A SURVEY OF A 6.67 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 26-18-11 DATED MAY 22, 1972 SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF SECTION 26-18-11. THERE ARE NO TIES ON THE SURVEY.
- 15) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 TO DETERMINE THE CORNERS OF TWO 7.5 ACRE TRACTS OF GROUND LOCATED IN THE NORTHWEST 1/4 OF SECTION 25-18-11 DATED NOVEMBER 31, 1972 AND CORRECTED MAY 14, 1973, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** AT THE NORTHWEST CORNER OF SECTION 25-18-11. THERE ARE NO TIES ON THE SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,320' SOUTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF TRACT NUMBER 1
  - 2) 1,815' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT NUMBER 1
  - 3) 2,4456.5' EAST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF TRACT NUMBER 2
  - 4) 2,674.0' EAST TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 25-18-11
- 16) LLOYD J. DOBLER, L.S. 541, IN SURVEY F23002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF THREE 6.67 ACRE TRACTS IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 23-18-11 DATED OCTOBER 19, 1977, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF SECTION 23-18-11. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,325.21' WEST TO HE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 23-18-11HIS INFORMATION IS CONTINUED ON PAGE 4

- 2) 1,765.21' WEST TO THE IRON PIN HE SET FOR A TRACT CORNER
  - 3) 2,205.21' WEST TO THE IRON PIN HE SET FOR A TRACT CORNER
  - 4) 2,645.21' WEST TO THE IRON PIN HE SET FOR A TRACT CORNER – BUT HE DID **NOT** IDENTIFY THIS IRON PIN AS THE SOUTH 1/4 CORNER OF SECTION 23-18-11
- 17) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1994, FOR JOB NUMBER 94203-02, SURVEY F23005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF AN 8.54 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 23-18-11, SAID THAT **SHE FOUND A 1/2" REBAR IN THE INTERSECTION OF THE GRAVEL ROADS** AT THE SOUTHEAST CORNER OF SECTION 23-18-11 FROM RECORDS AT THE COUNTY ENGINEER'S OFFICE.
- 1) 37.8' SW TO THE TOP OF A TELEPHONE PEDESTAL
  - 2) 49.5' NE TO THE TOP OF A TELEPHONE PEDESTAL
  - 3) 37.4' SE TO A NAIL & WASHER IN A POWER POLE
  - 4) 53.8' NE TO A NAIL & WASHER IN A CORNER POST
  - 5) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 6) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 425.00' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF THE 8.54 ACRE TRACT
  - 2) 2,660.39' WEST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 23-18-11
  - 3) 875.00' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 8.54 ACRE TRACT
  - 4) 2,657.50' NORTH TO THE STONE & REBAR SHE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 23-18-11
- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHEAST CORNER OF SECTION 26-18-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED JUNE 1994 .
- 1) 48.8' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 2) 53.8' NE TO A NAIL & WASHER IN A CORNER FENCE POST
  - 3) 34.7' SE TO A NAIL & WASHER IN A POWER POLE
  - 4) 37.8' SW TO THE TOP OF A TELEPHONE PEDESTAL
  - 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD "M" NORTH-SOUTH
  - 6) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD 210 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,323.51' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 26-18-11
  - 2) 1,402.71' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 18.57 ACRE TRACT
  - 3) 2,647.02' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
  - 4) 5,299.20' SOUTH TO THE 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 26-18-11
  - 5) 583.60' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 18.57 ACRE TRACT

HIS INFORMATION IS CONTINUED ON PAGE 5

- 6) 2,665.10' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11
  - 7) 5,243.72' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-18-11
- 19) KARA LaRIVIERE, L.S. 1413, WITH THE KANSAS DEPARTMENT OF TRANSPORTATION, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 99-56 KA-0012-01, SAID THAT **SHE FOUND A 5/8" REBAR AT 0.7' DEEP** AT THE NORTHWEST CORNER OF SECTION 25-18-11 FROM A REFERENCE REPORT FILED BY STEVEN S. BROSEMER, L.S. 752, IN OCTOBER 2004. SET BY REA IN BOOK 30 ON PAGE 34. KDOT CORNER 26508
- 1) 48.8' NW TO A FOUND CONCRETE NAIL & WASHER IN THE SIDE OF A CORNER FENCE POST
  - 2) 36.9' SE TO A SET SPIKE & KDOT WASHER IN A POWER POLE
  - 3) 53.8' NE TO A FOUND NAIL & WASHER IN THE NORTHWEST SIDE OF A CORNER FENCE POST
  - 4) 37.9' SW TO A FOUND NAIL & WASHER IN A TELEPHONE PEDESTAL POST
  - 5) 2' SOUTH TO THE TRAVELWAY OF EAST-WEST GRAVEL ROAD "210"
  - 6) 3' EAST TO THE TRAVELWAY OF NORTH-SOUTH GRAVEL ROAD "M"
  - 7) 51.2' WNW TO THE SOUTHEAST CORNER OF THE CONCRETE TOP OF WELL
  - 8) 49.6' NW TO A FOUND NAIL & SHINER IN THE TOP OF A CORNER FENCE POST
- THE DRAWING SIGNED BY LARRY DEE MOORE, L.S. 1174 DATED APRIL 20, 2010 SHOWS THE FOLLOWING DISTANCES:
- 1) PROJECT COORDINATES ON SECTION CORNERS: COORDINATES X 0.999928556 = STATE PLANE COORDINATES NAD-83 [1997 ADJUSTMENT] KANSAS SOUTH ZONE: NORTH = 1975024.029 EAST = 1984588.170
  - 2) 2,665.00' WEST TO THE 1/2" BAR SHE FOUND AT 0.2' DEEP AT THE NORTH 1/4 CORNER OF SECTION 26-18-11
  - 3) 5,243.65' WEST TO THE 1/2" REBAR WITH A KDOT CAP SHE SET FOR THE NORTHWEST CORNER OF SECTION 26-18-11
  - 4) 2,674.14' SOUTH TO THE 3" X 9" X 12" LIMESTONE SHE FOUND AT 0.2' DEEP AT THE EAST 1/4 CORNER OF SECTION 26-18-11
  - 5) 5,299.10' SOUTH TO THE 5/8" BAR SHE FOUND AT 0.7' DEEP AT THE SOUTHEAST CORNER OF SECTION 26-18-11
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED JUNE 13, 2014 FOR PROJECT NUMBER 14102-02, SURVEY F23007 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE DIRECT RETRACEMENT OF THE SURVEY OF A TRACT BY LLOYD J. DOBLER DATED OCTOBER 19, 1977 IN THE SOUTHWEST QUARTER OF SECTION 23-18-11 FOR GINA BROWNING, SAID THAT **HE FOUND THE 1/2" IRON PIN** AT THE SOUTHEAST CORNER OF SECTION 23-18-11 FROM EXISTING REFERENCE TIES BY KARA LARIVIERE FOR KDOT PROJECT NUMBER 99-56 KA-0012-01 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE.
- 1) 48.80' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 2) 36.90' SE TO A SPIKE & KDOT WASHER IN A POWER POLE
  - 3) 37.90' SW TO A NAIL & SHINER IN A TELEPHONE PEDESTAL POST
  - 4) 2.00' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 210 EAST-WEST
  - 5) 3.00' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,325.21' WEST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 23-18-11, AND THE SOUTHEAST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY A 1/2" X 24" IRON PIN

WITH HIS "S. BROSEMER" CAP HE SET AT 20.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 210

- 2) 1,765.21' WEST TO THE SOUTHWEST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2" IRON PIN HE FOUND AT 19.86' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 210
- 3) 2,664.97' WEST TO THE 1/2" IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 23-18-11

NORTHWEST CORNER 25-18-11