

CENTER CORNER SECTION 26, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGE 128 DATED APRIL 10, 1868 TO SURVEY J. A. FILINER'S LAND, BEING THE SOUTH 1/2 OF THE SOUTHWEST 1/4 AND 20 ACRES MORE OR LESS OF THE WEST END OF THE SOUTHWEST 1/4 AND ALSO TO DIVIDE EQUALLY 60 ACRES MORE OR LESS OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 26-18-11, SAID THAT **HE SET A TEMPORARY POST** FOR THE CENTER CORNER OF SECTION 26-18-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS, 2 LINKS SOUTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 26-18-11
 - 2) 160 RODS, 4 LINKS SOUTH TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 26-18-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 15, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 15 DATED FEBRUARY 28, 1870 TO ESTABLISH THE 1/4 SECTION CORNER BETWEEN SECTIONS 25 & 26, BETWEEN SECTION 23 & 26, AND THE CENTER OF SECTION 26, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND A TEMPORARY POST ALREADY SET** AT THE CENTER CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,607-1/4' EAST TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-18-11

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 11-25, 1903 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 22-18-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 26-16-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 26-18-11 TO BE AT THE INTERSECTION OF LINES FROM THE OPPOSITE 1/4 CORNERS, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,309.17' NORTH TO THE THEORETICAL POSITION FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 2) 2,618.36' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 3) 2,615.09' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 4) 2,656.68' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 2,599.96' WEST TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 26-18-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F26006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 7.09 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 FOR EK REALTY [DETWILER/BRAUN] FOR PROJECT NUMBER 11259-02 DATED SEPTEMBER 21, 2011, SHOWS ON HIS DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 26-18-11 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY. **NOTE:** HIS DRAWING LABELS THIS CORNER AS THE "NW COR. SW1/4" BUT IT SHOULD BE THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,599.86' WEST TO THE 1/2" IRON PIN WITH A 2" ALUMINUM CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 26-18-11
 - 2) 2,618.22' NORTH TO THE 1/2" IRON PIN HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 3) 1,307.43' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-18-11
 - 4) 2,614.86' EAST TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 26-18-11
 - 5) 2,422.38' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 7.09 ACRE TRACT
 - 6) 2,656.38' SOUTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11

CENTER CORNER 26-18-11