

NORTH 1/4 CORNER SECTION 26, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 334 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT THEY SET A **LIMESTONE** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-18-11, BUT THE NOTES DO NOT GIVE ANY DIMENSIONS OF THE STONE.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.83 CHAINS WEST TO THE 18" X 14" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11
 - 2) 39.82 CHAINS EAST TO THE 23" X 15" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-18-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 22 & 23 [PACKET 525 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE NOTES OF A COUNTY ROAD FROM THE POINT AT WHICH THE EMPORIA AND WATERLOO ROAD CROSSES THE EAST LINE OF NOAH BIXLER'S CLAIM TO THE NORTHEAST CORNER OF S. CRANDALL'S CLAIM, BEING THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 26-17-11 THAT WAS ESTABLISHED ON FEBRUARY 28, 1859 IN THE COMMISSIONERS JOURNAL ON PAGE 48, SAID THAT **HE FOUND THE NORTH 1/4 STONE POST** OF SECTION 26-18-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 79.70' NORTH TO THE NORTH 1/4 STONE POST OF SECTION 23-18-11 AT A TURN TO THE EAST ON THIS ROAD SURVEY
 - 2) 79.72 CHAINS SOUTH TO THE NORTH 1/4 STONE POST OF SECTION 35-18-11
 - 3) 94.72 CHAINS SOUTH TO THE POINT AT WHICH THE EMPORIA AND WATERLOO ROAD CROSSES THE EAST LINE OF NOAH BIXLER'S CLAIM TO COMMENCE THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 15, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 15 DATED FEBRUARY 28, 1870 TO ESTABLISH THE 1/4 SECTION CORNER BETWEEN SECTIONS 25 & 26, BETWEEN SECTION 23 & 26, AND THE CENTER OF SECTION 26, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE MARKED "1/4"** LYING ON THE GROUND AT THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-18-11. HE RETRACED THE SECTION LINE BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 26-18-11, AND **HE RESET THE ORIGINAL STONE** AT THE PROPER CORRECTION FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,641' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-18-11
 - 2) 2,641' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-18-11

- 4) IN SURVEY NUMBER 45 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 193 DATED MAY 9, 1872 TO ESTABLISH THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11 AND TO PART OFF 60 ACRES FROM THE SOUTH SIDE OF THE NORTHWEST 1/4 OF SECTION 26-18-11, THE NOTES STATE THAT **THEY FOUND THE 1/4 CORNER** BETWEEN SECTIONS 23 & 26-18-11 ON THIS **PERMANENT SURVEY**. [**NOTE:** THE SURVEY IS NOT SIGNED, BUT IT WAS APPARENTLY PERFORMED BY ROBERT MILLIKEN, COUNTY SURVEYOR AND THERE IS NO DESCRIPTION OF THE MONUMENT THAT HE FOUND AT THIS CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

CONTINUED ON PAGE 2

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 59 DATED FEBRUARY 18, 1874, TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 23-18-11 INTO EAST & WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 23-18-11 ON THIS **PERMANENT SURVEY**.

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 11-25, 1903 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 22-18-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY** TO RETRACE SURVEY NUMBER 89 BY D. T. McAULEY IN SURVEY BOOK "A" IN 1869. **HE SET A POINT** ON LINE WITH THE STONES THAT HE FOUND TO THE NORTH AND SOUTH, SAID POINT BEING 10 LINKS EAST AND 35 LINKS WEST OF HEDGES EXTENDING NORTH, AND 40 LINKS EAST AND 48 LINKS WEST OF HEDGES EXTENDING SOUTH. HE NOTED THAT MILLIKEN USED THE McAULEY ROAD STONE AT THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11 WHEN HE SET THIS 1/4 CORNER. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.02 CHAINS WEST TO THE 18" X 9" X 3" STONE MARKED "X" ON THE WEST SIDE **HE SET A 1 LINK SOUTH OF THE TRUE CORNER** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 23-18-11
 - 2) 79.46 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-18-11
 - 3) 118.69 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-18-11, AT 38 LINKS NORTH AND 37 LINKS WEST OF HEDGE FENCES

- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 24
ON FEBRUARY 11, 1944 A PETITION SIGNED BY JOHN WHITTLETON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND E. C. GOLDSMITH, COUNTY ENGINEER, ON MARCH 15, 1944 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 25, 1944 **VACATED** THE FOLLOWING ROAD:
 - 1) BEGINNING AT THE NORTH QUARTER CORNER OF SECTION 26-18-11, THENCE SOUTH ALONG THE NORTH AND SOUTH QUARTER SECTION LINE 280 RODS AND THERE ENDING
 - 2) SAID ROAD SHOULD BE VACATED. THE PORTION OF THE ROAD WHICH IT IS PROPOSED TO VACATE AS PETITIONED FOR BY JOHN WHITTLETON, IS NOT IN PASSABLE CONDITION AND THE USE OF THE ROAD WOULD NOT JUSTIFY THE COST OF PLACING IT IN CONDITION FOR PUBLIC TRAVEL. SINCE ALL ADJACENT PROPERTY HAS OTHER ACCESS ROADS, WE RECOMMEND THAT THE ROAD BE VACATED AS PETITIONED.

- 8) REA BOOK 30 ON PAGE 34 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 26-18-11 IN THE CENTER OF THE ROADS NORTH, EAST AND WEST AND AT 2,695.2' EAST OF THE NORTHWEST CORNER OF SECTION 26-18-11.
 - 1) 29' NE TO A WITNESS PIN 1 FOOT NORTH OF A HACKBERRY TREE
 - 2) 35' NW TO A WITNESS PIN IN A HEDGE CORNER

- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **REA PIN** AT THE "SW CORNER SE 1/4 SECTION 23-18-11".
- 1) 29' NE & 35' NW TO WITNESS PINS [REA]
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 175
ON DECEMBER 11, 1979 A PETITION SIGNED BY JOHN S. MARKEY AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO PEGGY STICE, DEPUTY COUNTY CLERK. THE COUNTY COMMISSIONERS VIEWED THE ROAD ON JANUARY 3, 1980, AND THEIR FINAL ORDER DATED JANUARY 3, 1980 ORDERED THE FOLLOWING ROAD BE **VACATED AS PETITIONED**:
- 1) BEGINNING 20 FEET EAST OF THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 23-18-11; THENCE NORTH 1,320 FEET; THENCE WEST 40 FEET; THENCE SOUTH 1,320 FEET; THENCE EAST 40 FEET TO THE PLACE OF BEGINNING.
- 11) LLOYD J. DOBLER, L.S. 541, IN SURVEY F23002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF THREE 6.67 ACRE TRACTS IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 23-18-11 DATED OCTOBER 19, 1977, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** AT 1,320' WEST OF THE IRON PIN THAT HE SET FOR THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 23-18-11. [**NOTE:** HE DOES **NOT** LABEL THIS IRON PIN AS THE SOUTH 1/4 CORNER OF SECTION 23-18-11 BUT IS SHOWN HERE TO NOTE THE ORIGIN OF THIS IRON PIN. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 12) JOHN R. YOUNG, L.S. 112, IN SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED NOVEMBER & DECEMBER 1977 FOR A *CERTIFICATE OF SURVEY* FOR THE NORTH HALF OF THE SOUTHWEST QUARTER OF SECTION 23-18-11 AND A TRACT IN THE NORTHWEST 1/4 OF SAID SECTION 23, SAID THAT **HE FOUND A 3/4" BAR** AT THE SOUTH 1/4 CORNER OF SECTION 23-18-11. THE FOLLOWING REFERENCES ARE ON THE SURVEY:
- 1) 40.9' NW TO A SPIKE & WASHER IN A POWER POLE
 - 2) 32.1' NE TO A SPIKE & 2 WASHERS IN A FENCE CORNER
 - 3) 43.6' SE TO A SPIKE & 3 WASHERS IN A POWER POLE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) ~~2,691.92' WEST TO A 1/2" REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 23-18-11~~ [**NOTE:** SEE THE REFERENCES FOR THE **STONE** AT THE SOUTHWEST CORNER OF SECTION 23-18-11! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 1,332.13' NORTH TO THE 1/2" REBAR HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 23-18-11
 - 3) 2,664.26' NORTH TO THE CENTER CORNER OF SECTION 23-18-11 AT A FENCE CORNER
- 13) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1994, FOR JOB NUMBER 94203-02, SURVEY F23005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF AN 8.54 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 23-18-11, SAID THAT **SHE FOUND A 1/2" REBAR** AT THE SOUTH 1/4 OF SECTION 23-18-11 FROM RECORDS AT THE COUNTY ENGINEER'S OFFICE.
- 1) 37.5' NW TO A NAIL & SHINER IN A POWER POLE
 - 2) 49.9' SE TO A NAIL & SHINER IN A POWER POLE
 - 3) 32.1' NE TO A NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST

HER INFORMATION IS CONTINUED ON PAGE 4

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,235.39' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF THE 8.54 ACRE TRACT
- 2) 2,660.39' EAST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 23-18-11

- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 26-18-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) **4.92' SE TO A 5/8" SQUARE BAR FOUND**
- 2) 37.5' NW TO A NAIL & SHINER IN A POWER POLE
- 3) 32.1' NE TO A NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 49.9' SE TO A NAIL & SHINER IN A POWER POLE
- 5) 2.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 210 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,578.62' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-18-11
- 2) 1,309.17' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 26-18-11
- 3) 2,618.34' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11
- 4) 5,275.02' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11
- 5) 2,081.50' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 18.57 ACRE TRACT
- 6) 2,665.10' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11

- 15) KARA LaRIVIERE, L.S. 1413, WITH THE KANSAS DEPARTMENT OF TRANSPORTATION, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 99-56 KA-0012-01, SAID THAT **SHE FOUND THE 1/2" REBAR AT 0.2' DEEP** AT THE NORTH 1/4 CORNER OF SECTION 26-18-11 FROM A REFERENCE REPORT FILED BY STEVEN S. BROSEMER, LS 752, IN OCTOBER 2004. ORIGIN OF THIS REBAR IS UNKNOWN. KDOT CORNER 26408

- 1) **5.05' ESE TO A FOUND 5/8" SQUARE REBAR**
- 2) 37.7' NW TO A FOUND NAIL & SHINER IN A POWER POLE
- 3) 33.0' NE TO A FOUND NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 49.9' SE TO A FOUND NAIL & SHINER IN A POWER POLE
- 5) 2.5' SOUTH TO THE TRAVELWAY OF GRAVEL COUNTY ROAD "210" EAST-WEST

THE DRAWING SIGNED BY LARRY DEE MOORE, L.S. 1174 DATED APRIL 20, 2010 SHOWS THE FOLLOWING INFORMATION:

- 1) PROJECT COORDINATES ON SECTION CORNERS: COORDINATES X 0.999928556 = STATE PLANE COORDINATES NAD-83 [1997 ADJUSTMENT] KANSAS SOUTH ZONE: NORTH = 1974930.229 EAST = 1981924.825
- 2) 2,578.65' WEST TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP SHE SET FOR THE NORTHWEST CORNER OF SECTION 26-18-11
- 3) 2,665.00' EAST TO THE 5/8" BAR SHE FOUND AT 0.7' DEEP AT THE NORTHEAST CORNER OF SECTION 26-18-11
- 4) 5,257.05' SOUTH TO THE 5/8" BAR WITH LYON COUNTY CAP SHE FOUND AT 0.05' DEEP AT THE SOUTH 1/4 CORNER OF SECTION 26-18-11

CONTINUED ON PAGE 5

- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2011 FOR PROJECT NUMBER 11259-02, SURVEY F26006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF A 7.09 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 FOR EK REALTY [DETWILER/BRAUN], SAID THAT **HE FOUND THE 1/2" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 26-18-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE DATED OCTOBER 2004. HE NOTED THAT K. LaRIVIERE, L.S. 1413, FOUND THE IRON PIN IN 2010 AND P. JONES, L.S. 1130, FOUND THE IRON PIN IN 1994.
- 1) **5.05' ESE TO A 5/8" SQUARE IRON PIN FOUND**
 - 2) 37.3' NW TO A NAIL & SHINER IN A POWER POLE FOUND
 - 3) 33.0' NE TO A NAIL & SHINER IN A CORNER FENCE POST FOUND
 - 4) 49.9' SE TO A NAIL & SHINER IN A POWER POLE FOUND
 - 5) 19.5' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
 - 6) 2' SOUTH TO THE GRAVELED WAY OF GRAVEL COUNTY ROAD 210 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,618.22' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE **SW1/4** OF SECTION 26-18-11 [**NOTE:** THIS CORNER SHOULD BE THE NORTHWEST CORNER OF THE **SE1/4** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 5,040.60' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH-WEST CORNER OF THE 7.09 ACRE TRACT
 - 3) 5,274.60' SOUTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11
- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED JUNE 13, 2014 FOR PROJECT NUMBER 14102-02, SURVEY F23007 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE DIRECT RETRACEMENT OF THE SURVEY OF A TRACT BY LLOYD J. DOBLER DATED OCTOBER 19, 1977 IN THE SOUTHWEST QUARTER OF SECTION 23-18-11 FOR GINA BROWNING, SAID THAT **HE FOUND THE 1/2" IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 23-18-11 FROM EXISTING REFERENCE TIES BY KARA LARIVIERE FOR KDOT PROJECT NUMBER 99-56 KA-0012-01 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE.
- 1) **5.05' EAST TO A 5/8" SQUARE REBAR FOUND**
 - 2) 37.70' NW TO A NAIL & SHINER IN A POWER POLE
 - 3) 33.00' NE TO A NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 49.90' SE TO A NAIL & SHINER IN A POWER POLE
 - 5) 2.50' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 210 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 899.76' EAST TO THE SOUTHWEST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2" IRON PIN HE FOUND AT 19.86' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 210
 - 2) 1,337.76' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 23-18-11, AND THE SOUTHEAST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET AT 20.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 210
 - 3) 2,664.97' EAST TO THE 1/2" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 23-18-11

NORTH QUARTER CORNER 26-18-11