

WEST 1/4 CORNER SECTION 26, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 333 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-18-11 ON DECEMBER 15, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 18" X 14" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 15" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-18-11
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 32 RECORDED IN SURVEY BOOK "A" ON PAGE 127 DATED APRIL 4, 1868 FOR A SURVEY OF WILLIAM STANLEY'S AND OTHERS LAND, BEING THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 27-18-11, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 27-18-11 EQUIDISTANT BETWEEN THE STONE THAT HE SET FOR THE NORTHEAST CORNER OF SECTION 27-18-11 AND STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-18-11.

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGE 128 DATED APRIL 10, 1868 TO SURVEY J. A. FILINER'S LAND, BEING THE SOUTH 1/2 OF THE SOUTHWEST 1/4 AND 20 ACRES MORE OR LESS OF THE WEST END OF THE SOUTHWEST 1/4 AND ALSO TO DIVIDE EQUALLY 60 ACRES MORE OR LESS OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 26-18-11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 26-18-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 315 RODS, 3 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 26-18-11
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 15, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 15 DATED FEBRUARY 28, 1870 TO ESTABLISH THE 1/4 SECTION CORNER BETWEEN SECTIONS 25 & 26, BETWEEN SECTION 23 & 26, AND THE CENTER CORNER OF SECTION 26, ALL IN TOWNSHIP 18, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-18-11 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE TO VERIFY THE POST THAT HE FOUND ALREADY SET AT THE CENTER CORNER OF SECTION 26-18-11.

- 5) IN SURVEY NUMBER 45 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 193 DATED MAY 9, 1872 TO ESTABLISH THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11 AND TO PART OFF 60 ACRES FROM THE SOUTH SIDE OF THE NORTHWEST 1/4 OF SECTION 26-18-11, THE NOTES STATE THAT **THEY FOUND THE 1/4 CORNER** BETWEEN SECTIONS 26 & 27-18-11 ON THIS **PERMANENT SURVEY**. [**NOTE:** THE SURVEY IS NOT SIGNED, BUT IT WAS APPARENTLY PERFORMED BY ROBERT MILLIKEN, COUNTY SURVEYOR. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,640 FEET NORTH TO TEMPORARY CORNER 1 HE SET
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 5 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 60 DATED FEBRUARY 19, 1874 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 27-18-11 INTO NORTH AND SOUTH HALVES, SAID

THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-18-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,312' NORTH TO THE 20" X 14" X 2" STONE HE SET FOR THE PERMANENT 1/2-4 CORNER ON THE EAST SIDE OF THE NE1/4 OF SECTION 27-18-11
- 2) 2,624' NORTH TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 22, 23, 26 & 27-18-11 "SET BY FIELD NOTES. SEE SURVEY NUMBER 45 OF THE 7TH TERM DATED MAY 9, 1872"

- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 24 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 79 DATED MAY 14, 1874 TO ESTABLISH THE 1/2-4 CORNER ON THE NORTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 27-18-11, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-18-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,314' WEST TO THE 14" X 10" X 2" STONE HE SET FOR THE PERMANENT 1/2-4 CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 27-18-11
- 2) 2,648' WEST TO THE STONE HE FOUND "ALREADY ESTABLISHED" AT THE CENTER CORNER OF SECTION 27-18-11 [SEE RECORD NUMBER 32 OF THE 5TH TERM]

- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION TWENTY-TWO (22), TOWNSHIP EIGHTEEN (18), RANGE ELEVEN (11) AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, THAT HE SURVEYED ON AUGUST 11, 12, 19, 20 & 25, 1903, SAID THAT **HE FOUND THE EXISTING STONE MARKED "1/4" ON THE WEST SIDE AT 2' EAST OF A FENCE CORNER AND 20' NORTH & 1' WEST OF AN 8" WALNUT TREE** AT THE EAST 1/4 CORNER OF SECTION 27-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 40.21 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-18-11, AT 34 LINKS WEST OF THE HEDGE ON THE EAST SIDE OF THE ROAD, AND 35 LINKS NORTH AND 32 LINKS SOUTH OF HEDGES EXTENDING EAST
- 2) 39.95 CHAINS NORTH TO THE 18" X 9" X 3" STONE MARKED "X" ON THE WEST SIDE **HE SET AT 1 LINK SOUTH OF THE TRUE CORNER** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 23-18-11. HE BURIED A WITNESS STONE 8" X 6" X 6" MARKED "W" ON THE TOP AT 1 FOOT DEEP AT 5-1/2 FEET SOUTH OF THE CORNER STONE. McAULEY ROAD STONE BEARS S. 79°30' W. AT 111 FEET DISTANCE. MILLIKEN WITNESS STONE BEARS S. 84° W. 86 FEET DISTANCE. HEDGE ON EAST SIDE OF ROAD AT 88 FEET. HEDGE ON WEST SIDE OF ROAD AT 130 FEET.
- 3) 80.03-1/2 CHAINS NORTH TO THE 24" X 6" X 3" STONE MARKED "X" ON THE WEST SIDE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 23-18-11. AN 8" BOX ELDER TREE BEARS S. 5°30' E. AT 18 FEET DISTANCE, ANOTHER S. 12° W. AT 19 FEET DISTANCE, ANOTHER S. 32°30' W. AT 22 FEET DISTANCE, AND 23-1/2 FEET EAST OF A HEDGE

HIS INFORMATION IS CONTINUED ON PAGE 3

- 4) 99.99 CHAINS NORTH TO THE 1/2/4 STONE HE FOUND ON THE WEST SIDE OF THE NW1/4 OF SECTION 23-18-11, AND HE TOOK THE AFFIDAVIT OF WILLIAM McCREARY THAT THE STONE WAS SET BY RESIDENTS OF THE NEIGHBORHOOD ON A TRUE LINE BETWEEN THE ORIGINAL GOVERNMENT CORNER AT THE NORTHWEST CORNER OF SECTION 23-18-11, AND THE STONE THAT WAS SET NEAR THE SOUTHWEST CORNER OF SECTION 23-18-11 BY ROBERT MILLIKEN ON THE STATEMENT OF WILLIAM STANLEY AND ROBERT ROBERTS
 - 5) 120.12 CHAINS NORTH TO THE STAKE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-18-11, AND WITNESSED BY A WAGON SPOKE HE DROVE AT 24 LINKS SOUTH OF THE **TRUE CORNER**. HE NOTED THAT THIS WAGON SPOKE IS 33 FEET EAST AND 16 FEET NORTH OF A HEDGE, AND THAT THIS CORNER WAS NOT CALLED FOR IN THE ORDER OF THE SURVEY SO HE DID **NOT** SET A STONE FOR THE NORTHWEST CORNER OF SECTION 23-18-11.
 - 6) 160.28 CHAINS NORTH TO THE 12" X 10" X 3" STONE FRAGMENT MARKED "4" ON IT CLOSE TO THE TOP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 14-18-11, AT 4-1/2 FEET DEEP CLOSE TO THE WALL ON THE SOUTH SIDE OF A STONE CULVERT. HE NOTED THAT THIS STONE IS ABOUT 4 FEET EAST OF A LINE OVER THE OTHER STONES.
 - 7) 180.31 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 14-18-11, NEARLY IN LINE WITH THE HEDGES. HE NOTED THAT A **WITNESS STONE** STANDS IN THE HEDGE AT 25-1/2 FEET WEST
 - 8) 200.34 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-18-11 STANDING ON LINE WITH THE HEDGES
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **STONE** AT THE "SW CORNER NW1/4 SECTION 26-18-11" AND "SE CORNER NE1/4 SECTION 27-18-11", BUT THERE IS NO DATE ON THIS ENTRY.
 - 1) 6' EAST TO A WITNESS STONE
 - 10) JAMES H. BROSEMER, L.S. 82, KDOT CHIEF OF SURVEYS, FOR KDOT PROJECT 99-56K-0549-01, SAID THAT **HE SET A 1/2" REBAR WITH AN ALUMINUM KDOT CAP STAMPED "W1/4 26-18-11"** FOR THE WEST 1/4 CORNER OF SECTION 26-18-11.
 - 1) 140.14' WEST OF STATION 153 + 72.19
 - 2) 4.40' NW TO A SPIKE & KDOT WASHER IN A 20" KENTUCKY COFFEE TREE
 - 3) 3.45' ESE TO A SPIKE & KDOT WASHER IN A 50" HACKBERRY TREE
 - 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT **HE FOUND THE EXISTING 1/2" REBAR WITH AN ALUMINUM KDOT CAP** AT THE WEST 1/4 CORNER OF SECTION 26-18-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY JAMES H. BROSEMER, L.S. 82, KDOT CHIEF OF SURVEYS.
 - 1) 4.4' NW TO A SPIKE & KDOT WASHER IN A 20" KENTUCKY COFFEE TREE
 - 2) 3.7' ESE TO A SPIKE & KDOT WASHER IN A 60" HACKBERRY TREE
 - 3) 18.75' NE TO A CONCRETE NAIL & WASHER IN A 12" ELM TREE
 - 4) 15.6' SOUTH TO A CROP LINE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,632.61' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-18-11
 - 2) 2,661.42' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-18-11
 - 3) 2,599.96' EAST TO THE THEORETICAL LOCATION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11

HIS INFORMATION IS CONTINUED ON PAGE 4

- 4) 5,215.05' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 30, 2009 FOR PROJECT NUMBER 09274-02, SURVEY F27002 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A 5.93 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 27, AND A 0.84 TRACT IN THE SOUTHWEST QUARTER OF SECTION 26-18-11 FOR SCHAEFER, SAID THAT **HE FOUND THE EXISTING 1/2" REBAR WITH THE KDOT CAP** AT THE EAST 1/4 CORNER OF SECTION 27-18-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 2004.
- 1) 4.4' NW TO A SPIKE & KDOT WASHER IN A 20" KENTUCKY COFFEY TREE
 - 2) 3.7' ESE TO A SPIKE & KDOT WASHER IN A 60" HACKBERRY TREE
 - 3) 18.75' NE TO A CONCRETE NAIL & WASHER IN A 12" ELM TREE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 319.93' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF TRACT 1
 - 2) 5,277.27' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 27-18-11
 - 3) 2,661.13' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 27-18-11
 - 4) 104.70' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF TRACT 2
 - 5) 564.50' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CORNER COMMON TO TRACTS 1 & 2
 - 6) 5,215.05' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 26-18-11
- 13) KARA LaRIVIERE, L.S. 1413, WITH THE KANSAS DEPARTMENT OF TRANSPORTATION, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 99-56 KA-0012-01, SAID THAT **SHE FOUND THE EXISTING 1/2" BAR WITH KDOT ALUMINUM CAP STAMPED "W1/4 26-18-11" AT 0.4' DEEP** FOR THE WEST 1/4 CORNER OF SECTION 26-18-11 FROM A REFERENCE REPORT FILES BY STEVEN S. BROSEMER, L.S. 752, IN OCTOBER 2009. SHE NOTED THAT THIS KDOT ALUMINUM CAPPED REBAR WAS SET BY JAMES H. BROSEMER, L.S. 82, KDOT CHIEF OF SURVEYS IN DECEMBER 1979. KDOT CORNER 26208
- 1) 140.59' LEFT [WEST] OF CENTERLINE STATION 153+73.52; SW ANGLE = 81°39'03"
 - 2) 18.8' NE TO A FOUND CONCRETE NAIL & WASHER IN A 12" DIAMETER ELM TREE
 - 3) 4.4' NW TO A FOUND SPIKE & KDOT WASHER IN A 20" DIAMETER KENTUCKY COFFEE TREE
 - 4) 3.7' ESE TO A FOUND SPIKE & KDOT WASHER IN A 60" DIAMETER HACKBERRY TREE
 - 5) 15.5' SOUTH TO AN EAST-WEST CROP LINE
- THE DRAWING SIGNED BY LARRY DEE MOORE, L.S. 1174 DATED APRIL 20, 2010 SHOWS THE FOLLOWING INFORMATION:
- 1) PROJECT COORDINATES ON SECTION CORNERS: COORDINATES X 0.999928556 = STATE PLANE COORDINATES NAD-83 [1997 ADJUSTMENT] KANSAS SOUTH ZONE: NORTH = 1972250.153 EAST = 1979423.542
 - 2) 2,633.22' NORTH TO THE 1/2" KDOT ALUMINUM CAPPED REBAR SHE SET FOR THE NORTHWEST CORNER OF SECTION 26-18-11
 - 3) 2,661.19' SOUTH TO THE 5/8" BAR WITH LYON COUNTY CAP SHE FOUND AT 0.6' DEEP AT THE SOUTHWEST CORNER OF SECTION 26-18-11
 - 4) 5,215.17' EAST TO THE 3" X 9" X 12" LIMESTONE SHE FOUND AT 0.2' DEEP AT THE EAST 1/4 CORNER OF SECTION 26-18-11

CONTINUED ON PAGE 5

- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2011 FOR PROJECT NUMBER 11259-02, SURVEY F26006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF A 7.09 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 FOR EK REALTY [DETWILER/BRAUN], SAID THAT **HE FOUND THE EXISTING 1/2" IRON PIN WITH AN ALUMINUM KDOT CAP** AT THE WEST 1/4 CORNER OF SECTION 26-18-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE DATED OCTOBER 2009.
- 1) 19.0' NE TO A CONCRETE NAIL & WASHER FOUND IN A 12" ELM TREE
 - 2) 4.5' NW TO A SPIKE & KDOT WASHER FOUND IN A 20" KENTUCKY COFFEY TREE
 - 3) 3.9' ESE TO A SPIKE & KDOT WASHER FOUND IN A 60" HACKBERRY TREE
 - 4) 15.5' SOUTH TO A CROP LINE RUNNING EAST-WEST
 - 5) 18.9' WEST TO A MAG NAIL FOUND IN AN 18" KENTUCKY COFFEY TREE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,599.86' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11 [**NOTE:** THIS SHOULD BE THE **NORTHEAST** CORNER OF THE SE1/4 OF SECTION 26-18-11 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 3,907.29' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-18-11
 - 3) 5,214.72' EAST TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 26-18-11
- 15) DANIEL E. GARBER, L.S. 683, OF GARBER SURVEYING SERVICES, P.A., IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 25, 2011 AND RECEIVED AT THE COUNTY ENGINEER'S OFFICE ON MARCH 19, 2012, FOR PROJECT NUMBER G2011-395, SAID THAT **HE FOUND THE EXISTING 1/2" ALUMINUM CAPPED REBAR STAMPED "W1/2 26-18-11"** FROM FIELD OBSERVATION AND RECOVERY DURING KDOT PROJECT #99-56KA-0012-01. HE SENT THE FOLLOWING HORIZONTAL TIES:
- 1) 41.89' WEST TO A 60 D SPIKE & BLUE TAIL IN THE NORTH FACE OF A 24" BLACK WALNUT TREE
 - 2) 71.13' WNW TO A 60 D SPIKE & RED TAIL IN THE NORTH FACE OF A 14" HACKBERRY TREE
 - 3) 71.88' NE TO A 60 D SPIKE & BLUE TAIL IN THE NORTH FACE OF A 14" BLACK WALNUT TREE
 - 4) 42.44' EAST TO A 60 D SPIKE & RED TAIL IN THE NORTH FACE OF A 48" ELM CLUSTER
 - 5) 154.39' SE TO THE CENTERLINE TOP OF A 24" X 5/8" GREEN CAPPED GSS CONTROL POINT #4
 - 6) 201.77' SE TO THE CENTERLINE TOP OF A 1/2" REBAR AT P.T. STATION 152+07.10 IN HIGHWAY K-99
 - 7) 192.80' SE TO A NAIL & WASHER IN A DELINEATOR POST
 - 8) 153.85' EESE TO A MAG NAIL & BLUE TAIL SET IN THE EAST EDGE OF THE ASPHALT OPPOSITE OF A DELINEATOR POST
- 16) DANIEL E. GARBER, L.S. 683, OF GARBER SURVEYING SERVICES, P.A., IN A *NOTICE OF COMPLETION OF ENDANGERMENT ACTIVITY AND REPORT OF RESTORATION* LAND SURVEY REFERENCE REPORT DATED NOVEMBER 13, 2013, FOR PROJECT NUMBER G2011-395, SAID THAT **HE FOUND EXISTING THE 1/2" ALUMINUM CAPPED REBAR STAMPED "W1/2 26-18-11"** AT THE WEST 1/4 CORNER OF SECTION 26-18-11 FROM TIES OF RECORD. HE SENT THE FOLLOWING HORIZONTAL TIES:
- 1) 41.89' WEST TO A 60 D SPIKE & BLUE TAIL IN THE NORTH FACE OF A 24" BLACK WALNUT TREE

HIS INFORMATION IS CONTINUED ON PAGE 6

- 2) 71.13' WNW TO A 60 D SPIKE & RED TAIL IN THE NORTH FACE OF A 14" HACKBERRY TREE
 - 3) 71.88' NE TO A 60 D SPIKE & BLUE TAIL IN THE NORTH FACE OF A 14" BLACK WALNUT TREE
 - 4) 42.44' EAST TO A 60 D SPIKE & RED TAIL IN THE NORTH FACE OF A 48" ELM CLUSTER
 - 5) 154.39' SE TO THE CENTERLINE TOP OF A 24" X 5/8" GREEN CAPPED GSS CONTROL POINT #4
 - 6) 201.77' SE TO THE CENTERLINE TOP OF A 1/2" REBAR AT P.T. STATION 152+07.10 IN HIGHWAY K-99
 - 7) 192.80' SE TO A NAIL & WASHER IN A DELINEATOR POST
 - 8) 153.85' EESE TO A MAG NAIL & BLUE TAIL SET IN THE EAST EDGE OF THE ASPHALT OPPOSITE OF A DELINEATOR POST
- 17) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 19, 2016 FOR PROJECT NUMBER 16058-02 FOR THE LYON COUNTY HIGHWAY DEPARTMENT DUE TO THE KDOT MILLING AND OVERLAY PROJECT ON K-99 HIGHWAY FROM THE ALLEN CREEK BRIDGE TO THE INTERSECTION OF K-170 HIGHWAY, SAID THAT **HE FOUND THE EXISTING RECORD 1/2" IRON BAR WITH A KDOT ALUMINUM CAP STAMPED "W1/4 26-18-11E"** AT THE WEST 1/4 CORNER OF SECTION 26-18-11 FROM HIS EXISTING REFERENCE TIES BY GARBER, L.S. 683 IN 2013 AND ON FILE AT THE LYON COUNTY ENGINEER'S OFFICE.
- 1) UN-ADJUSTED STATE PLANE COORDINATES: KANSAS ZONE SOUTH
NORTH = 1972109.200800 EAST = 1979282.0633
 - 2) 42.70' WEST TO A 60 D SPIKE AND BLUE TAIL IN A BLACK WALNUT TREE
 - 3) 72.30' NE TO A 60 D SPIKE AND BLUE TAIL IN A BLACK WALNUT TREE
 - 4) 42.70' EAST TO A 60 D SPIKE AND RED TAIL IN AN ELM TREE
 - 5) 1.00' SOUTH TO A STEEL FENCE POST
 - 6) 3.00' SOUTH TO A LINE OF FENCE EAST-WEST

WEST QUARTER CORNER 26-18-11