

WEST 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 26, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 82, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 11-25, 1903 AT THE REQUEST OF T. S. JONES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 22-18-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE EAST 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 178 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 73" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 26-18-11 ON LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER OF SECTION 26-18-11 AND THE THEORETICAL LOCATION FOR THE CENTER OF SECTION 26-18-11. THIS POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,309.17' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 2) 1,309.17' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 3) 3,965.85' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11
 - 4) 2,089.70' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A TRACT CORNER
 - 5) 2,114.70' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A TRACT CORNER
 - 6) 2,664.48' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 26-18-11

WEST SIXTEENTH CORNER NORTHEAST QUARTER 26-18-11