

CENTER CORNER SECTION 27, TOWNSHIP 18 SOUTH, RANGE 11 EAST

1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 32 RECORDED IN SURVEY BOOK "A" ON PAGE 127 DATED APRIL 4, 1868 FOR A SURVEY OF WILLIAM STANLEY'S AND OTHERS LAND, BEING THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 27-18-11, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 27-18-11 ON THIS SURVEY.

2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 5 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 60 DATED FEBRUARY 19, 1874 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 27-18-11 INTO NORTH AND SOUTH HALVES, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 27-18-11 ON THIS **PERMANENT SURVEY**. HIS NOTES SAY TO SEE SURVEY NUMBER 32 OF THE 5TH TERM DATED APRIL 4, 1868.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,317-1/2' NORTH TO THE 16" X 5" X 5" STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 27-18-11
- 2) 2,635' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-18-11

3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 24 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 79 DATED MAY 14, 1874 TO ESTABLISH THE 1/2/4 CORNER ON THE NORTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 27-18-11, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 27-18-11 "ALREADY ESTABLISHED" ON THIS **PERMANENT SURVEY**. HIS NOTES SAY "SEE NUMBER 32 IN 5TH TERM".

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,314' EAST TO THE 14" X 10" X 2" STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 27-18-11
- 2) 2,648' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-18-11

4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 161 DATED AUGUST 1903, SAID THAT **HE FOUND A STONE MARKED "1/4" ON THE WEST SIDE** AT THE CENTER CORNER OF SECTION 27-18-11 ON THIS **PERMANENT SURVEY**.

- 1) 2 FEET EAST OF A FENCE CORNER, AND 20 FEET NORTH
- 2) 1 FOOT WEST OF AN 8" WALNUT TREE

5) KARA LaRIVIERE, L.S. 1413, WITH THE KANSAS DEPARTMENT OF TRANSPORTATION, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 99-56 KA-0012-01, SAID THAT **SHE FOUND A 2.5" X 18" LIMESTONE AT 0.4' DEEP** AT THE CENTER CORNER OF SECTION 27-18-11 FROM THE 1868 SURVEY BY COUNTY SURVEYOR D. T. McAULEY FILED IN SURVEY BOOK "A" ON PAGE 127 AT THE LYON COUNTY HIGHWAY DEPARTMENT. KDOT CORNER 27008

- 1) 3.7' SOUTH TO A SET SPIKE & KDOT WASHER IN A 20" DIAMETER HACKBERRY
- 2) 7.0' NNE TO A SET SPIKE & KDOT WASHER IN A 10" DIAMETER TREE
- 3) 18.2' NW TO A SET SPIKE & KDOT WASHER IN A 10" DIAMETER TREE
- 4) 0.5' EAST TO A LONE OLD HEDGE POST LEANING WEST
- 5) IN LINE WITH AN OLD FENCE AND HEDGE LINE TO THE NORTH
- 6) IN LINE WITH FENCE REMNANTS TO THE WEST

THE DRAWING SIGNED BY LARRY DEE MOORE, L.S. 1174 DATED APRIL 20, 2010 SHOWS THE FOLLOWING INFORMATION:

- 1) PROJECT COORDINATES ON SECTION CORNERS: COORDINATES X 0.999928556 = STATE PLANE COORDINATES NAD-83 [1997 ADJUSTMENT] KANSAS SOUTH ZONE: NORTH = 1972204.239 EAST = 1976781.178
- 2) 2,634.20' WEST TO THE 1/2" BAR AT 0.7' DEEP SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-18-11
- 3) 2,639.01' NORTH TO THE 1/2" KDOT ALUMINUM CAPPED REBAR SHE SET OVER THE STONE SHE FOUND AT 0.2' DEEP AT THE NORTH 1/4 CORNER OF SECTION 27-18-11
- 4) 2,642.76' EAST TO THE 1/2" KDOT ALUMINUM CAPPED REBAR SHE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-18-11

CENTER CORNER 27-18-11