

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 347 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 22" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.94 CHAINS WEST TO THE 20" X 10" X 6" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-18-11
 - 2) 39.93 CHAINS EAST TO THE 26" X 19" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-18-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 63 RECORDED IN SURVEY BOOK "A" ON PAGE 163 DATED JULY 15, 1868 FOR A ROAD SURVEY PETITIONED BY L. H. JOHNSTONE AND OTHERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 29-18-11 ON THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 21 LINKS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-18-11
 - 2) 54 RODS EAST TO THE EMPORIA ROAD AT A STONE HE SET IN THE GROUND FOR THE TERMINUS OF THIS ROAD SURVEY

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 90 [PACKET 165 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY L. H. RICHARDSON AND OTHERS SURVEYED JULY 15, 1868, ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 225 AS A 60 FOOT WIDE ROAD AND FILED AND RECORDED ON JULY 21, 1868 BY J. L. WILLIAMS, LYON COUNTY CLERK, SAID THAT **HE FOUND THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 29-18-11 AT A TURN ON THIS ROAD SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 159 RODS AND 22 LINKS TO THE NORTHWEST CORNER OF SECTION 29-18-11 AT A TURN TO THE NORTH ON THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 54 RODS TO A STONE HE SET IN THE GROUND AT A POINT IN THE EMPORIA AND AMERICUS ROAD FOR THE TERMINUS OF THIS ROAD SURVEY

- 4) D. W. BOWMAN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 66 RECORDED IN SURVEY BOOK "A" ON PAGE 166 DATED JULY 22, 1868 FOR S SURVEY OF LAND OWNED BY JOHN WHITE AND OTHERS, BEING SECTION 20-18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 20-18-11 ON THIS SURVEY.

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 163 DATED FEBRUARY 10, 1879, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 29-18-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640' EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-18-11

- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 20 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 78 TO 80 FOR A PETITION BY PETER SLISHER AND OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN SECTION 29-18-11 [PACKET 13 IN THE VAULT

IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 29, 1879, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 7, 1879, AND WAS RECORDED ON APRIL 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 29-18-11 FOR THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 2,640 FEET TO THE NORTHWEST CORNER OF SECTION 28-18-11; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 3,960 FEET TO THE NORTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 28-18-11 TO COMMENCE THIS ROAD SURVEY
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGE 106 FOR ROAD NUMBER 27 AND DATED JULY 1879, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-18-11 ON THIS ROAD SURVEY.
- 8) **REA PIN—VERIFY AND CHECK FOR THE STONE OF RECORD AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 31 ON PAGE 2 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 20-18-11 AT 2,630 FEET EAST OF THE SOUTHWEST CORNER OF SECTION 20-18-11 AND IN LINE WITH A HEDGE TO THE SOUTH AND A FENCE TO THE NORTH.
 - 1) 25' NORTH TO A WITNESS PIN 3' ± NORTH OF A LARGE POST
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS A **REA PIN** AT THE 'SW CORNER SE1/4 SECTION 20-18-11" AND "NW CORNER NE1/4 SECTION 29-18-11". **VERIFY AND CHECK FOR THE STONE OF RECORD AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' NORTH TO A WITNESS [REA]
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 1, 2005, FOR PROJECT NUMBER 05362-02, SURVEY F20001 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 6.69 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 20-18-11 FOR PAUL HANCOCK/MICHAELS, SAID THAT **HE FOUND A 1/2" REBAR OF UNKNOWN ORIGIN** AT THE SOUTH 1/4 CORNER OF SECTION 20-18-11.
 - 1) 5.5' NORTH TO THE TRAVELED-WAY DIRT COUNTY ROAD 200 EAST-WEST
 - 2) 12.0' WEST TO A HEDGE TO THE SOUTH
 - 3) ON THE SOUTH EDGE OF A DIRT ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,640.63' WEST TO THE SQUARE #5 BAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 20-18-11
 - 2) 2,640.36' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 20-18-11
 - 3) 2,231.20' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE SOUTHWEST CORNER OF THE 6.69 ACRE TRACT
 - 4) 2,671.20' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 20-18-11
 - 5) 5,355.38' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 20-18-11 WITH A 5/8" REBAR WITH A LYON COUNTY CAP HE SET OVER THE 3/4" REBAR HE FOUND

NORTH QUARTER CORNER 29-18-11