

NORTH 1/4 CORNER SECTION 30, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 348 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 18" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-18-11 ON DECEMBER 20, 1956.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 37.78 CHAINS WEST TO THE POST THEY SET FOR THE CORNER TO SECTIONS 19 & 30-18-11 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 20" X 10" X 6" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-18-11
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 26 RECORDED IN SURVEY BOOK "A" ON PAGE 121 FOR THE SURVEY OF EDWIN MOOREHEAD'S LAND, BEING THE WEST HALF OF THE SOUTHWEST CORNER OF SECTION 30, TOWNSHIP 18, RANGE 11, THAT HE SURVEYED ON MARCH 13, 1868, SAID THAT **HE FOUND** THE NORTH 1/4 CORNER OF SECTION 30-18-11 ON THE RANGE LINE ON THIS SURVEY. HE DID NOT IDENTIFY THE MONUMENT THAT HE FOUND AT THIS CORNER, BUT THE MONUMENT OF RECORD WAS A **SANDSTONE**. HE NOTED THAT NO PLAT OF SURVEY WAS REQUIRED. A NOTE BELOW THE SURVEY READ: "THE ABOVE SURVEY HAS NOT BEEN CORRECTLY DONE. SEE STATUTES 1868 SECTIONS 161 & 162 OF CHAPTER 25. ROBERT MILLIKEN, COUNTY SURVEYOR, DATED OCTOBER 4, 1874", FOLLOWED BY A PENCIL NOTE THEN READ: "ROBERT MILLIKEN IS WAY OFF. THE CHAPTER REFERRED TO ABOVE DID NOT TAKE EFFECT UNTIL OCTOBER 31, 1868. D. T. McAULEY IS ALL RIGHT."

HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS SOUTH VARIANCE 11°30' E. TO THE TEMPORARY POST HE ESTABLISHED FOR THE CENTER CORNER OF SECTION 30-18-11
 - 2) 320 RODS SOUTH VARIANCE 11°30' E. TO THE SOUTH 1/4 CORNER OF SECTION 30-18-11
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 44 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 101 DATED SEPTEMBER 24 & 25, 1874 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 30-18-11, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-18-11 ON THIS **PERMANENT SURVEY**. A NOTE IN THE LEFT MARGIN SAID TO SEE SURVEY NUMBER 26 OF THE 5TH TERM DATED MARCH 16, 1868.

HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 1,771' WEST TO THE STONE HE SET FOR THE PERMANENT CORNER BETWEEN LARKIN AND MOOREHEAD
 - 2) 2,424' WEST TO THE DECAYED POST THAT HE FOUND AT THE CORNER BETWEEN SECTIONS 19 & 30 ON THE RANGE LINE THAT **HE REPLACED WITH A SANDSTONE 18" X 12" X 6"** FOR THE PERMANENT CORNER TO SECTIONS 19, 30, 24 & 25, TOWNSHIP 18, RANGES 10 & 11
 - 3) 2,659' [124.81 RODS] SOUTH TO THE 18" X 10" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-18-11
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 160, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 160 ORDERED BY GEORGE ATKINSON TO LOCATE THE EAST 1/4 CORNER AND THE CENTER OF SECTION 30, TOWNSHIP 18, RANGE 11, THAT HE SURVEYED ON MARCH 23 & 24, 1887, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 30-18-11 ON THIS **PERMANENT SURVEY**. [NOTE: THIS SURVEY WAS RECORDED DECEMBER 24, 1887 IN VOLUME 41 ON PAGE 285 IN THE REGISTER OF DEEDS

OFFICE, AND AS SURVEY F30005 IN THE SURVEY FILE FOR TOWNSHIP 18-11 IN THE COUNTY SURVEYORS OFFICE. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS FIELD NOTES AND PLAT OF SURVEY SHOW THE FOLLOWING INFORMATION:

- 1) THE VARIANCE ON THE NORTH-SOUTH CENTERLINE OF SECTION 30-18-11 TO THE 5" X 9" X 7" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-18-11 IS 10°5'

NORTH QUARTER CORNER 30-18-11