

NORTH 1/16TH CORNER OF THE SOUTHEAST QUARTER OF SECTION 31, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 6, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 186 DATED MAY 14, 1900 ORDERED BY J. A. SPRAGUE TO SURVEY THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11, SAID THAT **HE SET A STONE POINTED AT THE TOP, SQUARE, 20" X 9" X 6"** FOR THE PERMANENT NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER AND THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 19.87 CHAINS WEST TO THE 6" X 12" X 18" STONE SET FOR THE PERMANENT CENTER OF SECTION 31
 - 2) 19.87 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31007 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE SOUTH HALF OF THE NORTHEAST QUARTER OF THE SOUTHEAST QUARTER AND THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 31-18-11, EXCEPT THE SOUTH 46.5 FEET AND TWO OTHER TRACTS, FOR PROJECT NUMBER 95246-02 DATED DECEMBER 7, 1995 SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE 1/16TH CORNER ON THE NORTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 31 ON LINE AND HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 31, BUT IT WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,315.31' WEST TO A 1/2" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 31
- 2) 1,315.31' EAST TO A 1/2" REBAR HE FOUND AT THE EAST 1/4 CORNER OF SEC. 31
- 3) 1,324.34' SOUTH TO A #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF THE SE1/4 OF SECTION 31
- 4) 662.17' SOUTH TO A #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF THE SE1/4 OF SECTION 31
- 5) 1,324.34' SOUTH TO A #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH- WEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 31
- 6) 2,649.68' SOUTH TO A 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE E1/4 OF THE SE1/4 OF SECTION 31

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31008 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 15.6 ACRE TRACT OF LAND IN THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 31-18-11, FOR PROJECT NUMBER 97404-02 DATED DECEMBER 20, 1997 SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 670.00' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 15.6 ACRE TRACT
- 2) 1,315.31' WEST TO A 1/2" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 31
- 3) 1,457.30' SOUTH TO A 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF QUAIL RUN SUBDIVISION AND THE SOUTHEAST CORNER OF THE 15.6 ACRE TRACT

CONTINUED ON PAGE 2

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 7, 2009 FOR PROJECT NUMBER 09076-02, SURVEY F31015 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A TRACT IN THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 31-18-11 FOR WILLIAMS, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE NORTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 31 FROM HIS PRIOR SURVEY RECORDED IN 1995 IN VOLUME 501 ON PAGE 573 IN THE REGISTER OF DEEDS OFFICE.
- 1) 1.5' NW TO A CONCRETE NAIL & BOTTLE CAP IN A CORNER FENCE POST
 - 2) 1.0' NORTH TO A FENCE TO THE WEST
 - 3) 1.0' WEST TO A LINE OF FENCE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) 1,315.21' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 31
 - 2) 1,559.70' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE EXCEPTED TRACT
 - 3) 2,648.70' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 31

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 31-18-11