

NORTHWEST CORNER SECTION 31, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 47 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 26" X 10" X 3"** FOR THE CORNER TO SECTIONS 30 & 31-18-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 37.85 CHAINS EAST TO THE 18" X 16" X 3" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-18-11
 - 2) 77.85 CHAINS EAST TO THE 24" X 10" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 29,30, 31 & 32-18-11
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 25" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-18-11
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 24" X 2" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 10 & 11 EAST AT THE SOUTHWEST CORNER OF SECTION 31-18-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 26 RECORDED IN SURVEY BOOK "A" ON PAGE 121 AND DATED MARCH 1868, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE ON THIS SURVEY.

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 38 TO 40 FOR ROAD NUMBER 10 BY A PETITION BY J. N. SWEET AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 18-11 [PACKET 106 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 16, 1878, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 7, 1878, AND WAS RECORDED ON DECEMBER 3, 1878 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE AT A TURN ON THIS ROAD SURVEY. SEE THE SURVEY DRAWING FOR THE ROAD THAT WAS **VACATED** ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,640' TO THE NORTH 1/4 SECTION CORNER OF SECTION 36-18-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 5,280' TO THE SOUTHEAST CORNER OF SECTION 36-18-10 ON THE TOWNSHIP LINE

- 4) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 35
ON JULY 6, 1914 A PETITION SIGNED BY ED ATKINSON AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 18-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON OCTOBER 13, 1914, AND THE FINAL ORDER WAS ISSUED ON NOVEMBER 5, 1914.
 - 1) BEGINNING AT THE SOUTHEAST CORNER OF SECTION 25-18-10; THENCE NORTH ONE HALF MILE AND TERMINATING AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 25-18-10
 - 2) THE ROAD GRANTED WAS 25 FEET WIDE

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 685 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 42 PETITION BY ED ATKINSON AND OTHERS FOR A ROAD ON THE RANGE LINE BETWEEN TOWNSHIP 18-10 AND TOWNSHIP 18-11 [PACKET 877 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED AND WAS VIEWED WITH THE COUNTY

COMMISSIONERS ON OCTOBER 13, 1914 AND WAS ORDERED OPENED AT 25 FEET WIDE, 12-1/2 FEET ON EACH SIDE OF THE RANGE LINE, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE SOUTHEAST CORNER OF SECTION 25-18-10 ON THE RANGE LINE. HE DID NOT MENTION IF HE FOUND OR SET THIS CORNER.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINES FOR 1/2 MILE TO THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 25-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 6, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 186 DATED MAY 14, 1900 ORDERED BY J. A. SPRAGUE TO SURVEY PART OF SECTION 31-18-11, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE. HE SET A **TEMPORARY STAKE** FOR THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE AT THE PROPORTIONAL DISTANCE BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-18-11 AND THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.96 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-18-11
 - 2) 39.96 CHAINS SOUTH ON THE RANGE LINE TO THE TEMPORARY STAKE HE SET FOR WEST 1/4 CORNER OF SECTION 31-18-11
 - 3) 79.92 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF SECTION 31-18-11
 - 4) 119.88 CHAINS SOUTH ON THE RANGE LINE TO THE GOVERNMENT STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-19-11
 - 5) 37.90 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-18-11
- 7) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A SURVEY BY THE CONSENT OF THE PARTIES INTERESTED IN SECTION 36-18-10 RECORDED IN SURVEY BOOK "D" ON PAGE 170 THAT HE COMPLETED ON FEBRUARY 26, 1916, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE ON THIS CONSENT SURVEY.
- 8) REA BOOK 31 ON PAGE 5 SAYS THAT **THEY DROVE AN IRON PIN** AT 2,647.8' EAST OF THE SOUTH 1/4 CORNER OF SECTION 25-18-10 IN THE CENTER OF THE INTERSECTION FOR THE SOUTHEAST CORNER OF SECTION 25-18-10 ON THE RANGE LINE. THEY NOTED IN THE MARGIN THAT THE SOUTH 1/4 CORNER OF SECTION 30-18-11 IS 2,500 FEET EAST OF THIS CORNER.
- 1) 33' SE TO A WITNESS PIN
 - 2) 25' NE TO A WITNESS PIN
- 9) LARGE SURVEY SR #01003 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE. THERE IS NO NAME OR DATE ON THE SURVEY, BUT A PENCIL NOTE FOR THE NORTHWEST CORNER OF SECTION 6-19-11 SHOWS "IRON PIN SET 8/9/56".
THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,275.2' SOUTH ON THE RANGE LINE TO THE IRON PIN THEY SET 8/9/56 FOR THE SOUTHEAST CORNER OF SECTION 36-18-10
- 10) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36008 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY FOR A TRACT IN THE NORTHEAST 1/4 OF SECTION 36-18-10 DATED OCTOBER 22, 1958, HE SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF

SECTION 36-18-10. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY,

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318.12' SOUTH ON THE RANGE LINE TO THE "MONUMENT" HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 36-18-10 AND THE NORTHEAST TRACT CORNER – NOT DESCRIBED
- 2) 1,671.22' SOUTH ON THE RANGE LINE TO THE "MONUMENT" HE SET FOR THE SOUTHEAST TRACT CORNER – NOT DESCRIBED

- 11) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36005 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF 3 TRACTS TRACT IN THE NORTHEAST 1/4 OF SECTION 36-18-10 DATED OCTOBER 26, 1971, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,598.62' WEST TO THE NORTHEAST CORNER OF TRACT NUMBER 1
- 2) 1,873.74' WEST TO THE NORTHEAST CORNER OF TRACT NUMBER 2
- 3) 2,148.86' WEST TO THE "MONUMENT" HE SET FOR THE NORTHEAST CORNER OF TRACT NUMBER 3 – NOT DESCRIBED
- 4) 2,607.39' WEST TO A "MONUMENT" HE SET FOR THE NORTHWEST CORNER OF TRACT NUMBER 3 – NOT DESCRIBED

- 12) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A SURVEY NOT DATED BUT AFTER OCTOBER 26, 1971, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF A 5 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 36-18-10, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,598.62' WEST TO THE NORTHEAST CORNER OF TRACT NUMBER 1 PREVIOUSLY SURVEYED
- 2) 1,873.74' WEST TO THE NORTHEAST CORNER OF TRACT NUMBER 2 PREVIOUSLY SURVEYED
- 3) 2,148.86' WEST TO THE NORTHEAST CORNER OF TRACT NUMBER 3 PREVIOUSLY SURVEYED
- 4) 2,607.39' WEST TO THE "MONUMENT" HE SET FOR THE NORTHWEST CORNER OF TRACT NUMBER 3, BEING THE NORTHEAST CORNER OF THE 5 ACRE TRACT BEING SURVEYED – NOT DESCRIBED
- 5) 2,646.39' WEST TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 36-18-10 – NOT DESCRIBED

- 13) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 TO LOCATE THE CORNERS OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 25-18-10 DATED JANUARY 19, 1972, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE SOUTHEAST CORNER OF SECTION 25-18-10 ON THE RANGE LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.50' WEST TO THE SPIKE IN THE CENTERLINE OF THE ROAD AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 25-18-10
- 2) 1,319.50' NORTH ON THE RANGE LINE TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 25-18-10

CONTINUED ON PAGE 4

- 14) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A SURVEY NOT DATED, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF A 10 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 36-18-10, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,323.5’ WEST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 10 ACRE TRACT
- 15) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JULY 6, 1983, SAID THAT **HE FOUND A 5” X 12” YELLOW LIMESTONE AT 5” DEEP AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE. HE SET 5/8” X 24” REBARS WITH LYON COUNTY CAPS ON THE EAST & WEST SIDES OF THE STONE.** HE SAID THAT THIS STONE WAS SET BY W. G. RUGGLES, COUNTY SURVEYOR, IN 1916 AS RECORDED IN SURVEY BOOK “D” ON PAGE 170.
- 1) **5.25’ ESE TO A 5/8” REBAR FOUND**
 - 2) 28.0’ EAST TO A LINE OF FENCE TO THE SOUTH-EXTENDED
 - 3) 44.8’ NW TO A SPIKE IN A POWER POLE
 - 4) 35.8’ SE TO A RAILROAD SPIKE IN A CORNER POST
 - 5) IN LINE WITH THE WEST SHOULDER OF THE ROAD TO THE NORTH
 - 6) IN THE TRAVELED WAY OF THE ROAD TO THE EAST
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 2, 1993, SAID THAT **HE FOUND THE STONE WITH THE 5/8” REBARS WITH LYON COUNTY CAPS ON THE EAST & WEST SIDES OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE FROM HIS PREVIOUS TIES OF RECORD DATED JULY 6, 1983.
- 1) 30.4’ NNE TO A TELEPHONE PEDESTAL
 - 2) 46.9’ NORTH TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 3) 36.8’ SSW TO A SPIKE IN A CORNER FENCE POST
 - 4) 6.0’ WEST TO THE TRAVELED WAY OF COUNTY ROAD “G” TO THE NORTH
 - 5) **5.25’ ESE TO A 5/8” REBAR FOUND**
- 17) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1996, FOR PROJECT NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT **SHE FOUND THE STONE WITH A 5/8” CAPPED REBAR ON THE WEST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE FROM TIES OF RECORD BY STEVEN S. BROSEMER, L.S. 752, DATED JULY 1983 AND NOVEMBER 1993.
- 1) STATE PLANE COORDINATES IN U.S. FEET AT GROUND LEVEL
NORTH = 1968927.376 EAST = 1958384.475
 - 2) 30.4’ NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 30.65’ NNW TO A 1/2” REBAR SET FOR A WITNESS
 - 4) 47.4’ NORTH TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 5) 35.2’ SSW TO A RAILROAD SPIKE IN A CORNER FENCE POST
 - 6) 29.0’ EAST TO A LINE OF FENCE TO THE SOUTH
 - 7) **5.25’ ESE TO A 5/8” REBAR FOUND**
- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1997, FOR PROJECT NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT **HE FOUND THE STONE WITH A 1/2” REBAR ON THE WEST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE FROM HIS PREVIOUS TIES OF RECORD.

- 1) STATE PLANE COORDINATES IN U.S. FEET AT GROUND LEVEL
NORTH = 1968927.376 EAST = 1958384.475
 - 2) 30.4' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 30.65' NNW TO A 1/2" REBAR SET FOR A WITNESS
 - 4) 47.4' NORTH TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 5) 35.2' SSW TO A RAILROAD SPIKE IN A CORNER FENCE POST
 - 6) 29.0' EAST TO A LINE OF FENCE TO THE SOUTH
 - 7) **5.25' ESE TO A 5/8" REBAR FOUND**
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31010 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF TWO TRACTS IN THE NORTHWEST QUARTER OF SECTION 31-18-11 DATED DECEMBER 13, 1999, FOR PROJECT NUMBER 99668-02, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE WITH THE 5/8" REBAR ON THE EAST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 31-18-11 ON THE RANGE LINE FROM HIS PREVIOUS TIES OF RECORD. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,504.20' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A TRACT CORNER
 - 2) 1,954.20' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A TRACT CORNER
 - 3) 2,354.20' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A TRACT CORNER
 - 4) 2,504.20' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 31-18-11
- 20) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 2001, SAID THAT **SHE FOUND THE STONE WITH 5/8" REBARS ON THE EAST AND WEST SIDES OF THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE, MANY OF WHICH HAVE BEEN DESTROYED BY RECENT CONSTRUCTION IN SECTION 31-18-11. SHE RE-REFERENCED THIS CORNER TO PRESERVE HER TIES.
- 1) **5.25' EAST AND 1.0' NORTH TO A 5/8" REBAR OF UNKNOWN ORIGIN FOUND**
 - 2) 30.4' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 47.4' NORTH TO A MASONRY NAIL & WASHER IN A POWER POLE
 - 4) 29.75' NE TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
 - 5) 56.90' SSE TO A MASONRY NAIL & WASHER IN A POWER POLE
 - 6) 17.7' NORTH TO THE RIGHT-OF-WAY FENCE RUNNING EAST
 - 7) 20.0' EAST TO THE RIGHT-OF-WAY FENCE RUNNING NORTH
 - 8) 54.80' SOUTH TO A LINE OF POWER POLES RUNNING WEST
 - 9) 6.60' EAST TO THE TRAVELED WAY OF COUNTY ROAD "G" TO THE NORTH
- 21) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2001, FOR PROJECT NUMBER 01414-02, SAID THAT **HE FOUND THE STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE EAST SIDE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED OCTOBER 2001.
- 1) **5.25' EAST TO A 5/8" REBAR FOUND**
 - 2) 47.4' NORTH TO A SPIKE & WASHER IN A POWER POLE
 - 3) 53.45' SSE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 30.4' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL

HIS INFORMATION IS CONTINUED ON PAGE 6

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 2,504.35' EAST TO THE NORTH 1/4 CORNER OF SECTION 31-18-11
- 2) 2,636.94' SOUTH ON THE RANGE LINE TO THE WEST 1/4 CORNER OF SECTION 31-18-11
- 3) 5,273.39' SOUTH ON THE RANGE LINE TO THE SOUTHWEST CORNER OF SECTION 31-18-11 ON THE TOWNSHIP LINE

- 22) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31011 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TWO TRACTS IN THE NORTHWEST FRACTIONAL QUARTER OF SECTION 31-18-11 DATED MARCH 28, 2002, FOR PROJECT NUMBER 02023-02, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE WITH THE 5/8" REBAR ON THE EAST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,504.20' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND FROM A PREVIOUS SURVEY AT THE NORTHWEST CORNER OF THE WEST TRACT
- 2) 2,104.20' EAST TO THE P.O.B. OF THE WEST TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20' SOUTH
- 3) 2,504.02' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 31-18-11

- 23) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 22, 2005, FOR PROJECT NUMBER 05417-02, SURVEY F25009 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF A 10 ACRE TRACT IN THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 25-18-10 FOR COLDWELL BANKER, SAID THAT **HE FOUND THE STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE EAST SIDE OF THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-18-10 ON THE RANGE LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) **5.25' EAST TO A 5/8" REBAR FOUND**
- 2) 47.4' NORTH TO A SPIKE & WASHER IN A POWER POLE
- 3) 53.45' SSE TO A SPIKE & WASHER IN A POWER POLE
- 4) 30.4' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 5) 41.2' NE TO A SPIKE & WASHER IN A POWER POLE
- 6) 20.0' EAST TO A LINE OF FENCE TO THE NORTH – EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:

- 1) 2,643.31' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 25-18-10

- 24) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 24, 2008, FOR PROJECT NUMBER 07443-02, SURVEY F31013 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 31-18-11 FOR JOHN MALLON, SAID THAT **HE FOUND THE STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE EAST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-18-11 ON THE RANGE LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) **5.25' EAST TO A 5/8" REBAR FOUND OF UNKNOWN ORIGIN**
- 2) 47.4' NORTH TO A SPIKE & WASHER IN A POWER POLE
- 3) 53.45' SSE TO A SPIKE & WASHER IN A POWER POLE
- 4) 30.4' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 5) IN LINE WITH GRAVEL COUNTY ROAD 200 TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.75' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 31-18-11

- 25) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 2, 2009 FOR PROJECT NUMBER 09044-02, SURVEY F30006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TWO TRACTS IN THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 30-18-11 FOR FRANCES WHITAKER, SAID THAT **HE FOUND THE STONE AND 5/8" REBAR** AT THE SOUTHWEST CORNER OF SECTION 30-18-11 ON THE RANGE LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) **HE PLACED AN 80 D SPIKE OVER THE TOP OF THE STONE**
 - 2) 47.4' NNW TO A SPIKE & WASHER IN A POWER POLE
 - 3) 53.45' SE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 30.4' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 5) IN THE CENTER OF THE TRAVELED WAY OF COUNTY ROAD 200 TO THE EAST
 - 6) **5.25' EAST TO A 5/8" REBAR FOUND OF UNKNOWN ORIGIN**
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 879.50' NORTH ON THE RANGE LINE TO THE NORTHWEST CORNER OF TRACT 2 AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20' EAST
 - 2) 1,319.54' NORTH ON THE RANGE LINE TO THE 1/2" CAPPED REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 30-18-11 FROM A PREVIOUS SURVEY
 - 3) 1,252.48' EAST TO THE 1/2" CAPPED REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 30-18-11 FROM A PREVIOUS SURVEY
- 26) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 21, 2014, FOR PROJECT NUMBER 14126-02, SURVEY F36012 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF THE RIGHT-OF-WAY OF THE AMERICUS ROAD IN THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 36-18-10 FOR THE LYON COUNTY ROAD AND BRIDGE DEPARTMENT, SAID THAT **HE FOUND THE 80 D SPIKE OVER THE 5/8" REBAR OVER THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-18-10 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES FOR HIS PROJECT NUMBER 09044-02 DATED MARCH 2, 2009.
- 1) **5.25' ESE TO A 5/8" REBAR FOUND [ORIGIN UNKNOWN]**
 - 2) 47.40' NW TO A SPIKE & WASHER IN A POWER POLE
 - 3) 53.45' SE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 30.40' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 200 TO THE EAST
 - 6) 1.0' EAST TO THE CENTERLINE OF COUNTY ROAD "G" TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,321.69' WEST TO THE 2-1/2" MAG NAIL HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 36-18-10
 - 2) 2,643.38' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 36-18-10
 - 3) 1,318.63' SOUTH ON THE RANGE LINE TO THE 2-1/2 MAG NAIL HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 36-18-10, AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET ON THE WEST RIGHT-OF-WAY LINE OF COUNTY ROAD "G"/AMERICUS ROAD
 - 4) 2,637.26' SOUTH ON THE RANGE LINE TO THE 1/2" IRON PIN FOUND FROM REFERENCE TIES BY "LS 1130" [POLLY A. JONES]

NORTHWEST CORNER 31-18-11