

NORTHWEST CORNER SECTION 32, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 345 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 10" X 4" FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-18-11.**
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-18-11
 - 2) 80.00 CHAINS EAST TO THE 22" X 21" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-18-11

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 160, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 160 DATED MARCH 23 & 24, 1887 ORDERED BY GEORGE ATKINSON TO LOCATE THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 30-18-11, SAID THAT **HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 30-18-11 ON THIS PERMANENT SURVEY.** THIS SURVEY WAS RECORDED DECEMBER 24, 1887 IN VOLUME 41 ON PAGE 285 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F30005 IN THE SURVEY FILE FOR TOWNSHIP 18-11.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,641' NORTH TO THE 4" X 8" X 16" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 30-18-11
 - 2) 5,282' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-18-11

- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 629 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 385 THROUGH 388 PETITIONED BY ALEX CARR AND OTHERS FOR A ROAD IN TOWNSHIP 18-11 [PACKET 772 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 24 & 25, 1907, AND WAS GRANTED AS A 40 FOOT WIDE ROAD, 20 FEET EACH SIDE OF THE SURVEYED LINE, ON JULY 5, 1907 AS NOTED BY G. F. ARNOLD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE AT THE NORTHEAST CORNER OF SECTION 31-18-11 ON THIS ROAD SURVEY.**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) HE RAN SOUTH ON THE SECTION LINES FOR 584 FEET TO THE POINT TO BEGIN THIS ROAD SURVEY; THENCE N. 66° W. FOR 558 FEET; THENCE S. 78°19' W. FOR 158 FEET; THENCE N. 51°50' W. FOR 441 FEET; THENCE N. 77°25' W. FOR 93.5 FEET; THENCE S. 72°30' W. FOR 219.8 FEET; THENCE N. 42°6' W. FOR 193 FEET TO THE SECTION LINE; THENCE WEST ALONG THE SECTION LINE FOR 2,520 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 30-18-11 AND ENDING THERE

- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 196, A **PERMANENT/ROAD SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 18 FOR ALEX CARR, PRINCIPAL PETITIONER, FOR COUNTY ROAD NUMBER 629 IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE AT THE NORTHEAST CORNER OF SECTION 31-18-11 TO BEGIN THIS PERMANENT/ROAD SURVEY.** HE NOTED IN THE UPPER RIGHT CORNER THAT HIS SURVEY IS ALSO RECORDED IN ROAD RECORDED BOOK "D" ON PAGE 385.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) HE RAN SOUTH ON THE SECTION LINES FOR 584 FEET TO THE POINT TO BEGIN THIS ROAD SURVEY; THENCE N. 66° W. FOR 558 FEET; THENCE S. 78°19' W. FOR 158 FEET; THENCE N. 51°50' W. FOR 441 FEET; THENCE N. 77°25' W. FOR 93.5 FEET; THENCE S. 72°30' W. FOR 219.8 FEET; THENCE N. 42°6' W. FOR 193 FEET TO

THE SECTION LINE; THENCE WEST ALONG THE SECTION LINE FOR 2,520 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 30-18-11 AND ENDING THERE

- 5) REA BOOK 31 ON PAGE 2 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTHWEST CORNER OF SECTION 29-18-11 BY PRODUCING A LINE OF THE SECTION SOUTH 1 MILE FROM THE WEST 1/4 CORNER OF SECTION 20-18-11.
 - 1) 21' EAST TO A WITNESS PIN

- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JULY 2, 1983, SAID THAT **HE FOUND A 3/4" REBAR** AT THE NORTHWEST CORNER OF SECTION 32-18-11 THAT WAS SET BY SCHWAB-EATON, P.A. [JOHN YOUNG] IN 1981.
 - 1) 2,632.94' SOUTH TO THE REBAR AT THE WEST 1/4 CORNER OF SECTION 32
 - 2) 23.0' WEST TO A CROP LINE NORTH-SOUTH
 - 3) IN LINE WITH FENCE TO THE NORTH, EXTENDED

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 9, 1998, FOR JOB NUMBER 95024-02, SAID THAT **HE FOUND THE 3/4" REBAR** AT THE NORTHWEST CORNER OF SECTION 32-18-11 THAT WAS SET BY JOHN YOUNG OF SCHWAB-EATON, P.A. IN 1981 FROM HIS PREVIOUS TIES DATED JULY 1983.
 - 1) 99.8' SOUTH TO A 1/2" REBAR
 - 2) 6.3' NE TO A 40 D SPIKE & WASHER IN A QUAD BOX ELDER TREE
 - 3) 27.9' NNW TO A 40 D SPIKE & WASHER IN A 12" HACKBERRY TREE
 - 4) 22.0' WEST TO A 40 D SPIKE & WASHER IN A DOUBLE ELM TREE
 - 5) 22.0' WEST TO THE EDGE OF TIMBER
 - 6) **ADJUSTED ELEVATION = 1122.42 [NAD 88]**

NORTHWEST CORNER 32-18-11