

NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 35, TOWNSHIP 18 SOUTH, RANGE 11 EAST

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2011 FOR PROJECT NUMBER 11259-02, SURVEY F26006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF A 7.09 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 FOR EK REALTY [DETWILER/BRAUN], SAID THAT **HE SET A 1/2" X 24" IRON PIN WITH "BROSEMER LS 752" CAP** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 26 ON TRUE LINE AND HALFWAY BETWEEN THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 26.

- 1) 234' NORTH TO A 1/2" IRON PIN WITH "BROSEMER LS 752" CAP SET
- 2) 3' NORTH TO THE SOUTH EDGE OF A CREEK BANK
- 3) 8' WEST TO AN OLD LINE OF FENCE TO THE NORTH EXTENDED
- 4) 12.35' ESE TO A SPIKE & BOTTLE CAP IN A 7"
- 5) 5.8' ESE TO A SPIKE & BOTTLECAP IN A 13"
- 6) 1,320.19' WEST TO A 5/8" IRON PIN WITH A LYON COUNTY CAP [SOUTH 1/4 CORNER OF SECTION 26]
- 7) 1,320.19' EAST TO A 5/8" IRON PIN WITH A LYON COUNTY CAP [SOUTHEAST CORNER OF SECTION 26]

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 234.00' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTH-EAST CORNER OF THE 7.09 ACRE TRACT
- 2) 2,654.02' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 35-18-11