

NORTH 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 35, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGES 66 & 67 DATED JANUARY 12, 1861 TO ESTABLISH THE CENTER POST OF SECTION 35-18-11, ALSO TO DIVIDE THE NORTHWEST 1/4 INTO EAST AND WEST HALVES, ALSO TO DIVIDE THE SOUTHEAST 1/4 INTO EAST AND WEST HALVES, AND TO ESTABLISH THE BOUNDARIES OF A 40 ACRE LOT, BEING THE SOUTH PART OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 34, SAID THAT **HE SET A STONE** FOR THE NORTH 1/4/4 POST OF THE NORTHWEST 1/4 OF SECTION 35 ON LINE AND HALFWAY BETWEEN THE STONE POSTS HE FOUND AT THE NORTHWEST CORNER AND NORTH 1/4 CORNER OF SECTION 35 ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 19.90 CHAINS WEST TO THE STONE POST FOUND AT THE NORTHWEST CORNER OF SECTION 35
 - 2) 19.90 CHAINS EAST TO THE FOUND STONE NORTH 1/4 POST OF SECTION 35
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 10 DATED FEBRUARY 10-12, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 25-26-35-36 IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 35 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 1,316' WEST TO THE STONE FOUND AT THE NORTHWEST CORNER OF SEC. 35
 - 2) 1,299' EAST TO THE STONE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F26003 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF ALL OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 26-18-11 EXCEPTING THE SOUTH 630.5 FEET OF THE ENTIRE SOUTH SIDE OF THE QUARTER WITH NO DATE, SHOWS AN **IRON PIN** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 26. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. **VERIFY BEFORE USING AND CHECK FOR THE WALKER STONE!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 630.5' NORTH TO AN IRON PIN SET FOR THE NORTHWEST CORNER OF THE SOUTH 630.5' OF THE SE1/4 OF THE SW1/4 OF SECTION 26
- 2) 847.3' EAST TO AN IRON PIN SET
- 3) 1,330.9' EAST TO THE STONE AT THE SOUTHEAST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 26

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 35-18-11