

NORTH 1/4 CORNER OF SECTION 36, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 328 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 16" X 13" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.94 CHAINS WEST TO THE 20" X 12" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-18-11
 - 2) 39.94 CHAINS EAST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-18-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 49 RECORDED IN SURVEY BOOK "A" ON PAGES 145 & 146 DATED MAY 12 & 13, 1868 FOR A SURVEY OF LAND OWNED BY BISHOP AND OTHERS, BEING SECTION 36-18-10, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE SOUTHEAST QUARTER AND SOUTHWEST QUARTER INTO 40 ACRE LOTS, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 36-18-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 320 RODS, 2 LINKS SOUTH TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-18-11 ON THE TOWNSHIP LINE

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 10 DATED FEBRUARY 10-12, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 25-26-35-36 IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 36-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,319-1/2' EAST TO THE STAKE SET FOR THE NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 36-18-11
 - 2) 2,639' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-18-11 ON THE RANGE LINE

- 4) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 36-18-11 DATED JULY 14, 1976, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-11, BEING THE POINT OF BEGINNING OF THE 9.1 ACRE TRACT, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 885' WEST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 9.1 ACRE TRACT
 - 2) 158' EAST TO THE IRON PIN IN THE TRAVELED WAY OF THE BURLINGAME ROAD AT THE NORTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-11, BEING THE P.O.B. OF THE 9.1 ACRE TRACT

NORTH QUARTER CORNER 36-18-11