

NORTHWEST CORNER SECTION 36, TOWNSHIP 18 SOUTH, RANGE 11 EAST

- 1) ON PAGE 328 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 20" X 12" X 7"** FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-18-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.94 CHAINS EAST TO THE 16" X 13" X 3" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-18-11
 - 2) 79.88 CHAINS EAST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-18-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGES 66 & 67 DATED JANUARY 12, 1861 TO ESTABLISH THE CENTER POST OF SECTION 35-18-11, ALSO TO DIVIDE THE NORTHWEST 1/4 INTO EAST AND WEST HALVES, ALSO TO DIVIDE THE SOUTHEAST 1/4 INTO EAST AND WEST HALVES, AND TO ESTABLISH THE BOUNDARIES OF A 40 ACRE LOT, BEING THE SOUTH PART OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 34, SHOWS ON HIS DRAWING **THE STONE POST** AT THE NORTHEAST CORNER OF SECTION 35-18-11 WITH THE NOTE "TAKEN FROM THE ROAD SURVEY DATED AUGUST 24," ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.20 CHAINS SOUTH TO THE FOUND STONE EAST 1/4 POST OF SECTION 35-18-11 BASED ON THE ROAD SURVEY
 - 2) 60.34 CHAINS SOUTH TO THE STONE POST HE SET FOR THE NORTHEAST CORNER OF A 40 ACRE LOT IN THE SOUTH PART OF THE E1/2 OF THE SE1/4 OF SECTION 35-18-11
 - 3) 80.41 CHAINS SOUTH TO THE STONE POST HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-18-11 ON THE TOWNSHIP LINE

- 3) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 32 [PACKET 918 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD IN FREMONT TOWNSHIP, BRECKENRIDGE COUNTY, PETITIONED BY THOMAS BRYANT AND OTHERS SURVEYED AUGUST 21, 1861 AND ESTABLISHED DECEMBER 3, 1861 ON THE COMMISSIONERS JOURNAL ON PAGE 163, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-18-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 6.59 CHAINS NORTH TO ANGLE STAKE NUMBER 1 TO THE NORTHWESTERLY
 - 2) 40.20 CHAINS SOUTH TO THE STONE HE FOUND AT THE CORNER TO T. BRYANT'S SHOP
 - 3) 80.41 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-18-11 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGE 128 DATED APRIL 10, 1868 TO SURVEY J. A. FILINER'S LAND, BEING THE SOUTH 1/2 OF THE SOUTHWEST 1/4 AND 20 ACRES MORE OR LESS OF THE WEST END OF THE SOUTHWEST 1/4 AND ALSO TO DIVIDE EQUALLY 60 ACRES MORE OR LESS OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 26-18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 26-18-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 158 RODS, 9-1/2 LINKS WEST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 35-18-11
 - 2) 316 RODS, 19 LINKS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-18-11

- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 49 RECORDED IN SURVEY BOOK "A" ON PAGES 145 & 146 DATED MAY 12 & 13, 1868 FOR A SURVEY OF LAND OWNED BY BISHOP AND OTHERS, BEING SECTION 36-18-10, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE SOUTHEAST QUARTER AND SOUTHWEST QUARTER INTO 40 ACRE LOTS, SAID THAT **HE SET A STONE** FOR THE NORTHWEST CORNER OF SECTION 36-18-11 ON THIS SURVEY.

- 6) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 62 RECORDED IN SURVEY BOOK "A" ON PAGE 162 DATED MAY 30, 1868 FOR A SURVEY OF LAND OWNED BY CLARK AND OTHERS, BEING SECTION 26-18-11 TO DIVIDE THE SOUTHEAST 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 26-18-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS, 10 LINKS NORTH TO THE STONE HE SET FOR THE 1/2/4 CORNER ON THE EAST SIDE OF THE SE1/4 OF SECTION 26-18-11
 - 2) 160 RODS, 20 LINKS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 26-18-11

- 7) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 108 RECORDED IN SURVEY BOOK "A" ON PAGE 199 DATED APRIL 24, 1869 FOR A CHANGE IN A COUNTY ROAD PETITIONED BY M. H. CLARKE AND OTHERS IN TOWNSHIP 18-11, SAID THAT HE BEGAN THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD AT THE SOUTHEAST CORNER OF SECTION 26-18-11 **AT A STONE SET IN THE GROUND.**

- 8) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 10 DATED FEBRUARY 10-12, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 25-26-35-36 IN TOWNSHIP 18-11, SAID THAT **HE SET A STONE** FOR THE NORTHWEST CORNER OF SECTION 36-18-11 BY TAKING THE AVERAGE OF THE DISCREPANCIES IN THE MEASURE OF THE FOUR SECTION LINES BASED ON STONES HE FOUND TO THE NORTH, SOUTH, EAST AND WEST OF THIS CORNER ON THIS **PERMANENT SURVEY.** SEE THE SURVEY FOR HIS METHODOLOGY.

- 9) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 174 & 175 [PACKET 22 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY ARTHUR PLUMB TO VACATE A COUNTY ROAD IN TOWNSHIP 18-12 THAT HE SURVEYED ON JULY 14, 1871, AND WAS ORDERED VACATED AND THE VACATION RECORDED ON SEPTEMBER 4, 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, BEGINNING AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-11, SHOWS ON HIS SURVEY DRAWING A "SECTION CORNER" AT THE NORTHWEST CORNER OF SECTION 36-19-11, BUT HE DOES NOT SAY IF THERE WAS A STONE AT THIS CORNER.

- 10) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 187, A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 7 FOR REQUESTED BY MRS. GUY SERVISS TO MAKE A SURVEY OF THE SECTION LINE BETWEEN SECTIONS 25 & 26-18-11, SAID THAT **HE SET A 1/2" X 1/2" X 24" IRON PIN IN THE GROUND** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-18-11 ON THIS **PERMANENT SURVEY.** THE SURVEY WAS BEGUN ON MARCH 20, 1907 AND ENTERED ON MAY 5, 1907. HIS TIES TO WITNESS TREES:
 - 1) A 5" DIAMETER HEDGE TREE IN A HEDGE CORNER IS S. 89° W. AT 30 FEET
 - 2) A 30" DIAMETER BOX ELDER TREE IS S. 76°30" W. AT 46 FEET

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,640' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 26-18-11 "ON LINE"
 - 2) 5,280' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 26-18-11
- 11) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 16
ON APRIL 11, 1942 A PETITION SIGNED BY C. F. WIGGINS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO TED NEWCOMER, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND O. D. HENRY, COUNTY ENGINEER, ON MAY 6, 1942 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MAY 6, 1942 VACATED THE FOLLOWING ROAD:
- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 36-18-11, THENCE EAST TO A POINT WHERE SAID ROAD INTERSECTS WITH THE BURLINGAME ROAD, AND ENDING THERE
 - 2) SAID ROAD SHOULD BE VACATED. AT THE VIEW ON THE HOUR AND DATE SET FORTH IN THE PETITION, NO PERSON OR PERSONS APPEARED IN PROTEST TO THE PETITION, AND THE BOARD OF VIEWERS NOTICED THE CONDITION OF THE ROAD WAS NOT SAFE OR POSSIBLE FOR PUBLIC TRAVEL, AND THERE HAS BEEN NO DEMAND FOR AN EXPENDITURE OF MONEY SUFFICIENT TO CONSTRUCT THE ROAD TO A POINT WHERE IT WOULD BE OF ANY PUBLIC UTILITY.
 - 3) WE, THEREFORE, FOR THESE REASONS, HAVE ARRIVED AT THE ABOVE DECISION TO VACATE THE ROAD.
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 2, 1982, SAID THAT **HE FOUND THE 1/2" SQUARE REBAR** AT THE NORTHWEST CORNER OF SECTION 36-18-11 THAT WAS SET BY HARRISON PARKMAN IN 1907 ON A SURVEY RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 7. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP OVER THE 1/2" SQUARE REBAR THAT HE FOUND.**
- 1) 13.5' NORTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
 - 2) 7.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 3) 30.7' WEST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
 - 4) 23.5' EAST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
 - 5) 23.0' EAST TO A LINE OF FENCE TO THE SOUTH [EXTENDED]
 - 6) 18' SOUTH TO A LINE OF HEDGE TO THE EAST [EXTENDED]
- 13) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1996, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 2" BELOW THE ROAD SURFACE THAT IS OVER THE 1/2" SQUARE REBAR FROM PARKMAN'S 1907 PERMANENT SURVEY** AT THE NORTHWEST CORNER OF SECTION 36-18-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED NOVEMBER 1982.
- 1) 33.3' WNW TO THE HEAD OF THE LOWER BOLT IN THE SOUTH FACE OF A CORNER POST
 - 2) 7.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 3) 42.95' NE TO A CONCRETE NAIL & WASHER IN A CORNER GATE POST
 - 4) 13.5' NORTH TO A LINE OF FENCE TO THE WEST—EXTENDED
 - 5) 65.10' NW TO A SPIKE & WASHER IN A POWER POLE
 - 6) 23.5' EAST TO A LINE OF FENCE TO THE NORTH—EXTENDED
 - 7) 68.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- HER TIES ARE CONTINUED ON PAGE 4

- 8) 30.7' WEST TO A LINE OF FENCE TO THE NORTH—EXTENDED
 - 9) STATE PLANE COORDINATES IN U.S. FEET—GROUND LEVEL
NORTH = 1969588.368 EAST = 1984619.861
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1997, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 2" BELOW THE ROAD SURFACE THAT IS OVER THE 1/2" SQUARE REBAR FROM PARKMAN'S 1907 PERMANENT SURVEY AT THE NORTHWEST CORNER OF SECTION 36-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.**
- 1) 33.3' WNW TO THE HEAD OF THE LOWER BOLT IN THE SOUTH FACE OF A CORNER POST
 - 2) 7.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 3) 42.95' NE TO A CONCRETE NAIL & WASHER IN A CORNER GATE POST
 - 4) 13.5' NORTH TO A LINE OF FENCE TO THE WEST – EXTENDED
 - 5) 65.10' NW TO A SPIKE & WASHER IN A POWER POLE
 - 6) 23.5' EAST TO A LINE OF FENCE TO THE NORTH – EXTENDED
 - 7) 68.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 8) 30.7' WEST TO A LINE OF FENCE TO THE NORTH – EXTENDED
 - 9) STATE PLANE COORDINATES IN U.S. FEET – GROUND LEVEL
NORTH = 1969588.368 EAST = 1984619.861
- 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 2004, FOR PROJECT NUMBER 04379-02, SURVEY F26004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF AN 18.57 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 26-18-11 FOR STEVE SHIREMAN, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP THAT IS OVER THE 1/2" SQUARE REBAR FROM PARKMAN'S 1907 PERMANENT SURVEY AT THE SOUTHEAST CORNER OF SECTION 26-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JANUARY 1997.**
- 1) 42.95' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 33.3' WNW TO THE HEAD OF THE LOWER BOLT IN THE SOUTH FACE OF A CORNER POST
 - 3) 65.10' NW TO A SPIKE & WASHER IN A POWER POLE
 - 4) 68.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 5) 13.5' NORTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
 - 6) 7.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640.57' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11
 - 2) 5,281.14' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-18-11
 - 3) 2,652.18' NORTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
 - 4) 3,896.49' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 18.57 ACRE TRACT
 - 5) 3,975.69' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 26-18-11
 - 6) 5,299.20' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 26-18-11
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 23, 2008, FOR PROJECT NUMBER 07438-02, SURVEYS F35005 AND F35006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 15.76 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 35-18-11 FOR

FULLER, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP THAT IS OVER THE 1/2" SQUARE REBAR FROM PARKMAN'S 1907 PERMANENT SURVEY** AT THE NORTHEAST CORNER OF SECTION 35-18-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 2004.

- 1) 42.95' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 65.1' NW TO A SPIKE & WASHER IN A POWER POLE
- 3) 68.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 13.5' NORTH TO A LINE OF FENCE TO THE WEST
- 5) 7.0' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "M" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.28' SOUTH TO THE 1/2" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 35-18-11 AND THE P.O.B. OF THE 15.76 ACRE TRACT
- 2) 2,204.42' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752 CAP HE SET FOR THE SOUTHEAST CORNER OF THE 15.76 ACRE TRACT
- 3) 2,645.56' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-11
- 4) 5,309.12' SOUTH TO THE 5/8" REBAR IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-18-11 ON THE TOWNSHIP LINE

- 17) KARA LaRIVIERE, L.S. 1413, WITH THE KANSAS DEPARTMENT OF TRANSPORTATION, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 99-56 KA-0012-01, SAID THAT **SHE FOUND THE 5/8" REBAR WITH NO CAP AT 0.7' DEEP** AT THE SOUTHEAST CORNER OF SECTION 26-18-11 FROM A REFERENCE REPORT FILED BY STEVEN S. BROSEMER, L.S. 752, IN JANUARY 2008. IT WAS ORIGINALLY SET BY COUNTY SURVEYOR HARRISON PARKMAN IN 1907. KDOT CORNER 26,708

- 1) 49.95' NE TO A FOUND CONCRETE NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 2) 65.1' NW TO A FOUND SPIKE & WASHER IN A POWER POLE
- 3) 69.05' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 33.08' WNW TO THE TOP CENTER OF A 2' DIAMETER PIPE CORNER FENCE POST
- 5) 7.5' NORTH TO THE TRAVELWAY OF A PRIVATE DRIVE TO THE EAST
- 6) 13.5' NORTH TO A LINE OF FENCE TO THE WEST
- 7) 7' WEST TO THE TRAVELWAY OF NORTH-SOUTH GRAVEL ROAD "M"

THE DRAWING SIGNED BY LARRY DEE MOORE, L.S. 1174 DATED APRIL 20, 2010 SHOWS THE FOLLOWING INFORMATION:

- 1) PROJECT COORDINATES ON SECTION CORNERS: COORDINATES X 0.999928556 = STATE PLANE COORDINATES NAD-83 [1997 ADJUSTMENT] KANSAS SOUTH ZONE: NORTH = 1969728.323 EAST = 1984761.875
- 2) 2,651.89' NORTH TO THE 3" X 9" X 12" LIMESTONE SHE FOUND AT 0.2' DEEP AT THE EAST 1/4 CORNER OF SECTION 26-18-11
- 3) 5,299.10' NORTH TO THE 5/8" BAR SHE FOUND AT 0.7' DEEP AT THE NORTHEAST CORNER OF SECTION 26-18-11
- 4) 2,640.56' WEST TO THE 5/8" BAR WITH A LYON COUNTY CAP SHE FOUND AT 0.05' DEEP AT THE SOUTH 1/4 CORNER OF SECTION 26-18-11
- 5) 5,280.91' WEST TO THE 5/8" BAR WITH LYON COUNTY CAP SHE FOUND AT 0.6' DEEP AT THE SOUTHWEST CORNER OF SECTION 26-18-11

- 18) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 23, 2011 FOR PROJECT NUMBER MS05, **FOUND THE 1/2" SQUARE IRON PIN AT 21" DEEP THAT WAS SET BY HARRISON PARKMAN, COUNTY SURVEYOR, IN A 1907 SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 7** AT THE NORTHWEST CORNER OF SECTION 36-18-11.

THE 5/8" REBAR THAT WAS OVER THIS 1/2" SQUARE IRON PIN WAS DESTROYED BY COUNTY FORCES ON MARCH 17, 2011 WHILE REPLACING A CROSS ROAD CULVERT. THIS 1/2" SQUARE IRON PIN WAS FOUND FROM REFERENCE TIES BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN JANUARY 1997, OCTOBER 2004, AND JANUARY 2008, AND KARA LaRIVIERE, L.S. 1114, IN MARCH 2010. **I SET A 5/8" X 10" REBAR WITH A LYON COUNTY CAP OVER THE 1/2" SQUARE IRON PIN, WITH THE TOP OF THE 5/8" REBAR AT 11" BELOW THE SURFACE OF THE GRAVEL ROAD.**

- 1) 42.9' NE TO A FOUND CONCRETE NAIL & WASHER IN THE WEST FACE OF A CORNER FENCE POST
 - 2) 65.0' NW TO A FOUND SPIKE & WASHER IN A POWER POLE
 - 3) 33.7' WNW TO THE TOP CENTER OF A 2" DIAMETER STEEL PIPE CORNER FENCE POST
 - 4) 69.05' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 5) 10' NORTH TO THE TRAVELED WAY OF A GRAVEL DRIVEWAY TO THE EAST
 - 6) 8' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "M" NORTH-SOUTH
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2011 FOR PROJECT NUMBER 11259-02, SURVEY F26006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF A 7.09 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-11 FOR EK REALTY [DETWILER/BRAUN], SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE SOUTHEAST CORNER OF SECTION 26 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. **[NOTE: THIS 5/8" REBAR IS OVER THE 1/2" SQUARE REBAR FROM PARKMAN'S 1907 PERMANENT SURVEY - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 43.0' NE TO A CONCRETE NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 2) 65.2' NW TO A SPIKE & WASHER IN A POWER POLE
 - 3) 69.3' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 33.8' WNW TO THE TOP CENTER OF A 2" DIAMETER PIPE CORNER FENCE POST
 - 5) 7' WEST TO THE TRAVEL WAY OF NORTH-SOUTH GRAVEL COUNTY ROAD "M"
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,320.19' WEST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 26-18-11
 - 2) 2,640.38' WEST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 26-18-11
 - 3) 2,651.73' NORTH TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 26-18-11

NORTHWEST CORNER 36-18-11