

**NORTH 1/4 CORNER SECTION 01, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 74 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 6" X 5"** FOR THE NORTH 1/4 CORNER OF SECTION 1-18-12 ON THE TOWNSHIP LINE ON DECEMBER 14, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 36" X 5" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-18-12
  - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 12 & 13 EAST AT THE NORTHEAST CORNER OF SECTION 1-18-12
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** TO ESTABLISH THE CORNERS OF SECTION 36-17-12 DATED APRIL 6 & 7, 1880 AND RECORDED IN THE REGISTER OF DEEDS OFFICE ON MAY 29, 1880, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 17-12, SAID THAT **HE RESET THE STONE THAT HE FOUND** AT THE SOUTH 1/4 CORNER OF SECTION 36-17-12 ON THE TOWNSHIP LINE ON THIS **AGREEMENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.96 CHAINS WEST ON THE TOWNSHIP LINE TO THE ROCK HE PLANTED FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 36-17-12
- 2) 39.92 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-17-12
- 3) 19.96 CHAINS EAST ON THE TOWNSHIP LINE TO THE ROCK HE PLANTED FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 36-17-12
- 4) 39.92 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-17-12
- 5) 20.01 CHAINS NORTH TO THE ROCK HE PLANTED FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 36-17-12
- 6) 40.02 CHAINS NORTH TO THE ROCK HE PLANTED FOR THE CENTER CORNER OF SECTION 36-17-12
- 7) 60.03 CHAINS NORTH TO THE ROCK HE PLANTED FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 36-17-12
- 8) 80.04 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 36-17-12

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 68, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 147 DATED MARCH 3, 1903 FOR MARY D. COULSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 36-17-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN LINE WITH A HEDGE TO THE NORTH AND 25 FEET SOUTH OF THE END OF THE HEDGE** AT THE SOUTH 1/4 CORNER OF SECTION 36-17-12 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 118 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 74" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.06-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 36-17-12, THAT WAS SET BY HIBBEN IN A SURVEY ONLY RECORDED IN THE REGISTER OF DEEDS OFFICE
- 2) 40.12 CHAINS NORTH TO THE 15" X 8" X 4" STONE MARKED "X" ON TOP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 36-17-12, IN THE INTERSECTION OF HEDGE LINES BY THE AFFIDAVIT OF C. W. BATES

NORTH QUARTER CORNER 01-18-12