

**NORTHWEST CORNER SECTION 06, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 71 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 16" X 4" WITH A MOUND OF ROCKS** FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 11 & 12 ON DECEMBER 12, 1856 AT THE NORTHWEST CORNER OF SECTION 6-18-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION

- 1) 34.05 CHAINS EAST ON THE TOWNSHIP LINE TO THE 15" X 6" X 5-1/2" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-18-12
  - 2) 74.05 CHAINS EAST ON THE TOWNSHIP LINE TO THE 15" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-18-12
  - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 12" X 6" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-18-12
  - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 9" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-18-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 31 RECORDED IN SURVEY BOOK "A" ON PAGE 126 DATED APRIL 2, 1868 TO SURVEY SECTION 36-17-11 FOR W. GILLILAND, ANDERSON, SHIELDS, AND ROSYENE, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-17-11 ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 36-17-11
- 2) 160 RODS NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-17-11
- 3) 240 RODS NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 36-17-11
- 4) 320 RODS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 50 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 202 TO 204 PETITION BY JAMES CALL AND OTHERS FOR THE VACATION OF ONE COUNTY ROAD AND THE LOCATION OF TWO COUNTY ROADS IN TOWNSHIPS 18-11 AND 18-12 [PACKET 141 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 3, 1879, WAS ESTABLISHED AS 40 FEET WIDE ON OCTOBER 6, 1879, AND WAS RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-17-11 AT THE TOWNSHIP CORNER ON THE SECOND ROAD ON THIS ROAD SURVEY. THE ROAD **VACATED** WAS ALL THAT PORTION OF THE COUNTY ROAD NOW LOCATED THAT LIES BETWEEN THE NORTHWEST CORNER OF SECTION 24-18-11 AND WHERE IT CROSSES THE SECTION LINE ON THE EAST LINE OF SECTION 12-18-11 ON THE RANGE LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 26-17-11 TO COMMENCE THIS SECOND ROAD
  - 2) THIS SECOND ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE INTERSECTION OF THE EMPORIA AND LAWRENCE STATE ROAD, LOCATED 5,110' SOUTH TO THE NORTHEAST CORNER OF SECTION 24-18-11, AND THE TERMINUS OF THIS SECOND ROAD
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 103 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 414 TO 416 PETITION BY JAMES WILLIAMS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS

17-11 AND 18-11 THAT HE SURVEYED ON DECEMBER 6, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 10, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 10, 1881 BY WILLIAM F. EWING. COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-18-11 AT THE TOWNSHIP CORNER TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE TO A HICKORY TREE AT 745 FEET WEST OF THE NORTH 1/4 CORNER OF SECTION 1-18-11 AT AN ANGLE TO THE SOUTHWESTERLY; THEN INTERSECTS THE TOWNSHIP LINE AT A POINT 1,249 FEET EAST OF THE NORTHWEST CORNER OF SECTION 1-18-11; THEN CONTINUES WEST ON THE TOWNSHIP LINE TO THE NORTHWEST CORNER OF SECTION 3-18-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 196 DATED DECEMBER 6, 1880, FOR A ROAD SURVEY IN TOWNSHIP 18-11 APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-18-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE TO A HICKORY TREE AT 745 FEET WEST OF THE NORTH 1/4 CORNER OF SECTION 1-18-11 AT AN ANGLE TO THE SOUTHWESTERLY; THEN INTERSECTS THE TOWNSHIP LINE AT A POINT 1,249 FEET EAST OF THE NORTHWEST CORNER OF SECTION 1-18-11; THEN CONTINUES WEST ON THE TOWNSHIP LINE TO THE NORTHWEST CORNER OF SECTION 3-18-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 39, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 91 DATED JUNE 7, 1886 FOR A ROAD ON THE TOWNSHIP LINE BETWEEN TOWNSHIPS 17 & 18, RANGE 12 FOR W. S. HAMPTON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE SOUTHWEST CORNER OF SECTION 31-17-12 TO BEGIN THIS ROAD SURVEY. HE NOTED THAT STONES WERE SET AT THE END OF EACH MILE ON THIS ROAD SURVEY AND PROPERLY MARKED. NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 2 MILES AND 22.70 CHAINS TO THE STONE MARKED "R" HE SET AT THE TERMINUS OF THIS ROAD SURVEY, AT THE INTERSECTION OF THE LAWRENCE AND EMPORIA STATE ROAD

- 7) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 329 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 266 TO 268 PETITIONED BY W. S. HAMPTON AND OTHERS FOR A ROAD ON THE TOWNSHIP LINE BETWEEN TOWNSHIPS 17-12 & 18-2 [PACKET 583 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 7, 1886, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 13, 1886 AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 9, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE SOUTHWEST CORNER OF SECTION 31-17-12 TO BEGIN THIS ROAD SURVEY. HE NOTED THAT "MILE STONES WERE SET IN THEIR RESPECTIVE PLACES AND PROPERLY MARKED".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 2 MILES, 22 CHAINS AND 70 LINKS TO THE ROAD STONE MARKED "R" HE SET AT THE

INTERSECTION OF THE LAWRENCE AND EMPORIA ROAD AT THE TERMINUS OF THIS ROAD SURVEY IN THE SOUTHWEST 1/4 OF SECTION 33-17-12

- 8) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 23, 1983, SAID THAT **HE FOUND A 1/2" REBAR OF UNCERTAIN ORIGIN** AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-17-11.
- 1) 35.1' NW TO A SPIKE & WASHER IN A POWER POLE
  - 2) 2.0' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 3) 46.5' SE TO A SPIKE & WASHER IN A TELEPHONE POLE
  - 4) 20.6' WEST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,641.95' NORTH ON THE RANGE LINE TO THE McAULEY STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 36-17-11
  - 2) 5,283.90' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 36-17-11
- 9) LLOYD J. DOBLER, L.S. 541 IN SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED AUGUST 26, 1983 FOR A SURVEY OF A 2.0+ ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 1-18-11 FOR CAROL DARRETT, SHOWS ON HIS SURVEY DRAWING A **"PIN SET BY LYON COUNTY"** AT THE TOWNSHIP CORNER AT THE NORTHEAST CORNER OF SECTION 1-18-11. THERE ARE NO TIES ON THE SURVEY AND THE SURVEY IS NOT SEALED.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,629.15' SOUTH ON THE RANGE LINE TO THE "PIN SET BY LYON COUNTY" HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 1-18-11
  - 2) 2,750.15' SOUTH ON THE RANGE LINE TO THE PIN HE SET FOR THE SOUTHEAST CORNER OF THE 2.0 ACRE TRACT
  - 3) 5,279.00' SOUTH ON THE RANGE LINE TO THE "PIN SET BY LYON COUNTY" HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-18-11
- 10) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 9, 1985, FOR PROJECT NUMBER 85113, SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO REESTABLISH THE WEST LINE OF SECTION 36-17-11, SAID THAT **HE FOUND A 1/2" REBAR OF UNCERTAIN ORIGIN** AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-17-11. THIS SURVEY WAS RECORDED IN VOLUME 418 ON PAGE 13 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 22, 1985.
- 1) 35.1' NW TO A SPIKE & WASHER IN A POWER POLE
  - 2) 2.0' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 3) 46.5' SE TO A SPIKE & WASHER IN A TELEPHONE POLE
  - 4) 20.6' WEST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,641.72' NORTH ON THE RANGE LINE TO THE McAULEY STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 36-17-11
  - 2) 5,283.88' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11
  - 3) 5,255.6' WEST ON THE TOWNSHIP LINE TO THE 5/8" SQUARE REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-17-11, ATTRIBUTABLE TO AI CHAMNESS
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 1989, SAID THAT **HE FOUND AND ACCEPTED THE 1/2" REBAR** AT THE SOUTHEAST CORNER OF SECTION 36-17-11 ON THE TOWNSHIP LINE.

HIS TIES ARE ON PAGE 4

- 1) 32.8' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 2) 34.6' NW TO A SPIKE IN A POWER POLE
  - 3) 21.0' WEST TO A LINE OF FENCE TO THE SOUTH
  - 4) 23.0' NORTH TO A LINE OF FENCE TO THE WEST
  - 5) IN THE CENTERLINE TRAVELED WAY OF ROADS NORTH-SOUTH-EAST-WEST
- 12) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 3, 1995, FOR BRIDGE REPLACEMENT PROJECT NUMBER 95-1G, **FOUND THE 1/2" REBAR AT 6" BELOW THE ROAD SURFACE** AT THE SOUTHEAST CORNER OF SECTION 36-17-11 ON THE TOWNSHIP LINE FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED OCTOBER 18, 1989 WHEN HE ACCEPTED THIS 1/2" REBAR AS THE SOUTHEAST CORNER OF SECTION 36-17-11.
- 1) 38.53' NE TO A PK NAIL & WASHER IN THE SOUTHEAST FACE OF A CORNER FENCE POST
  - 2) 33.32' SE TO A PK NAIL & 2 WASHERS IN THE TOP OF A CORNER FENCE POST
  - 3) 35.35' NW TO A PK NAIL & WASHER IN THE SOUTHWEST FACE OF A POWER POLE
  - 4) IN THE TRAVELED WAYS OF COUNTY ROAD 190 EAST-WEST AND COUNTY ROAD "N" NORTH-SOUTH
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED AUGUST 20, 1996, FOR PROJECT NUMBER 94406-02, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHEAST CORNER OF SECTION 1-18-11 ON THE TOWNSHIP LINE FROM HIS TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED AUGUST 1985 AND OCTOBER 1989.
- 1) 38.5' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 2) 35.5' NW TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 3) 45.0' ESE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 4) 73.6' SSW TO THE NORTHWEST CORNER OF A REINFORCED CONCRETE BOX CULVERT HEADWALL
- 14) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9 AND MAY 30, 1997, FOR JOB NUMBER 96201-02, SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 18-12, TO SURVEY THE SOUTH HALF OF THE FRACTIONAL SOUTHWEST QUARTER OF SECTION 6-18-12 FOR MARGE KEARN, SAID THAT **SHE FOUND THE 1/2" REBAR** AT THE NORTHWEST CORNER OF SECTION 6-18-12 ON THE TOWNSHIP LINE FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 35.1' NW TO A SPIKE & WASHER IN A POWER POLE
  - 2) 46.5' SE TO A SPIKE & WASHER IN A TELEPHONE POLE
  - 3) 20.6' WEST TO A LINE OF FENCE TO THE SOUTH-EXTENDED
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,249.08' EAST ON THE TOWNSHIP LINE TO THE GLO STONE SHE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-18-12 WITH A 1/2" REBAR WITH HER "LS 1130" CAP ABOVE THE STONE,
  - 2) 4,891.15' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR SHE FOUND AT THE NORTHEAST CORNER OF SECTION 6-18-12
  - 3) 2,629.11' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-18-12
  - 4) 3,954.05' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SW 1/4 OF SECTION 6-18-12
  - 5) 5,278.99' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-18-12

CONTINUED ON PAGE 5

- 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 1997, FOR PROJECT NUMBER 97297-02 FOR LYON COUNTY BRIDGE REPLACEMENT PROJECT NUMBER 97-9U, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHWEST CORNER OF SECTION 6-18-12 ON THE TOWNSHIP LINE FROM HIS TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED AUGUST 1996.
- 1) 38.5' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 2) 35.5' NW TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 3) 45.0' ESE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 4) 73.6' SSW TO THE NORTHWEST CORNER OF A REINFORCED CONCRETE BOX CULVERT HUBGUARD
- 16) DAVID L. NEWTON. L.S. 1345, OF WILSON & COMPANY, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 13, 2003, FOR KDOT PROJECT NUMBER 99-56-K9440-01, THE REPLACEMENT OF K-99 BRIDGE 049 OVER THE KANSAS TURNPIKE, SURVEY F01010 IN THE SURVEY FILE FOR TOWNSHIP 18-11, SAID THAT **FOUND THE 1/2" IRON BAR [0.40' DEEP]** AT THE NORTHEAST CORNER OF SECTION 1-18-11 ON THE TOWNSHIP LINE FROM A LAND SURVEY REFERENCE REPORT, KANSAS STATE HISTORICAL SOCIETY DOCUMENT NUMBER 971157, DATED JUNE 2, 1997, AND DOCUMENT NUMBER 000586, DATED OCTOBER 7, 1985. POINT NUMBER 15011.
- 1) 35.30' NORTHWEST TO A FOUND PK NAIL & WASHER IN A POWER POLE [35.1' RECORD]
  - 2) 38.35' NORTHEAST TO A FOUND PK NAIL & WASHER IN THE SOUTHEAST SIDE OF A CORNER FENCE POST [38.5' RECORD]
  - 3) 33.60' SOUTHEAST TO A FOUND PK NAIL & WASHER IN THE TOP OF A CORNER FENCE POST [NO RECORD]
  - 4) 45.10' EAST-SOUTHEAST TO THE TOP OF A TELEPHONE PEDESTAL [45.0' RECORD]
  - 5) 20.5' WEST TO A LINE OF FENCE TO THE SOUTH [20.6' RECORD]
  - 6) 1.0' EAST TO THE CENTERLINE TRAVELED WAY NORTH-SOUTH [COUNTY ROAD "N"]
  - 7) AT THE INTERSECTION OF COUNTY ROAD "N" AND COUNTY ROAD 250
  - 8) KANSAS STATE PLANE SOUTH ZONE- FEET  
NORTH = 1996074.577000      EAST = 1989454.625000
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,627.93' WEST ON THE TOWNSHIP LINE TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 1-18-11
  - 2) 5,255.86' WEST ON THE TOWNSHIP LINE TO THE 5/8" IRON BAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 1-18-11
  - 3) 2,629.19' SOUTH ON THE RANGE LINE TO THE 5/8" IRON BAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 1-18-11
  - 4) 5,279.05' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-18-11
  - 5) 7,914.67' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-1'8-11
  - 6) 10,549.98' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-18-11
- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 03, 2008 FOR PROJECT NUMBER 07358-02, SURVEY F01011 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE WEST LINE OF A PREVIOUSLY DESCRIBED TRACT IN THE SOUTHEAST 1/4 OF SECTION 1-18-11 FOR DON BOYCE, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHEAST CORNER OF SECTION 1-18-11 AT THE TOWNSHIP CORNER FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

HIS TIES ARE ON PAGE 6

- 1) 35.3' NW TO A MAG NAIL & WASHER IN A POWER POLE
- 2) 38.5' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
- 3) 33.6' SE TO A PK NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 45.1' ESE TO THE TOP OF A TELEPHONE PEDESTAL
- 5) 1.0' EAST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "N" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,629.11' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 1-18-11
- 2) 5,279.03' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 1-18-11
- 3) 2,627.92' WEST ON THE TOWNSHIP LINE TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 1-18-11
- 4) 5,255.85' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 1-18-11

NORTHWEST CORNER 06-18-12