

**WEST 1/4 CORNER SECTION 06, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 71 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 6"** FOR THE WEST 1/4 CORNER OF SECTION 6-18-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 12, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE RANGE LINE TO THE 16" X 16" X 4" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 11 & 12 EAST AT THE NORTHWEST CORNER OF SEC. 6-19-12
  - 2) 40.00 CHAINS SOUTH ON THE RANGE LINE TO THE 18" X 9" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-18-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 34 RECORDED IN SURVEY BOOK "A" ON PAGE 129 DATED APRIL 22, 1868 TO SURVEY ROSYENE'S LAND, BEING 5 ACRES IN SECTION 25-17-11 AND THE NORTHEAST 1/4 OF SECTION 1-18-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 322 RODS, 19 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 1-18-11
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 22, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 22 DATED APRIL 2, 1884, AT THE REQUEST OF J. H. GILLILAND TO ESTABLISH THE CENTER CORNER OF SECTION 1-18-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 26, 1983, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER OVER A LARGE AREA FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE BETWEEN THE NORTHEAST CORNER AND THE SOUTHEAST CORNER OF SECTION 1-18-11, AND IN LINE WITH A HEDGE AND A FENCE TO THE WEST.
- 1) 25.7' EAST TO A LINE OF FENCE TO THE NORTH
  - 2) 23.4' WEST TO A LINE OF FENCE TO THE NORTH
  - 3) 16.5' NORTH TO A LINE OF FENCE TO THE EAST-EXTENDED
  - 4) 43.3' SW TO A SPIKE & WASHER IN A POWER POLE
  - 5) 2' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH

- 5) LLOYD J. DOBLER, L.S. 541 IN SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 18-11 DATED AUGUST 26, 1983 FOR A SURVEY OF A 2.0+ ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 1-18-11 FOR CAROL DARRETT, SHOWS ON HIS SURVEY DRAWING A **"PIN SET BY LYON COUNTY"** AT THE NORTHEAST CORNER THE SOUTHEAST 1/4 OF SECTION 1-18-11 ON THE RANGE LINE. THERE ARE NO TIES ON THE SURVEY OR THE SURVEY TIE FILES, AND THE SURVEY IS NOT SIGNED OR SEALED.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,629.15' NORTH ON THE RANGE LINE TO THE "PIN SET BY LYON COUNTY" HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-18-11 AT THE TOWNSHIP CORNER
- 2) 121.00' SOUTH ON THE RANGE LINE TO THE "PIN" HE SET FOR THE SOUTHEAST CORNER OF THE 2.0 ACRE TRACT

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,649.85' SOUTH ON THE RANGE LINE TO THE "PIN SET BY LYON COUNTY" HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-18-11
  - 4) 720.00' WEST TO THE "PIN" HE SET FOR THE NORTHWEST CORNER OF THE 2.0 ACRE TRACT
  - 5) 5,310.06' WEST TO THE "PIN SET BY LYON COUNTY" HE FOUND AT THE WEST 1/4 CORNER OF SECTION 1-18-11
- 6) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9 AND MAY 30, 1997, FOR JOB NUMBER 96201-02, SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 18-12, TO SURVEY THE SOUTH HALF OF THE FRACTIONAL SOUTHWEST QUARTER OF SECTION 6-18-12 FOR MARGE KEARN, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 6-18-12 ON THE RANGE LINE FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S 752, DATED AUGUST 1983.
- 1) 23.2' WEST TO A NAIL & WASHER IN A CORNER FENCE POST
  - 2) 42.9' SW TO A NAIL & WASHER IN A POWER POLE
  - 3) 30.7' SSE TO A NAIL & WASHER IN A FENCE POST
  - 4) 27.4' ENE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 5) 2.0' EAST TO THE TRAVELED WAY OF COUNTY ROAD "N" NORTH-SOUTH
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,324.94' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 6-18-11
  - 2) 2,649.88' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-18-11
  - 3) 2,629.11' NORTH ON THE RANGE LINE TO THE 1/2" REBAR SHE FOUND AT THE NORTHWEST CORNER OF SECTION 6-18-11 AT THE TOWNSHIP CORNER
  - 4) 2,246.80' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 6-18-11
  - 5) 4,895.99' EAST TO THE 5/8" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE EAST 1/4 CORNER OF SECTION 6-18-11
- 7) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 12, 1998, SAID THAT THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED MAY 1997.
- 1) 23.2' WEST TO A SPIKE & WASHER IN A CORNER FENCE POST
  - 2) 43.0' SW TO A SPIKE & WASHER IN A POWER POLE
  - 3) 30.6' SE TO A SPIKE & WASHER IN A FENCE POST
- 8) DAVID L. NEWTON. L.S. 1345, OF WILSON & COMPANY, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 13, 2003, FOR KDOT PROJECT NUMBER 99-56-K9440-01, THE REPLACEMENT OF K-99 BRIDGE 049 OVER THE KANSAS TURNPIKE, SURVEY F01010 IN THE SURVEY FILE FOR TOWNSHIP 18-11, SAID THAT **HE FOUND A 5/8" IRON BAR [0.40' DEEP]** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE. HE SAID THAT EVIDENCE OF THE YELLOW CAP WAS DESTROYED. THIS REBAR WAS FOUND FROM LAND SURVEY REFERENCE REPORT, KANSAS STATE HISTORICAL SOCIETY DOCUMENT NUMBER 971157, DATED JUNE 2, 1997. POINT NUMBER 16011.
- 1) 30.65' SOUTH SOUTHEAST TO A FOUND NAIL & SHINER IN A FENCE POST [30.7' RECORD]
  - 2) 27.60' EAST NORTHEAST TO THE TOP OF A TELEPHONE PEDESTAL [27.4' RECORD]

HIS TIES ARE CONTINUED ON PAGE 3

- 3) 42.80' SOUTHWEST TO A SET MAG NAIL & SHINER IN THE NORTHWEST SIDE OF A POWER POLE
- 4) 23.0' WEST TO THE EAST SIDE OF A STEEL FENCE POST
- 5) 2.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "N" [2.0' RECORD]
- 6) KANSAS STATE PLANE SOUTH ZONE—FEET  
NORTH = 1993445.909000 EAST = 1989498.125000

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,629.19' NORTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-18-11 AT THE TOWNSHIP CORNER
- 2) 2,649.86' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-18-11
- 3) 5,285.48' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-18-11
- 4) 7,920.79' SOUTH ON THE RANGE LINE TO THE 1/2" IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-18-11
- 5) 5,302.39' WEST TO THE 5/8" IRON BAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 1-18-11

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 3, 2008 FOR PROJECT NUMBER 07358-02, SURVEY F01011 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE WEST LINE OF A PREVIOUSLY DESCRIBED TRACT IN THE SOUTHEAST 1/4 OF SECTION 1-18-11 FOR DON BOYCE, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 27.6' ENE TO THE TOP OF A TELEPHONE PEDESTAL
- 2) 42.95' SW TO A MAG NAIL & SHINER IN A POWER POLE
- 3) 22.9' WEST TO THE NEAR FACE OF A PIPE CORNER FENCE POST
- 4) 3.8' SOUTH TO A LINE OF PIPE FENCE TO THE WEST
- 5) 16.3' NORTH TO A LINE OF FENCE TO THE EAST
- 6) 4.5' EAST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "N" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,629.11' NORTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 1-18-11 AT THE TOWNSHIP CORNER
- 2) 2,649.92' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 1-18-11
- 3) 2,651.49' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 1-18-11
- 4) 5,302.26' WEST TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 1-18-11

- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 28, 2010 FOR PROJECT NUMBER 10327-02, SURVEY F01012 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 17.72 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 1-18-11 FOR ANDREW BOYCE, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE EAST 1/4 CORNER OF SECTION 1-18-11 ON THE RANGE LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE. HE NOTED THAT HE SET THIS REBAR IN 1983.

- 1) 27.5' ENE TO THE TOP CENTERLINE TRAVELED WAY OF ROAD
- 2) 42.45' SW TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 22.9' WET TO THE NEAR FACE OF A PIPE CORNER FENCE POST
- 4) 16.3' NORTH TO A FENCE LINE TO THE EAST

HIS TIES ARE CONTINUED ON PAGE 4

- 5) 3.8' SOUTH TO A PIPE FENCE TO THE WEST
- 6) 4.5' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD  
"N" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,325.73' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 1-18-11
- 2) 5,302.33' WEST TO A 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 1-18-11
- 3) 2,649.99' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 1-18-11

WEST QUARTER CORNER 06-18-12